

lssue:	AN ORDINANCE OF THE COUNCIL OF THE CITY OF NIXA AUTHORIZING THE DIRECTOR OF PLANNING AND DEVELOPMENT TO ACCEPT THE DEDICATIO OF PUBLIC STREETS AND EASEMENT TO THE CITY OF NIXA, AS SHOWN ON THE PRELIMINARY PLAT OF THE WALKER WOODS SUBDIVISION, GENERALLY LOCATED AT THE NORTHEAST CORNER OF THE INTERSECTION OF MAIN STREET AND TRACKER ROAD, UPON THE APPLICANT FILING AND RECORDING A FINAL PLAT THAT SUBSTANTIALLY CONFORMS TO THE PRELIMINARY PLAT; AND AUTHORIZING THE CITY CLERK TO SIGN THE FINAL PLAT UPON COMPLIANCE WITH ALL THE TERMS OF THIS ORDINANCE.	
Date:	August 23, 2021	
Submitted By:	Garrett Tyson, Director of Planning and Development	

Background

The Walker Woods subdivision is a mixed-use subdivision located within the R-1 single-family residential and General Commercial (GC) zoning districts. The subject property was annexed into the Nixa City Limits in 2021 and the existing zoning arrangement was established at that time. The property owner has submitted a preliminary plat illustrating the proposed arrangement of new lots and the public infrastructure required to serve them.

Preliminary plats are a means to provide subdivision developers with an initial approval concerning compliance of the planned arrangement with the City's zoning, subdivision, and other pertinent regulations prior to engaging the more expensive actions of detailed engineering and construction.

<u>Analysis</u>

The Walker Woods subdivision proposes to create 54 single-family residential lots that are all planned to be served by public streets, municipal water, municipal sanitary sewer, and municipal electric services. Additionally, the subdivision will create two lots within the General Commercial (GC) zoning district and four common areas containing sinkholes that also function as part of the subdivision's overall stormwater management scheme. The common areas will be owned and maintained by an association of property owners within the subdivision.

Recommendation

Staff has reviewed the preliminary plat and has determined the document to be in substantial conformance with the applicable regulations of the Nixa City Code concerning major subdivisions within the R-1 and GC zoning districts.

1	AN ORDINANCE OF THE COUNCIL OF THE CITY OF NIXA APPROVING THE
2	PRELIMINARY PLAT OF THE WALKER WOODS SUBDIVISION GENERALLY
3	LOCATED AT THE NORTHEAST CORNER OF THE INTERSECTION OF MAIN
4	STREET AND TRACKER ROAD AND AUTHORIZING CERTAIN CITY OFFICIALS TO
5	TAKE CERTAIN ACTIONS UPON THE FILING OF A FINAL PLAT.
6	
7	
8	WHEREAS an original Preliminary Plat of the Walker Woods Subdivision dated
9	June 18, 2021, is on file with the City's Department of Planning and Development
10	("Preliminary Plat"); and
11	
12	WHEREAS the Department of Planning and Development has issued a staff
13	report finding the Preliminary Plat to be in substantial compliance with the requirement
14	of the Nixa City Code; and
15	
16	WHEREAS the Planning and Zoning Commission considered the Preliminary
17	Plat at their meeting on August 2, 2021; and
18	
19	WHEREAS the Commission, after considering the Preliminary Plat, staff's
20	recommendation regarding the Application, and after holding a public hearing on the
21	Application, issued a recommendation of approval of the Preliminary Plat; and
22	
23	WHEREAS the City Council, now having considered the Preliminary Plat, staff's
24	recommendation regarding the Application, and after providing an opportunity for public
25	comment on the Preliminary Plat, now desires to approve the Preliminary Plat; and
26	
27	WHEREAS the City Council desires to authorize the Director of Planning and
28	Development and City Clerk to take certain actions consistent with this Ordinance.
29	
30	NOW, THEREFORE, BE IT ORDAINED BY THE COUNCIL OF THE CITY OF
31	NIXA, AS FOLLOWS, THAT:
32	
33	SECTION 1: City Council hereby approves the Preliminary Plat of the Walker
34	Woods Subdivision which is generally located at the northeast corner of the intersection
35	of Main Street and Tracker Road, as approved by the Planning and Zoning
36	Commission. The original preliminary plat of the Walker Woods Subdivision is on file in
37	the Department of Planning and Development, a reduced version of which is attached
38	hereto for general reference as "Council Bill Exhibit A." All of "Council Bill Exhibit A"
39	including any referenced attachments, is hereby incorporated herein by this reference.
40	
41	SECTION 2: The Director of Planning and Development, on behalf of the City of
42	Nixa, is hereby authorized to accept the land, easements, and improvements dedicated
43	to the City, as shown on the Preliminary Plat of the Walker Woods Subdivision, upon:
44	(1) the applicant filing and recording a final plat which is in accordance with this
45	Ordinance, including any conditions attached to and described in "Council Bill Exhibit
46	A," and the Subdivision Regulations of the City and said final plat shall substantially

ORDINANCE NO.

conform to the Preliminary Plat, and (2) upon the Director of Public Works certifying to the Director of Planning and Development that the public improvements have been made in accordance with the City standards and specifications. Said public improvements shall not be accepted until the occurrence of the above written conditions. **SECTION 3:** The final plat shall not be recorded until: (1) the public improvements relating to the Preliminary Plat have been constructed according to the specifications of the City of Nixa, Missouri, and are approved by the Director of Public Works, and all engineering fees, permit fees, licenses, and other fees occasioned by or in connection with the construction of said improvements have been paid to the City; or (2) in lieu of construction of the improvements, that the Developer has filed with the Planning and Development Director, according to the terms of the Subdivision Regulations of the City, the prescribed financial assurances in a form acceptable to the City to ensure the construction of the improvements and the payment to the City of all engineering fees, permit fees, licenses, and other fees occasioned by, or which will be occasioned by, the construction of the improvements. **SECTION 4:** Upon compliance with all the requirement of this Ordinance. including any conditions described in "Council Exhibit A", the City Clerk is hereby authorized to endorse the City Council's approval upon the final plat pursuant to Section 445.030 RSMo., and such endorsement shall constitute the acceptance of the Public Improvements contained therein. SECTION 5: This Ordinance shall be in full force and effect from and after its final passage by the City Council and after its approval by the Mayor, subject to the provisions of section 3.11(g) of the City Charter. [Remainder of page intentionally left blank. Signatures follow on the next page.]

93	ADOPTED BY THE CITY CO	UNCIL THIS 23 RD DAY OF AUGUST 2021.	
94			
95 96	ATTEST		
97			
98			
99 100	CITY CLERK	PRESIDING OFFICER	
100			
102	APPROVED BY THE MAYOR	R THIS DAY OF	_ 2021.
103			
104	ATTEST.		
106			
107			
108	CITY CLERK	MAYOR	
109			
111	APPROVED AS TO FORM:		
112			
113 114	CITY ATTORNEY		



SINGLE FAMILY RESIDENTIAL DISTRICT			
LOT #	SQ. FT.	AC.	
1	10,047	0.23	
2	10,010	0.23	
3	11,440	0.26	
4	11,440	0.26	
5	11,356	0.26	
6	14,074	0.32	
7	13,396	0.31	
8	12,758	0.29	
9	13,842	0.32	
10	10,010	0.23	
11	10,010	0.23	
12	10,000	0.23	
13	15,384	0.35	
14	11,416	0.26	
15	8,925	0.20	
16	9,608	0.22	
17	10,673	0.25	
18	10.220	0.23	

SINGLE FAMILY RESIDENTIAL DISTRICT			
LOT #	SQ. FT.	AC.	
19	16.548	0.38	

10	10,040	0.00
20	20,611	0.47
21	10,010	0.23
22	10,010	0.23
23	15,259	0.35
24	10,886	0.25
25	10,010	0.23
26	10,970	0.25
27	12,373	0.28
28	16,187	0.37
29	16,812	0.39
30	11,354	0.26
31	11,507	0.26
32	11,520	0.26
33	11,520	0.26
34	11,520	0.26
35	11,520	0.26
36	12,022	0.28

SINGLE FAMILY RESIDENTIAL DISTRI			
LOT #	SQ. FT.	AC.	
37	13,898	0.32	
38	12,284	0.28	
39	12,493	0.29	
40	14,007	0.32	
41	14,984	0.34	
42	10,010	0.23	
43	10,010	0.23	
44	10,578	0.24	
45	11,175	0.26	
46	11,018	0.25	
47	9,724	0.22	
48	9,724	0.22	
49	9,724	0.22	
50	9,724	0.22	
51	9,724	0.22	
52	9,724	0.22	
53	9,724	0.22	
54	9,857	0.23	

GENERAL COMMERCIAL				
LOT #	SQ. FT.	AC.		
GC1	55,264	1.27		
GC2	44,979	1.03		
LOT #	SQ. FT.	AC.		
C1	25.676	0.59		
C2	83,615	1.92		
C3	85,198	1.96		

COMMUNITY PANEL NO. 29043C0060C, WHICH BEARS AN EFFECTIVE DATE OF DECEMBER 17, 2010. THE SINKHOLE FLOOD OUTLINES SHOWN FOR THE 100-YEAR AND 500-YEAR FLOODPLAINS ARE BASED ON THE PRELIMINARY FIRM PANEL 29043C0058D, WITH A PRELIMINARY DATE OF 2019/09/20

DECLARATION BY SURVEYOR

I, JOSEPH R. PULLIAM, DO HEREBY CERTIFY THAT THIS PRELIMINARY PLAT WAS PREPARED UNDER MY PERSONAL SUPERVISION FROM AN ACTUAL SURVEY OF THE LAND HEREIN, IN ACCORDANCE WITH THE CURRENT MISSOURI STANDARDS FOR PROPERTY BOUNDARY SURVEYS.

PHYSICAL EVIDENCE OF IMPROVEMENTS IS SHOWN FROM INFORMATION TAKEN BY VISUAL INSPECTION OF THE PREMISES. EASEMENTS SHOWN ARE THOSE WRITTEN, PROVIDED, OR DISCOVERED AND MAY NOT BE ALL INCLUSIVE. APPARENT OWNERSHIPS AS SHOWN ARE BASED UPON INFORMATION PROVIDED BY OTHERS AND DO NOT REPRESENT AN OPINION AS TO TITLE. THIS PRELIMINARY PLAT IS INTENDED FOR REVIEW AND PLANNING PURPOSES ONLY AND IS NOT TO BE USED BY ANYONE FOR CONVEYANCE OF LANDS OR TITLE OF REAL ESTATE.

COMMON AREA

COMMON AREAS DEPICTED ON THIS SUBDIVISION PLAT AS LOTS C1 THROUGH C4 SHALL BE CONVEYED IN FEE-TITLE TO THE HOME OWNERS ASSOCIATION FOR SAID SUBDIVISION FOLLOWING COMPLETION OF CONSTRUCTION AND THE RECORDING OF FINAL PLAT THEREOF. THESE COMMON AREAS ARE HEREAFTER RESTRICTED FROM ADDITIONAL SUBDIVIDING OR FROM THE CONSTRUCTION AND/OR ERECTION OF ANY STRUCTURE WHETHER PERMANENT OR TEMPORARY. THESE AREAS ARE TO BE RESERVED AND SET ASIDE IN PERPETUITY AS "GREEN SPACE", THE ONLY PERMITTED USE OF SAID AREAS BEING THE INSTALLATION OF LANDSCAPING, INCLUDING THE PLANTING OF TREES, AND GENERAL MAINTENANCE ACTIVITIES SUCH AS MOWING AND DEBRIS REMOVAL. ALL TAXES, EXPENSES AND OTHER COST RELATED TO THESE COMMON AREAS ARE THE SOLE RESPONSIBILITY OF THE HOMEOWNERS ASSOCIATION.

DATE OF PREL TOTAL ACREA TOTAL NUMBE CURRENT ZON

PROPOSED ZO R-1 SMALLEST R-1 LARGEST

NOTES

- 4.

LEGEND

 ADJOINING PROPERTY LINE
 UTILITY EASEMENT LINE
 SETBACK LINE
 SINKHOLE BOUNDARY
SINKHOLE

-----(NO CONSTRUCTION LIMITS)

PRELIMINARY PLAT WALKER WOODS SUBDIVISION A SUBDIVISION IN THE SOUTHEAST QUARTER OF THE SOUTHEAST QUARTER OF SECTION 1. TOWNSHIP 27 NORTH

RANGE 22 WEST OF THE FIFTH PRINCIPAL MERIDIAN, CITY OF NIXA, CHRISTIAN COUNTY, STATE OF MISSOURI.

OWNER: DON E. WALKER AND LOIS M. WALKER

DEVELOPER: MORELOCK BUILDERS & ASSOCIATES

722 W. OLIVE STREET SPRINGFIELD, MISSOURI 65806



PROPERTY DESCRIPTION

ALL THAT PART OF THE SOUTHEAST QUARTER OF THE SOUTHWEST QUARTER OF SECTION 1 - TOWNSHIP 27 NORTH - RANGE 22 WEST OF THE FIFTH PRINCIPAL MERIDIAN, CHRISTIAN COUNT, STATE OF MISSOURI, DESCRIBED AS FOLLOWS: COMMENCING AT THE SOUTHEAST CORNER OF SAID SOUTHEAST QUARTER OF THE SOUTHWEST QUARTER AND MEASURE N01°44'43"E ALONG THE EAST LINE THEREOF 1328 70 FEET TO THE NORTHEAST CORNER THEREOF: THENCE N87°47'06"W ALONG THE NORTH LINE THEREOF 15.0 FEET TO THE POINT OF BEGINNING: THENCE \$01°44'43"W 1308.54 FEET TO A POINT ON THE NORTH RIGHT OF WAY LINE OF TRACKER ROAD: (THE FOLLOWING FOLLOWS THE NORTH R/W OF TRACKER ROAD) THENCE N87°10'30"W 754.49 FEET: THENCE N02°59'28"E 23.57 FEET THENCE N87°04'01"W 490.18 FEET: THENCE N42°51'10"W 35.82 FEET TO A POINT ON THE EAST RIGHT OF WAY LINE OF MAIN STREET: (THE FOLLOWING FOLLOWS THE EAST R/W OF MAIN STREET) THENCE N01°27'03"E 339.90 FEET: THENCE N88°07'29"W 13.97 FEET; THENCE N02°01'18"E 242.62 FEET TO A POINT ON THE SOUTH LINE OF THE NORTHWEST QUARTER OF THE SOUTHEAST QUARTER OF THE SOUTHWEST QUARTER; THENCE S87°30'09"E ALONG THE SOUTH LINE THEREOF 631 22 FEET TO THE SOUTHEAST CORNER THEREOF. THENCE NO1°45'07"E ALONG THE EAST LINE THEREOF 661.06 FEET TO THE NORTHEAST CORNER THEREOF; THENCE S87°47'06"E ALONG THE NORTH LINE OF THE NORTHEAST QUARTER OF THE SOUTHEAST QUARTER OF THE SOUTHWEST QUARTER 652.40 FEET TO THE POINT OF BEGINNING, CONTAINING 28.39 ACRES.

LIMINARY PLA	T SUBMITTAL: JU	JNE 18, 2021
AGE OF THE DE	EVELOPMENT: 28	3.39
ER OF LOTS:	56	
NING:	R-1 (SINGLE FAMIL` GC (GENERAL COM	Y RESIDENTIAL DISTRICT) IMERCIAL)
ONING:	R-1 (SINGLE FAMIL` GC (GENERAL COM	Y RESIDENTIAL DISTRICT) IMERCIAL)
T LOT:	LOT 12, 10,000 SQU/	ARE FEET
LOT:	LOT 20, 20,611 SQU	ARE FEET

1. MINIMUM LOT WIDTH IS 60 FEET FOR R-1 (SINGLE FAMILY RESIDENTIAL DISTRICT). 2. MINIMUM LOT WIDTH IS NONE FOR GC (GENERAL COMMERCIAL).

3. MINIMUM LOT SIZE IS 6,600 SQUARE FEET.

R-1 (SINGLE FAMILY RESIDENTIAL DISTRICT) 25 FOOT BUILDING SETBACK LINE IN THE FRONT OF ALL LOTS. 20 FOOT BUILDING SETBACK LINE IN THE REAR OF ALL LOTS. 5 FOOT BUILDING SETBACK LINE ON THE SIDE OF ALL LOTS. 12 FOOT BUILDING SETBACK LINE ON THE SIDE OF ALL LOTS WITH LOCAL STREET FRONTAGE.

5. GC (GENERAL COMMERCIAL) 20 FOOT BUILDING SETBACK LINE IN THE FRONT OF ALL LOTS. 20 FOOT BUILDING SETBACK LINE IN THE REAR OF ALL LOTS. 10 FOOT BUILDING SETBACK LINE ON THE SIDE OF ALL LOTS

15 FOOT BUILDING SETBACK LINE ON THE SIDE OF ALL LOTS WITH LOCAL STREET FRONTAGE. 6. ROADS ARE TO BE DEDICATED FOR THE USE OF THE PUBLIC.

7. 10 FOOT UTILITY EASEMENT ON FRONT AND REAR OF ALL LOTS.

8. COMMON AREA (C1, C2, C3 & C4), ARE TO BE COMMON AREA.

9. APPROXIMATE LOCATION OF PROPOSED FIRE HYDRANT (TYPICAL).

10. PRELIMINARY SINKHOLE FLOOD OUTLINE FOR THE 100-YEAR FLOOD. SEE FLOOD PLAIN NOTE THIS SHEET. 11. PRELIMINARY SINKHOLE FLOOD OUTLINE FOR THE 500-YEAR FLOOD. SEE FLOOD PLAIN NOTE THIS SHEET. 12. APPROXIMATE LOCATION OF PROPOSED DETENTION AREAS (TYPICAL).

13. ROADS, UTILITIES AND OTHER ENGINEERING DESIGN ITEMS ARE SHOWN HEREON FOR PLANNING PURPOSES

ONLY AND WILL BE DESIGNED SEPARATELY BY LICENSED ENGINEER. 14. PRE-EXISTING STRUCTURE LOCATED ON LOTS 21 AND 22 EXEMPT FROM SETBACK REQUIREMENTS UNTIL SUCH TIME AS STRUCTURE IS REMOVED, ALL NEW STRUCTURES MUST CONFORM TO LOT SETBACKS.

15. NO DIRECT ACCESS TO TRACKER ROAD OR MAIN STREET FROM ADJOINING LOTS. ALL LOT ACCESS MUST BE FROM ADJOINING STREETS WITHIN SUBDIVISION INTERIOR.

> BASIS OF BEARING MISSOURI STATE PLANE NAD 83 CENTRAL ZONE VERTICAL DATUM = NAVD1988



NOTE: DRAWING REPRODUCTION AND SCALING MAY CHANGE THE INDICATED GRAPHIC SCALES H. SCALE: 1" = 100'



mo1call.com

JOSEPH R. PULLIAM - LAND SURVEYOR MO# PLS-2006016641 Ш C-001

Δ

Σ

ם

PULLIAN NUMBER 5-200601

COUNCIL BILL EXHIBIT A -ATTACHMENT 1

ENGINEER'S REPORT

WALKER ESTATES AND WALKER WOODS SUBDIVISION CITY OF NIXA, MISSOURI | SUMMER 2021



1550 E. REPUBLIC ROAD | SPRINGFIELD, MO 65804 | 417.888.0645 107 SE WASHINGTON ST | SUITE 465 | PORTLAND, OR 97214 | 503.946.6440 369 W HERMISTON AVE | HERMISTON, OR 97838 | 541-289-7000 TOTHASSOCIATES.COM

TABLE OF CONTENTS

INTF	ODUC	TION		1
Α.	STORMWATER DRAINAGE1			
	1.	Existi	ng Conditions	1
	2.	Storn	nwater Improvements	1
	3.	Deter	ntion	1
		a.	Detention Basins	1
		b.	Detention Volume	1
В.	WAT	ER SUF	PLY	1
	1.	Desig	n Flows	2
C.	ELEC	TRICAL	SUPPLY	2
D.	OTHE	ER UTIL	ITIES	2
E.	WASTEWATER DISPOSAL			
	1. Design Flows			
	2. Hydraulic Design			
	3. BOD			
F.	STREET IMPROVEMENTS			
	1.	Subd	ivision Streets	3
	2.	Trans	portation Impact Study	3
G.	PREL	IMINA	RY PLAT	3

EXHIBIT 1: WALKER WOODS SUBDIVISION PRELIMINARY PLAT EXHIBIT 2: WALKER ESTATES SUBDIVISION PRELIMINARY PLAT





INTRODUCTION

Walker Woods is a proposed 54 lot single family residential and 2 lot general commercial subdivision located at the northeast corner of the intersection of Main Street and Tracker Road in Nixa, Missouri. Walker Estates is a proposed 25 lot single family residential, 2 lot high-density multi-family, and single lot general commercial subdivision located at the southeast corner of the intersection of Main Street and Tracker Road in Nixa, Missouri. This Engineer's Report has been developed in accordance with the City of Nixa Technical Specification Manual. It summarizes the design of stormwater drainage, water, gas, electric and communications supply, wastewater disposal, traffic analysis, and planning data for the proposed subdivisions.

A. STORMWATER DRAINAGE

1. Existing Conditions

Based on topographic survey data and geotechnical investigation, stormwater currently flows primarily to one of ten of the sinkholes across the subject properties that are to be developed. The subject properties are currently undeveloped, and they have FEMA floodplains within some of the larger sinkholes, as shown on the Preliminary Plats. All runoff from the developable property drains to either a sinkhole or flows offsite to a drainage system.

2. Stormwater Improvements

The proposed subdivisions will have new 4-foot by 8-foot concrete curb inlets installed to address runoff in the right-of-way. The inlets will be spaced in compliance with City of Nixa design standards. Piping from the inlets that are placed under all paved areas will be reinforced concrete, and all other areas will utilize HDPE.

3. Detention

a. Detention Basins

Runoff from the site will be directed to multiple proposed storm water detention basins within a drainage area and near adjacent sinkholes. The basins will be sized to provide for both water quality and flood control. Flows from the basins will be released into adjacent sinkholes or into nearby storm systems at a rate less than the current undeveloped flow rates. This will ensure that individual sinkholes are not receiving excess runoff that could cause an increase in flood elevations in a post-development condition.

b. Detention Volume

The detention volume for the proposed subdivisions was calculated in compliance with the City of Nixa Technical Specification Manual. A 6-hour storm with a 25-year frequency was used to analyze stormwater runoff. The proposed subdivisions were delineated into drainage areas, and the curve numbers and times of concentration were calculated for each drainage area. The total estimated detention volume was then calculated by using HEC-1, producing a required volume of 258,300 cubic feet for the proposed subdivisions. Based on the initial layouts in the attached Preliminary Plats, the required value shall be achievable.

B. WATER SUPPLY

Water supply to the proposed subdivisions will be provided by the City of Nixa through multiple



connections to existing water mains on both the south side of Tracker Road and the west side of Main Street. Main lines will lie inside the right-of-way and service lines will run to each of the individual buildings and dwellings. Fire hydrants will be provided at each new intersection, at ends of mains, and spaced at 500 to 600 feet.

1. Design Flows

The design flows for this project are based on a full capacity of all residential units, houses, and businesses. A two person occupancy is assumed for each apartment unit. A 2.8 person occupancy is assumed for each single family house. A flow rate of 200 gallons per day per 1,000 square feet of floor area is assumed for commercial businesses. Flow Rate per person is estimated using a rate of 100 gallons per day. With a total of 79 single family dwellings, 95 apartment units, and 37,500 square feet of commercial businesses, the estimated average daily flow is equal to 48,700 gallons per day. Using a peaking factor of 4.00, the estimated peak daily flow is 194,800 gallons per day, giving a total flow of 135.3 gallons per minute.

C. ELECTRICAL SUPPLY

Electrical utilities for the proposed subdivisions will be provided by City of Nixa and will be underground.

D. OTHER UTILITIES

All other utilities (i.e. Natural Gas, Communication, Trash Services, etc.) for the proposed subdivisions will be provided by current utility providers that provide services inside the City of Nixa.

E. WASTEWATER DISPOSAL

The proposed subdivisions will be served with sewer by the City of Nixa through connection to an existing 8-inch public sewer main that crosses Tracker Road on the east side of the intersection with Main Street. New sewer mains will be extended to provide service line connections to each set of buildings and residential homes. Sewer from Walker Woods Subdivision will be directed to the existing manhole located at the northeast corner of the intersection of Main Street and Tracker Road, and sewer from Walker Estates Subdivision will be directed to the existing manhole located at the anticipated number of units is provided below.

1. Design Flows

2. The design flows for this project are based on a full capacity of all residential units, houses, and businesses. A two person occupancy is assumed for each apartment unit. A 2.8 person occupancy is assumed for each single family house. A flow rate of 200 gallons per day per 1,000 square feet of floor area is assumed for commercial businesses. Flow Rate per person is estimated using a rate of 100 gallons per day. With a total of 79 single family dwellings, 95 apartment units, and 37,500 square feet of commercial businesses, the estimated average daily flow is equal to 48,700 gallons per day. Using a peaking factor of 4.00, the estimated peak daily flow is 194,800 gallons per day, giving a total flow of 135.3 gallons per minute.

3. Hydraulic Design

The hydraulic design for this project is based on a full capacity of the proposed PVC (n = 0.011) sewer line, with a minimum slope of 0.5 percent. Using the Manning equation, the flow capacity in the 8-inch sewer main is 453 gallons per minute.



4. BOD

The BOD for this project is based on a loading of 0.22 pounds of BOD per person per day. From the design flows, a population equivalent was calculated to be 487. Using these values, the total BOD is estimated to be 107.1 pounds of BOD per day.

F. STREET IMPROVEMENTS

1. Subdivision Streets

The proposed subdivisions will have dedicated public streets designed to City of Nixa standards. Right-of-way is being provided to meet city requirements with a width of 50 feet. All streets will be new with a width of 27 feet (back of curb to back of curb). Storm inlets and drainage piping will be included with street design that will be designed to the City of Nixa standards. Sidewalks will also be installed in accordance with City of Nixa standards.

2. Transportation Impact Study

Based on the Transportation Impact Study, a recommendation has been made to install required pavement and striping for turn lanes at the following 3 intersections: Main Street and Mandy Lane, Donald Street and Tracker Road, and Maxine Avenue and Tracker Road. Please refer to Transportation Impact Study dated June 18, 2021, to see the detailed analysis and recommendation.

G. PRELIMINARY PLAT

The Preliminary Plats for both subdivisions were laid out in accordance with the City of Nixa standards and have each been signed by a Professional Land Surveyor licensed in the state of Missouri. Copies of each Preliminary Plat are included in this report as Exhibits 1 and 2.



EXHIBITS

- 1. WALKER WOODS SUBDIVISION PRELIMINARY PLAT
- 2. WALKER ESTATES SUBDIVISION PRELIMINARY PLAT





SINGLE FAMILY RESIDENTIAL DISTRICT			
LOT #	SQ. FT.	AC.	
1	10,047	0.23	
2	10,010	0.23	
3	11,440	0.26	
4	11,440	0.26	
5	11,356	0.26	
6	14,074	0.32	
7	13,396	0.31	
8	12,758	0.29	
9	13,842	0.32	
10	10,010	0.23	
11	10,010	0.23	
12	10,000	0.23	
13	15,384	0.35	
14	11,416	0.26	
15	8,925	0.20	
16	9,608	0.22	
17	10,673	0.25	
18	10.220	0.23	

SINGLE FA	MILY RESIDEN	TIAL DISTRICT
LOT #	SQ FT	AC

19	16,548	0.38
20	20,611	0.47
21	10,010	0.23
22	10,010	0.23
23	15,259	0.35
24	10,886	0.25
25	10,010	0.23
26	10,970	0.25
27	12,373	0.28
28	16,187	0.37
29	16,812	0.39
30	11,354	0.26
31	11,507	0.26
32	11,520	0.26
33	11,520	0.26
34	11,520	0.26
35	11,520	0.26
36	12,022	0.28

SINGLE FAMILY RESIDENTIAL DISTRIC						
LOT #	SQ. FT.	AC.				
37	13,898	0.32				
38	12,284	0.28				
39	12,493	0.29				
40	14,007	0.32				
41	14,984	0.34				
42	10,010	0.23				
43	10,010	0.23				
44	10,578	0.24				
45	11,175	0.26				
46	11,018	0.25				
47	9,724	0.22				
48	9,724	0.22				
49	9,724	0.22				
50	9,724	0.22				
51	9,724	0.22				
52	9,724	0.22				
53	9,724	0.22				
54	9,857	0.23				

GENERAL	COMMERCIAL	
LOT #	SQ. FT.	AC.
GC1	55,264	1.27
GC2	44,979	1.03
COMMON	I AREA SQ. FT.	AC.
C1	25,676	0.59
C2	83,615	1.92
C3	85,198	1.96
C4	149,140	3.42

DECLARATION BY SURVEYOR

I, JOSEPH R. PULLIAM, DO HEREBY CERTIFY THAT THIS PRELIMINARY PLAT WAS PREPARED UNDER MY PERSONAL SUPERVISION FROM AN ACTUAL SURVEY OF THE LAND HEREIN, IN ACCORDANCE WITH THE CURRENT MISSOURI STANDARDS FOR PROPERTY BOUNDARY SURVEYS.

PHYSICAL EVIDENCE OF IMPROVEMENTS IS SHOWN FROM INFORMATION TAKEN BY VISUAL INSPECTION OF THE PREMISES. EASEMENTS SHOWN ARE THOSE WRITTEN, PROVIDED, OR DISCOVERED AND MAY NOT BE ALL INCLUSIVE. APPARENT OWNERSHIPS AS SHOWN ARE BASED UPON INFORMATION PROVIDED BY OTHERS AND DO NOT REPRESENT AN OPINION AS TO TITLE. THIS PRELIMINARY PLAT IS INTENDED FOR REVIEW AND PLANNING PURPOSES ONLY AND IS NOT TO BE USED BY ANYONE FOR CONVEYANCE OF LANDS OR TITLE OF REAL ESTATE.

COMMON AREA

COMMON AREAS DEPICTED ON THIS SUBDIVISION PLAT AS LOTS C1 THROUGH C4 SHALL BE CONVEYED IN FEE-TITLE TO THE HOME OWNERS ASSOCIATION FOR SAID SUBDIVISION FOLLOWING COMPLETION OF CONSTRUCTION AND THE RECORDING OF FINAL PLAT THEREOF. THESE COMMON AREAS ARE HEREAFTER RESTRICTED FROM ADDITIONAL SUBDIVIDING OR FROM THE CONSTRUCTION AND/OR ERECTION OF ANY STRUCTURE WHETHER PERMANENT OR TEMPORARY. THESE AREAS ARE TO BE RESERVED AND SET ASIDE IN PERPETUITY AS "GREEN SPACE", THE ONLY PERMITTED USE OF SAID AREAS BEING THE INSTALLATION OF LANDSCAPING, INCLUDING THE PLANTING OF TREES, AND GENERAL MAINTENANCE ACTIVITIES SUCH AS MOWING AND DEBRIS REMOVAL. ALL TAXES, EXPENSES AND OTHER COST RELATED TO THESE COMMON AREAS ARE THE SOLE RESPONSIBILITY OF THE HOMEOWNERS ASSOCIATION.

LEGEND

----- ADJOINING PROPERTY LINE ----- UTILITY EASEMENT LINE SETBACK LINE _____ ____ _____ SINKHOLE BOUNDARY SINKHOLE

(NO CONSTRUCTION LIMITS)

PRELIMINARY PLAT WALKER WOODS SUBDIVISION A SUBDIVISION IN THE SOUTHEAST QUARTER OF THE SOUTHEAST QUARTER OF SECTION 1, TOWNSHIP 27 NORTH

RANGE 22 WEST OF THE FIFTH PRINCIPAL MERIDIAN, CITY OF NIXA, CHRISTIAN COUNTY, STATE OF MISSOURI.

OWNER: DON E. WALKER AND LOIS M. WALKER

DEVELOPER: MORELOCK BUILDERS & ASSOCIATES

722 W. OLIVE STREET SPRINGFIELD, MISSOURI 65806



PROPERTY DESCRIPTION

ALL THAT PART OF THE SOUTHEAST QUARTER OF THE SOUTHWEST QUARTER OF SECTION 1 - TOWNSHIP 27 NORTH - RANGE 22 WEST OF THE FIFTH PRINCIPAL MERIDIAN, CHRISTIAN COUNT, STATE OF MISSOURI, DESCRIBED AS FOLLOWS: COMMENCING AT THE SOUTHEAST CORNER OF SAID SOUTHEAST QUARTER OF THE SOUTHWEST QUARTER AND MEASURE N01°44'43"E ALONG THE EAST LINE THEREOF 1328.70 FEET TO THE NORTHEAST CORNER THEREOF: THENCE N87°47'06"W ALONG THE NORTH LINE THEREOF 15.0 FEET TO THE POINT OF BEGINNING: THENCE \$01°44'43"W 1308.54 FEET TO A POINT ON THE NORTH RIGHT OF WAY LINE OF TRACKER ROAD: (THE FOLLOWING FOLLOWS THE NORTH R/W OF TRACKER ROAD) THENCE N87°10'30"W 754.49 FEET: THENCE N02°59'28"E 23.57 FEET THENCE N87°04'01"W 490.18 FEET; THENCE N42°51'10"W 35.82 FEET TO A POINT ON THE EAST RIGHT OF WAY LINE OF MAIN STREET: (THE FOLLOWING FOLLOWS THE EAST R/W OF MAIN STREET) THENCE N01°27'03"E 339.90 FEET: THENCE N88°07'29"W 13.97 FEET; THENCE N02°01'18"E 242.62 FEET TO A POINT ON THE SOUTH LINE OF THE NORTHWEST QUARTER OF THE SOUTHEAST QUARTER OF THE SOUTHWEST QUARTER; THENCE S87°30'09"E ALONG THE SOUTH LINE THEREOF 631.22 FEET TO THE SOUTHEAST CORNER THEREOF: THENCE N01°45'07"E ALONG THE EAST LINE THEREOF 661.06 FEET TO THE NORTHEAST CORNER THEREOF; THENCE S87°47'06"E ALONG THE NORTH LINE OF THE NORTHEAST QUARTER OF THE SOUTHEAST QUARTER OF THE SOUTHWEST QUARTER 652.40 FEET TO THE POINT OF BEGINNING, CONTAINING 28.39 ACRES.

LIMINARY PLA	T SUBMITTAL:	JUNE 18, 2021
AGE OF THE DE	EVELOPMENT:	28.39
ER OF LOTS:	56	
NING:	R-1 (SINGLE FAN GC (GENERAL C	/ILY RESIDENTIAL DISTRICT) OMMERCIAL)
ONING:	R-1 (SINGLE FAN GC (GENERAL C	/ILY RESIDENTIAL DISTRICT) OMMERCIAL)
T LOT:	LOT 12, 10,000 SC	QUARE FEET
LOT:	LOT 20, 20,611 SC	QUARE FEET

1. MINIMUM LOT WIDTH IS 60 FEET FOR R-1 (SINGLE FAMILY RESIDENTIAL DISTRICT). 2. MINIMUM LOT WIDTH IS NONE FOR GC (GENERAL COMMERCIAL).

3. MINIMUM LOT SIZE IS 6,600 SQUARE FEET.

R-1 (SINGLE FAMILY RESIDENTIAL DISTRICT) 25 FOOT BUILDING SETBACK LINE IN THE FRONT OF ALL LOTS. 20 FOOT BUILDING SETBACK LINE IN THE REAR OF ALL LOTS. 5 FOOT BUILDING SETBACK LINE ON THE SIDE OF ALL LOTS. 12 FOOT BUILDING SETBACK LINE ON THE SIDE OF ALL LOTS WITH LOCAL STREET FRONTAGE.

20 FOOT BUILDING SETBACK LINE IN THE FRONT OF ALL LOTS. 20 FOOT BUILDING SETBACK LINE IN THE REAR OF ALL LOTS. 10 FOOT BUILDING SETBACK LINE ON THE SIDE OF ALL LOTS

15 FOOT BUILDING SETBACK LINE ON THE SIDE OF ALL LOTS WITH LOCAL STREET FRONTAGE. 6. ROADS ARE TO BE DEDICATED FOR THE USE OF THE PUBLIC.

7. 10 FOOT UTILITY EASEMENT ON FRONT AND REAR OF ALL LOTS.

8. COMMON AREA (C1, C2, C3 & C4), ARE TO BE COMMON AREA.

9. APPROXIMATE LOCATION OF PROPOSED FIRE HYDRANT (TYPICAL).

10. PRELIMINARY SINKHOLE FLOOD OUTLINE FOR THE 100-YEAR FLOOD. SEE FLOOD PLAIN NOTE THIS SHEET. 11. PRELIMINARY SINKHOLE FLOOD OUTLINE FOR THE 500-YEAR FLOOD. SEE FLOOD PLAIN NOTE THIS SHEET. 12. APPROXIMATE LOCATION OF PROPOSED DETENTION AREAS (TYPICAL).

13. ROADS, UTILITIES AND OTHER ENGINEERING DESIGN ITEMS ARE SHOWN HEREON FOR PLANNING PURPOSES

ONLY AND WILL BE DESIGNED SEPARATELY BY LICENSED ENGINEER. 14. PRE-EXISTING STRUCTURE LOCATED ON LOTS 21 AND 22 EXEMPT FROM SETBACK REQUIREMENTS UNTIL SUCH TIME AS STRUCTURE IS REMOVED, ALL NEW STRUCTURES MUST CONFORM TO LOT SETBACKS.

15. NO DIRECT ACCESS TO TRACKER ROAD OR MAIN STREET FROM ADJOINING LOTS. ALL LOT ACCESS MUST BE FROM ADJOINING STREETS WITHIN SUBDIVISION INTERIOR.

> BASIS OF BEARING MISSOURI STATE PLANE NAD 83 CENTRAL ZONE VERTICAL DATUM = NAVD1988



NOTE: DRAWING REPRODUCTION AND SCALING MAY CHANGE THE INDICATED GRAPHIC SCALES H. SCALE: 1" = 100'



PULLIAM NUMBER 5-200601 JOSEPH R. PULLIAM - LAND SURVEYOR MO# PLS-2006016641 Δ Σ Ш Δ

C-001



SINGLE FAMILY RESIDENTIAL DISTRICT						
LOT #	SQ. FT.	AC.				
1	10,602	0.24				
2	11,613	0.27				
3	11,613	0.27				
4	10,170	0.23				
5	10,009	0.23				
6	10,069	0.23				
7	11,540	0.26				
8	11,192	0.26				
9	10,789	0.25				
10	10,758	0.25				
11	8,057	0.18				
12	8,129	0.19				
13	7,497	0.17				

LOT #	SQ. FT.	AC.
14	11,148	0.26
15	10,670	0.24
16	15,077	0.35
17	11,328	0.26
18	10,002	0.23
19	10,050	0.23
20	10,492	0.24
21	11,409	0.26
22	11,114	0.26
23	10,435	0.24
24	10,010	0.23
25	9,794	0.22

SINGLE FAMILY RESIDENTIAL DISTRICT

CO

MMON	IAREA	
OT #	SQ. FT.	AC.
C1	28,919	0.66
C2	448,246	10.29
NERAL	COMMERCIAL	
OT #	SQ. FT.	AC.
GC1	72,410	1.66
H-DE	NSITY MULTI-FAMI	_Y
OT #	SQ. FT.	AC.
H1	75,979	1.74
H2	237,464	5.45

LEGEND

____ __ ___

_____ _____

— — — — — UTILITY EASEMENT LINE SETBACK LINE

(NO CONSTRUCTION LIMITS)

ADJOINING PROPERTY LINE

15' UTILITY EASEMENT

BOOK G PAGE 484

COPPER LEAF

BOOK 370

PAGE 1419

EXHIBIT 2

ROGER ECKLEY

BOOK 2007 PAGE 5222

SEE NOTE 11

FLOOD NOTE

AND ARE USED AS A REFERENCE ONLY.

DECLARATION BY SURVEYOR

EASEMENT VACATION

DEPICTED HEREON.

COMMON AREA

BY GRAPHIC PLOTTING ONLY, THIS PROPERTY IS IN ZONE X OF THE FLOOD INSURANCE RATE MAP,

THE SINKHOLE FLOOD OUTLINES SHOWN FOR THE 100-YEAR AND 500-YEAR FLOODPLAINS ARE

BASED ON THE PRELIMINARY FIRM PANEL 29043C0058D, WITH A PRELIMINARY DATE OF 2019/09/20

I, JOSEPH R. PULLIAM, DO HEREBY CERTIFY THAT THIS PRELIMINARY PLAT WAS PREPARED UNDER MY PERSONAL SUPERVISION FROM AN ACTUAL SURVEY OF THE LAND HEREIN, IN

ACCORDANCE WITH THE CURRENT MISSOURI STANDARDS FOR PROPERTY BOUNDARY SURVEYS.

PHYSICAL EVIDENCE OF IMPROVEMENTS IS SHOWN FROM INFORMATION TAKEN BY VISUAL INSPECTION OF THE PREMISES. EASEMENTS SHOWN ARE THOSE WRITTEN, PROVIDED, OR

DISCOVERED AND MAY NOT BE ALL INCLUSIVE. APPARENT OWNERSHIPS AS SHOWN ARE BASED UPON INFORMATION PROVIDED BY OTHERS AND DO NOT REPRESENT AN OPINION AS TO TITLE.

THIS PRELIMINARY PLAT IS INTENDED FOR REVIEW AND PLANNING PURPOSES ONLY AND IS NOT

BY APPROVAL OF THE FINAL PLAT OF WALKER ESTATES SUBDIVISION BY THE CITY OF NIXA ALL

EXISTING PUBLIC UTILITY EASEMENTS AND PUBLIC ROAD RIGHT-OF-WAY (OF RECORD OR NOT OF

RECORD) LOCATED WITHIN THE BOUNDARY OF SAID SUBDIVISION BUT NOT SPECIFICALLY CALLED OUT AND/OR GRAPHICALLY DEPICTED HEREON SHALL HENCEFORTH BECOME ABANDONED,

DISSOLVED AND VACATED. ANY EXISTING UTILITY STRUCTURE, LINE OR APPURTENANCE

REGARDLESS OF TYPE LOCATED WITHIN ANY HEREINAFTER VACATED EASEMENT OR RIGHT-OF-WAY MAY REMAIN IN PLACE UNTIL SUCH TIME AS REPAIR, UPGRADE OR RELOCATION

BECOME NECESSARY. ONCE REPAIR, UPGRADE OR RELOCATION BECOME NECESSARY SAID

UTILITY STRUCTURE MUST BE RELOCATED INTO ONE OF THE NEWLY ESTABLISHED EASEMENTS

COMMON AREAS DEPICTED ON THIS SUBDIVISION PLAT AS LOTS C1 THROUGH C2 SHALL BE CONVEYED IN FEE-TITLE TO THE HOME OWNERS ASSOCIATION FOR SAID SUBDIVISION

FOLLOWING COMPLETION OF CONSTRUCTION AND THE RECORDING OF FINAL PLAT THEREOF.

COMMON AREAS ARE THE SOLE RESPONSIBILITY OF THE HOMEOWNERS ASSOCIATION.

THESE COMMON AREAS ARE HEREAFTER RESTRICTED FROM ADDITIONAL SUBDIVIDING OR FROM THE CONSTRUCTION AND/OR ERECTION OF ANY STRUCTURE WHETHER PERMANENT OR TEMPORARY. THESE AREAS ARE TO BE RESERVED AND SET ASIDE IN PERPETUITY AS "GREEN SPACE", THE ONLY PERMITTED USE OF SAID AREAS BEING THE INSTALLATION OF LANDSCAPING, INCLUDING THE PLANTING OF TREES, AND GENERAL MAINTENANCE ACTIVITIES SUCH AS MOWING AND DEBRIS REMOVAL. ALL TAXES, EXPENSES AND OTHER COST RELATED TO THESE

TO BE USED BY ANYONE FOR CONVEYANCE OF LANDS OR TITLE OF REAL ESTATE.

COMMUNITY PANEL NO. 29043C0060C, WHICH BEARS AN EFFECTIVE DATE OF DECEMBER 17, 2010.

SEE NOTE 10-

- SEE NOTE 13

N87°10'30"W 754.49' MEAS.-

ELECTRIC EASEMENT

350.0' GC - (GENERAL COMMERCIAL) ₹-1 (SINGLE FAMILY RESIDENTIAL

> SINKHOLE BOUNDARY

BOOK 2007 PAGE 2656

ROBERT HUNSAKER

BOOK 341 PAGE 806

QUARTER CORNER SECTION 1 & 12

EXISTING FIRE HYDRANT

SINKHOLE

SINKHOLE BOUNDARY

PRELIMINARY PLAT WALKER ESTATES SUBDIVISION A SUBDIVISION IN THE NORTHEAST QUARTER OF THE NORTHWEST QUARTER OF SECTION 12, TOWNSHIP 27 NORTH,

RANGE 22 WEST OF THE FIFTH PRINCIPAL MERIDIAN, CITY OF NIXA, CHRISTIAN COUNTY, STATE OF MISSOURI.

OWNER: DON E. WALKER AND LOIS M. WALKER

DEVELOPER: MORELOCK BUILDERS & ASSOCIATES

722 W. OLIVE STREET SPRINGFIELD, MISSOURI 65806



PROPERTY DESCRIPTION

ALL THAT PART OF THE NORTHEAST QUARTER OF THE NORTHWEST QUARTER OF SECTION 12 - TOWNSHIP 27 NORTH - RANGE 22 WEST OF THE FIFTH PRINCIPAL MERIDIAN, CHRISTIAN COUNT, STATE OF MISSOURI, DESCRIBED AS FOLLOWS: COMMENCING AT THE SOUTHWEST CORNER OF SAID NORTHEAST QUARTER OF THE NORTHWEST QUARTER AND MEASURE \$87°09'29"E ALONG THE SOUTH LINE THEREOF 46.72 FEET TO A POINT ON THE EAST RIGHT OF WAY LINE OF MAIN STREET FOR THE POINT OF BEGINNING; THENCE N01°44'33"E ALONG SAID EAST RIGHT OF WAY LINE 10.00 FEET TO A POINT ON THE SOUTH LINE OF THAT TRACT OF LAND DESCRIBED IN BOOK 2017 ON PAGE 9466; THENCE S87°14'38"E ALONG SAID SOUTH LINE 200.29 FEET TO THE SOUTHEAST CORNER THEREOF: THENCE N01°44'45"W ALONG THE EAST LINE THEREOF 172.00 FEET TO THE NORTHEAST CORNER THEREOF: THENCE N87°13'12"W ALONG THE NORTH LINE THEREOF 200.30 FEET TO A POINT ON THE EAST RIGHT OF WAY LINE OF MAIN STREET; (THE FOLLOWING FOLLOWS THE EAST R/W OF MAIN STREET) THENCE N01°44'41"E 487.33 FEET; THENCE N01°45'40"E 271.99 FEET; THENCE N07°27'19"E 140.43 FEET; THENCE N02°24'42"E 189.27 FEET; THENCE N47°20'09"E 35.05 FEET TO A POINT ON THE SOUTH RIGHT OF WAY LINE OF TRACKER ROAD; (THE FOLLOWING FOLLOWS THE SOUTH R/W OF TRACKER ROAD) THENCE S87°03'09"E 476.06 FEET; THENCE N02°49'33"E 16.69 FEET; THENCE S87°11'50"E 452.72 FEET TO A POINT MARKING THE NORTHEAST CORNER OF THE WEST 350 FEET OF THE EAST HALF OF THE NORTHEAST QUARTER OF THE NORTHWEST QUARTER: THENCE S01°36'27"W ALONG THE EAST LINE THEREOF 1311.90 FEET TO THE SOUTHEAST CORNER THEREOF, SAID POINT ON THE SOUTH LINE OF SAID NORTHEAST QUARTER OF THE NORTHWEST QUARTER; THENCE N87°09'29"W 973.52 FEET TO THE POINT OF BEGINNING, CONTAINING 28.17 ACRES.

UNE OF RELIMINARY PLAT SUBJECT 1: UNE 1: 2017 TOTA: AURAGES THE PROPER OWNERT: 2017 TOTA: MARKET DOTAINS THE PROPER OF ALL LOTS: 2017 TOTA: MARKET DOTAIN													
<pre>DIGINAL CONSIGNED OF THE GRANE AND ALL OTS DE DIGINAL DESTRUCT: DE DIGINAL CONSIGNER CONTROLLES AND ALL OTS DE DIGINAL DESTRUCT: DE DIGINAL CONSIGNER CONTROLLES AND ALL OTS DE DIGINAL DESTRUCT: DE DIGINAL CONSIGNER CONTROLLES AND ALL OTS DE DIGINAL DESTRUCT: DE DIGINAL DESTRUCTURA DE DIGINAL DESTRUCT: DE DIGINAL DESTRUCTURA DE DIGINAL DESTRUCTION DE DIGINAL DE DIGINAL DE DIGINAL DESTRUCTION DE DIGINAL DE DIGINAL DE DIGINAL DESTRUCTION DE DIGINAL DE DIGINAL DE DIGINAL DESTRUCTION DE DIGINAL DESTRUCTURA DE DIGINAL DESTRUCTION DE DIGINAL DE DIGINAL DE DIGINAL DE DIGINAL DESTRUCTION DE DIGINAL DE DIGINAL DE DIGINAL DE DIGINAL DESTRUCTURA DE DIGINAL DE DIGNE DE DIGINAL DE DIGINAL DE DIGI</pre>	DAT	E OF PRELIMINARY PLA	T SUBMITTAL:	JUNE 18, 2021									
TOTAL NUMBER OF LOTS 2 OURRENT ZONNE 2 PROFESSION MAIL FOR LATANALY RESIDENTIAL DISTINGT (COLOR DATE OU ADMINISTRATION (RESIDENTIAL FAMILY) PROFESSION ALL FOR COMPARIANCE (COLOR DATE OU ADMINISTRATION (RESIDENTIAL FAMILY) PROFESSION ALL FOR COMPARIANCE (RESIDENTIAL FAMILY) PROFESSION ALL FOR COMPARIANCE (RESIDENTIAL FAMILY) PROFESSION ALL FOR COMPARIANCE (RESIDENTIAL FAMILY) RESIDENTIAL FAMILY RESIDENTIAL DISTINGT (RESIDENTIAL FAMILY RESIDENTIAL DISTINGT (RESIDENTIAL FAMILY) RESIDENTIAL FAMILY RESIDENTIAL DISTINGT (RESIDENTIAL FAMILY) RESIDENTIAL FAMILY RESIDENTIAL DISTINGT (RESIDENTIAL FAMILY RESIDENTIAL DISTINGT (RESIDENTIAL FAMILY) RESIDENTIAL FAMILY RESIDENTIAL DISTINGT (RESIDENTIAL FAMILY RESIDENTIAL DISTINGT (RESIDENTIAL FAMILY) RESIDENTIAL FAMILY RESIDENTIAL DISTINGT (RESIDENTIAL FAMIL	TOT	AL ACREAGE OF THE DI	EVELOPMENT:	28.17									
CURRENT ZONING: B() (SINCE FAMILY REPORTING DISTINCT) B() (SINCE FAMILY REPORTING DISTINCT) B(TOT	AL NUMBER OF LOTS:	28										
<pre>PERCENCIPIENT PROTECTION PRO</pre>	CUR	RENT ZONING:	R-1 (SINGLE FAN GC (GENERAL C R-3 (HIGH-DENS	MILY RESIDENTI OMMERCIAL) ITY MULTI-FAMII	AL DISTRICT) _Y)								
RI SAULEST LOT: LOT 13, 7497 SOURCE FEET RI LARGESTIOT: LOT 14, 1597 SOURCE FEET MARKAN LOT WOTH IS NOR FEET FOR PA 1 SENDE FAMILY RESIDENTIAL IDISTRICT. MARKAN LOT WOTH IS NOR FEET FOR PA 1 SENDE FAMILY RESIDENTIAL IDISTRICT. MARKAN LOT WOTH IS NOR FEET FOR PA 1 SENDE FAMILY RESIDENTIAL IDISTRICT. MARKAN LOT WOTH IS NOR FEET FOR PA 1 SENDE FAMILY RESIDENTIAL IDISTRICT. MARKAN LOT WOTH IS NOR FEET FOR PA 1 SENDE FAMILY RESIDENTIAL IDISTRICT. MARKAN LOT WOTH IS NOR FEET FOR PA 1 SENDE FAMILY RESIDENTIAL IDISTRICT. MARKAN LOT WOTH IS NOR FEET FOR PA 1 SENDE FAMILY RESIDENTIAL IDISTRICT. MARKAN LOT WOTH IS NOR FEET FOR PA 1 SENDE FAMILY RESIDENTIAL IDISTRICT. MARKAN LOT WOTH IS NOR FEET FOR PA 1 SENDE FAMILY RESIDENTIAL IDISTRICT. MARKAN LOT SUPE IS NOR SCHARKE HER IN THE FERMO OF ALL LOTS. MARKAN LOT SUPE IS NOR FEET FOR PA 1 LOTS. MARKAN LOT SUPE IS NOT FEED FOR PA 1 LOTS. MARKAN LOT WOTH IS UP FEED OF ALL LOTS. MARKAN LOT WOTH IS UP FEED OF ALL LOTS. MARKAN LOT WOTH IS UP FEED OF THE LOT THE FERMO FAUL LOTS. MARKAN LOT WOTH IS UP FEED OF ALL LOTS. MARKAN LOT WOTH IS UP FEED OF THE LOT THE INFORMATION. MARKAN LOT WOTH IS UP FEED OF THE LOT THE INFORMATION IN THE THIS SHEET. MARKAN LOT WOTH IS UP FEED OF THE US OF THE PAUL. MARKAN LOT OF THE US OF THE HER PAUL FAIL LOTS. MARKAN LOT OF THE US OF THE HER PAUL FAIL LOTS. MARKAN LOT OF THE US OF THE HER PAUL FAIL LOTS. MARKAN LOT OF THE US OF THE US OF THE US OF THE US OF THE INFORMATION FEED OF PAUL NOTE THIS SHEET. MARKAN LOCATION OF FROMOSES TO ALL LOTS. MARKAN LOCATION OF THE US OF THE INFORMATION OF THE SHEET. MARKAN LOCATION OF FROMOSES TO ALL LOTS. MARKAN LOCATI	PRO	POSED ZONING:	R-1 (SINGLE FAN GC (GENERAL C R-3 (HIGH-DENS	MILY RESIDENTI OMMERCIAL) ITY MULTI-FAMII	AL DISTRICT) _Y)								
RM LARGESTLOT: LOTE 15,077 SOURCE FEET NOTES 1. MINUMUM LOT WOTH 18 NOR FEET FOR R. 1, SANGE FAMILY RESIDENTIAL DISTRICT. 2. MINUMUM LOT WOTH 18 NOR FEET CORE (COMMERCIAL) 3. MINUMUM LOT SEED 5 6.000 SOURCE FEET. 3. MINUMUM LOT SEED 5 6.000 SOURCE FEET. 3. MINUMUM SERVICES AND THE PHOP MONTAL LOTS WITH LOCAL STREET FROMTAGE. 3. MINUMUM SERVICES WITH NUMBER SETURATION TO HELE DOS OF ALL LOTS WITH LOCAL STREET FROMTAGE. 3. MINUMUM SERVICES WITH NUMBER SETURATION ON THE SEBO OF ALL LOTS WITH LOCAL STREET FROMTAGE. 3. MINUMUM SERVICES WITH NUMBER SETURATION ON THE SEBO OF ALL LOTS WITH LOCAL STREET FROMTAGE. 3. MINUMUM SERVICES WITH NUMBER SETURATION ON THE SEBO OF ALL LOTS WITH LOCAL STREET FROMTAGE. 4. ROAD AREA (C1 & G 2) ARE TO GE COMMON AREA OF ALL LOTS WITH LOCAL STREET FROMTAGE. 4. ROAD SART TO GE DEDUCATED FOR THE USE OF THE FUEL OF MINUMENT LOCAL STREET FROMTAGE. 5. COMMON AREA (C1 & G 2) ARE TO GE COMMON AREA 4. REQUINING SERVICES WITH NUMBER FOR ALL LOTS WITH LOCAL STREET FROMTAGE. 5. COMMON AREA (C1 & G 2) ARE TO GE COMMON AREA 4. REQUINING SERVICES WITH NUMBER FOR ALL LOTS WITH LOCAL STREET FROMTAGE. 5. COMMON AREA (C1 & G 2) ARE TO GE COMMON AREA 4. REQUINING SERVICES WITH NUMBER FOR ALL LOTS WITH LOCAL STREET FROMTAGE. 5. ADDITION OF REPORTED FOR THE USE OF THE FUEL DIST 4. REQUINING SERVICES WITH NUMBER FOR ALL LOTS WITH LOCAL STREET FROMTAGE. 5. ADDITION OF REPORTED FOR THE SEG OF THE FUEL DIST MINUT LOCAL STREET FROMTAGE. 5. ADDITION OF REPORTED FOR THE USE OF THE FUEL DIST MINUT LOCAL STREET FROMTAGE. 5. ADDITION OF REPORTED FOR THE SEG OF THE FUEL DIST MINUT LOCAL STREET FROMTAGE. 5. ADDITION OF REPORTED FOR THE SEG OF THE FUEL DIST MINUT LOCAL STREET FROMTAGE. 5. ADDITION OF REPORTED FROM MINUTE PORT HE SEG OF THE FUEL DIST MINUT LOCAL STREET FROMTAGE. 5. ADDITION OF REPORTED FROM MINUTE PORT HE SEG OF ALL LOTS. 5. ADDITION OF REPORTED FROM MINUTE PORT HE SEG OF ALL LOTS. 5. ADDITION OF REPORTED FROM MINUTE PORT HE SEG OF ALL LOTS. 5. ADDITION OF REPORTED FROM MINUT	R-1 \$	SMALLEST LOT:	LOT 13, 7,497 SQ	UARE FEET									
NOTES IMMUNU DUTVIDHIS DOREET FOR RAISONELE FAMILY RESIDENTIAL DISTRICT. 1 MINUMU DUTVIDHIS NORE FOR CO CONRENAL COMMENCIAL. 2 MINUMU DUTVIDHIS NORE FOR CO CONRENAL COMMENCIAL. 3 MINUMU DUTVIDHIS NORE FOR CO CONRENAL COMMENCIAL. 4 MINUMU DUTVIDHIS NORE FOR CO CONRENAL COMMENCIAL. 5 MINUMU DUTVIDHIS NORE FOR COMMENCIAL. 5 MINUMU DUTVIDHIS NORE FOR COMMENCIAL. 6 MINUMU DUTVIDHIS NORE FOR COMMENCIAL. 7 MINUMU DUTVIDHIS NORE FOR COMMENCIAL. 8 MINUMU DUTVIDHIS NORE FOR COMMENCIAL. 9 MINUMU DUTVIDHIS NORE FOR COMMENCIAL. 10 MINUMU DUTVIDHIS NORE FOR COMMENCIAL. 11 MINUMU DUTVIDHIS NORE FOR COMMENCIAL. 12 MINUMU DUTVIDHIS NORE FOR COMMENCIAL. 13 MINUMU DUTVIDHIS NORE FOR COMMENCIAL. 14 ROADS ARE TO GE DEDICATED FOR THE UDVIDHIS ALL DOTS ARE FOR DOL PLAN NOTE THIS SHEFT. 13 APPROXIMATE LOCATION OF PROPOSED DEFENTION AREAS (TPICAL. 14 PROXIMARARE SINCOLOL FOR THE UDVICAR FLOCOD DUT HIS FOR THE UD	R-1 l	ARGEST LOT:	LOT 16, 15,077 SC	QUARE FEET									
NOTES													
 MINIMUMUED WIDTH IS WORKET FOR FLISINGLE FAMILY RESIDENTIAL DISTRICT.) MINIMUMUED WIDTH IS WORKET FOR THE SINGLE FAMILY RESIDENTIAL COMMERCIAL.) MINIMUMUED STERES IS MORE FOR GO (GENERAL COMMERCIAL.) MINIMUMUED STERES IS MORE FOR GO (GENERAL COMMERCIAL.) MINIMUMUED STERES IS MORE FOR GO (GENERAL COMMERCIAL.) MINIMUMUED STERES IS MORE FOR TO FAIL LOTS. 30'FOOT BULLING SETBACK LINE IN THE FRONT OF AIL LOTS. 30'FOOT BULLING SETBACK LINE IN THE FRONT OF AIL LOTS. 30'FOOT BULLING SETBACK LINE IN THE FRONT OF AIL LOTS. 30'FOOT BULLING SETBACK LINE IN THE FRONT OF AIL LOTS. 30'FOOT BULLING SETBACK LINE IN THE FRONT OF AIL LOTS. 30'FOOT BULLING SETBACK LINE IN THE FRONT OF AIL LOTS. 30'FOOT BULLING SETBACK LINE IN THE FRONT OF AIL LOTS. 30'FOOT BULLING SETBACK LINE IN THE FRONT OF AIL LOTS. 30'FOOT BULLING SETBACK LINE IN THE FRONT OF AIL LOTS. 30'FOOT BULLING SETBACK LINE IN THE FRONT OF AIL LOTS. 30'FOOT BULLING SETBACK LINE IN THE FRONT OF AIL LOTS. 30'FOOT BULLING SETBACK LINE IN THE FRONT OF AIL LOTS. 30'FOOT BULLING SETBACK LINE IN THE FRONT OF AIL LOTS. 40'FOOT BULLING SETBACK LINE IN THE FRONT OF AIL LOTS. 40'FOOT BULLING SETBACK LINE IN THE FRONT OF AIL LOTS. 40'FOOT BULLING SETBACK LINE IN THE FRONT OF AIL LOTS. 40'FOOT BULLING SETBACK LINE IN THE FRONT OF AIL LOTS. 40'FOOT BULLING SETBACK LINE IN THE FRONT OF AIL LOTS. 40'FOOT BULLING SETBACK LINE IN THE FRONT OF AIL LOTS. 40'FOOT BULLING SETBACK LINE IN THE FRONT OF AIL LOTS. 40'FOOT BULLING SETBACK LINE IN THE FRONT OF AIL LOTS. 40'FOOT BULLING SETBACK LINE IN THE FRONT OF AIL LOTS. 40'FOOT BULLING SETBACK LINE IN THE REAR OF AIL LOTS. 40'FOOT BULLING SETBACK LINE IN THE FRONT OF AIL LOTS. 40'FOOT BULLING SETBACK LINE IN THE FRONT OF AIL LOTS. 40'FOOT BULLING SETBACK LINE IN THE FRONT OF AIL LOTS. 40'FOOT BULLING SETBACK LINE IN THE FRONT OF AIL LOTS. 40'FOOT BULLING SETBACK LINE IN THE FRONT AIR AILE SECON THE FRONT AIR AILE SECON THE FRONT AIR AILE S	NO	TES											
 MINIMUM LOT WOTH IS ROME FOR CC (CENERAL COMMERCIAL). MINIMUM LOT WOTH IS ROME FOR CC (CENERAL COMMERCIAL). MINIMUM LOT WOTH IS ROME FOR CC (CENERAL COMMERCIAL). MINIMUM LOT SEE IS 6,000 SQUARE FEET. R. (SINCLE FAMILY REGEMENTIAL DISTRCT) SPOTOT BULDING SETTACK LINE ON THE SIDE OF ALL LOTS (STOOT BULDING SETTACK LINE ON THE SIDE OF ALL LOTS (STOOT BULDING SETTACK LINE ON THE SIDE OF ALL LOTS (STOOT BULDING SETTACK LINE ON THE SIDE OF ALL LOTS (STOOT BULDING SETTACK LINE ON THE SIDE OF ALL LOTS (STOOT BULDING SETTACK LINE ON THE SIDE OF ALL LOTS (STOOT BULDING SETTACK LINE ON THE SIDE OF ALL LOTS (STOOT BULDING SETTACK LINE ON THE SIDE OF ALL LOTS (STOOT BULDING SETTACK LINE ON THE SIDE OF ALL LOTS (STOOT BULDING SETTACK LINE ON THE SIDE OF ALL LOTS (STOOT BULDING SETTACK LINE ON THE SIDE OF ALL LOTS (STOOT BULDING SETTACK LINE ON THE SIDE OF ALL LOTS (STOOT BULDING SETTACK LINE ON THE SIDE OF ALL LOTS (STOOT BULDING SETTACK LINE ON THE SIDE OF ALL LOTS (STOOT BULDING SETTACK LINE ON THE SIDE OF ALL LOTS (STOOT BULDING SETTACK LINE ON THE SIDE OF ALL LOTS (STOOT BULDING SETTACK LINE ON THE SIDE OF ALL LOTS (STOOT BULDING SETTACK LINE ON THE SIDE OF ALL LOTS (STOOT BULDING SETTACK LINE ON THE SIDE OF ALL LOTS (STOOT BULDING SETACK LINE ON THE SIDE OF ALL LOTS (STOOT BULDING SETACK LINE ON THE SIDE OF ALL LOTS (STOOT BULDING SETACK LINE ON THE SIDE OF ALL LOTS (STOOT BULDING SETACK LINE ON THE SIDE OF ALL LOTS (STOOT BULDING SETACK LINE ON THE SIDE OF ALL LOTS (STOOT BULDING SETACK LINE ON THE SIDE OF ALL LOTS (STOOT BULDING SETACK LINE ON THE SIDE OF ALL LOTS (STOOT BULDING SETACK LINE ON THE SIDE OF ALL LOTS (STOOT BULDING SETACK LINE ON THE SIDE OF ALL LOTS (STOOT BULDING SETACK LINE ON THE SIDE OF ALL LOTS (STOOT BULDING SETACK LINE ON THE SIDE OF ALL LOTS (STOOT BULDING SETACK LINE ON THE SIDE OF ALL LOTS (STOOT BULDING SETACK LINE ON THE SIDE OF ALL LOTS (STOOT BULDING SETACK LINE ON THE SIDE OF ALL LOTS (STOOT	1.	MINIMUM LOT WIDTH	IS 60 FEET FOR R-	1 (SINGLE FAMIL	Y RESIDENTIAL D	ISTRICT).							
 MINIMULUT SIZE IS ADD SQUARE FEET. R.1 SIMMULUT SIZE IS ADD SQUARE FEET. R.2 COT SULDING SETBACK LINE IN THE FER AD FAIL LOTS. 3P FOOT SULDING SETBACK LINE IN THE FER AD FAIL LOTS. 3P FOOT SULDING SETBACK LINE IN THE FEAR OF ALL LOTS. 3P FOOT SULDING SETBACK LINE IN THE FEAR OF ALL LOTS. 3P FOOT SULDING SETBACK LINE IN THE FEAR OF ALL LOTS. 3P FOOT SULDING SETBACK LINE IN THE FEAR OF ALL LOTS. 3P FOOT SULDING SETBACK LINE IN THE FEAR OF ALL LOTS. 3P FOOT SULDING SETBACK LINE IN THE FEAR OF ALL LOTS. 3P FOOT SULDING SETBACK LINE IN THE FEAR OF ALL LOTS. 3P FOOT SULDING SETBACK LINE IN THE FEAR OF ALL LOTS. 3P FOOT SULDING SETBACK LINE IN THE FEAR OF ALL LOTS. 3P FOOT SULDING SETBACK LINE IN THE FEAR OF ALL LOTS. 3P FOOT SULDING SETBACK LINE IN THE FEAR OF ALL LOTS. 3P FOOT SULDING SETBACK LINE IN THE FEAR OF ALL LOTS. 3P FOOT SULDING SETBACK LINE IN THE FEAR OF ALL LOTS. 3P FOOT SULDING SETBACK LINE ON THE SIDE OF ALL LOTS. 3P FOOT SULDING SETBACK LINE ON THE SIDE OF ALL LOTS. 3P FOOT SULDING SETBACK LINE ON THE SIDE OF ALL LOTS. 3P FOOT SULDING SETBACK LINE ON THE SIDE OF ALL LOTS. 3P FOOT SULDING SETBACK LINE ON THE SIDE OF ALL LOTS. 3P FOOT SULDING SETBACK LINE ON THE SIDE OF ALL LOTS. 3P FOOT SULDING SETBACK LINE ON THE SIDE OF ALL LOTS. 3P FOOT SULDING SETBACK LINE ON THE SIDE OF ALL LOTS. 3P FOOT SULDING SETBACK LINE ON THE SIDE OF ALL LOTS. 3P FOOT SULDING SETBACK LINE ON THE SIDE OF THE PUBLIC. APPROXIMATE LOCATION OF PROPOSED FIRE HYDRANT (TYPICAL). APPROXIMATE LOCATION OF TRACKERE READ SALL LOT ADD SALL OT ALL OT ACCESS MUST BE FROM	2.	MINIMUM LOT WIDTH I	IS NONE FOR GC (GENERAL COM	MERCIAL).								
 R-1 INNEL FAMALY RESIDENTIAL DISTRICT) 25 FOOT BUILONS STERACK LINE IN THE REAR OF ALL LOTS 25 FOOT BUILONS STERACK LINE IN THE REAR OF ALL LOTS 25 FOOT BUILONS STERACK LINE ON THE REAR OF ALL LOTS 25 FOOT BUILONS STERACK LINE ON THE REAR OF ALL LOTS 25 FOOT BUILONS STERACK LINE ON THE REAR OF ALL LOTS 25 FOOT BUILONS STERACK LINE ON THE REAR OF ALL LOTS 25 FOOT BUILONS STERACK LINE ON THE REAR OF ALL LOTS 25 FOOT BUILONS STERACK LINE ON THE REAR OF ALL LOTS 25 FOOT BUILONS STERACK LINE ON THE REAR OF ALL LOTS 25 FOOT BUILONS STERACK LINE ON THE SIDE OF ALL LOTS 25 FOOT BUILONS STERACK LINE ON THE SIDE OF ALL LOTS 25 FOOT BUILONS STERACK LINE ON THE SIDE OF ALL LOTS 25 FOOT BUILONS STERACK LINE ON THE SIDE OF ALL LOTS 25 FOOT BUILONS STERACK LINE ON THE SIDE OF ALL LOTS 25 FOOT BUILONS STERACK LINE ON THE SIDE OF ALL LOTS. 25 FOOT BUILONS STERACK LINE ON THE SIDE OF ALL LOTS. 25 FOOT BUILONS STERACK LINE ON THE SIDE OF ALL LOTS. 25 FOOT BUILONS STERACK LINE ON THE SIDE OF ALL LOTS. 25 FOOT BUILONS STERACK LINE ON THE SIDE OF ALL LOTS. 25 FOOT BUILONS STERACK LINE ON THE SIDE OF ALL LOTS. 25 FOOT BUILONS STERACK LINE ON THE SIDE OF ALL LOTS. 25 FOOT BUILONS STERACK LINE ON THE SIDE OF ALL LOTS. 25 FOOT BUILONS STERACK LINE ON THE SIDE OF ALL LOTS. 25 FOOT BUILONS STERACK LINE ON THE SIDE OF ALL LOTS. 25 FOOT BUILONS STERACK LINE ON THE SIDE OF ALL LOTS. 26 COMMON AREA (CT & C2). ARE TO BE COLCATE OF OTH THE SIDE OF ALL LOTS. 26 COMMON AREA (CT & C2). ARE TO BE COLCATE OF OTH HE SOLYCAR FLOOD SEE FLOOD PLAN NOTE THIS SHEET. 26 OPHICING STERACK LINE ON THE SIDE OF ALL LOTS. 26 COMMON AREA (CT & C2). ARE TO THAT PORTING AN AREA SHOWN HEREON FOR PLANNING PURPOSES ONLY AND MUE BUISDION INCLUDES A REPART AND ALL COVENANTS / RESTRICTION OF PROPOSED DETERMINE ANY SUBMICIDE CALL DISTRICT MARK REAL OF THE SIDE OF ALL DOTS AND THE PLANE MUE SIGNING STANDALL OF THE AREA AND ALL COVENANTS / RESTRICTION OF PROPOSED ONLY AND MUE BUISDION INCLUDES A REPART AND ALL COVENANTS / RESTRICTIONS	3.	MINIMUM LOT SIZE IS	6,600 SQUARE FEE	ET.						Z		(0)	
	4.	R-1 (SINGLE FAMILY F 25 FOOT BUILDING SE 20 FOOT BUILDING SE 5 FOOT BUILDING SET 12 FOOT BUILDING SE	RESIDENTIAL DISTI TBACK LINE IN TH TBACK LINE IN TH BACK LINE ON TH TBACK LINE ON TH	RICT) E FRONT OF ALI E REAR OF ALL E SIDE OF ALL L HE SIDE OF ALL	LOTS. LOTS. OTS. LOTS WITH LOCAI	L STREET FRONTAG	GE.			DIVISIO	3	SOCIATES	AT
 8. Read High-DENSITY AULT-FAMILY) 92 FOOT BUILDING SETBACK LINE IN THE FRONT OF ALL LOTS. 12 FOOT BUILDING SETBACK LINE ON THE SIDE OF ALL LOTS. 12 FOOT BUILDING SETBACK LINE ON THE SIDE OF ALL LOTS. 13 FOOT BUILDING SETBACK LINE ON THE SIDE OF ALL LOTS. 14 FOOT JUILITY EASEMENT ON FRONT AND REAR OF ALL LOTS. 15 ROOT BUILDING SETBACK LINE ON THE USE OF THE USE OF THE USE OF THE USE OF THE PUBLIC. 16 COMMON AREA (C1 & C2) ARE TO BE COMMON AREA. 19 PRELIMINARY SINKHOLE FLOOD OUTLINE FOR THE USE OF THE 100-YEAR FLOOD. SEE FLOOD PLAIN NOTE THIS SHEET. 14 PROXIMATE LOCATION OF PROPOSED DETENTION AREA STOPPACH FLOOD. SEE FLOOD PLAIN NOTE THIS SHEET. 15 APPROXIMATE LOCATION OF PROPOSED DETENTION AREA STOPPACH. 16 PORT UTILTES AND OTHER ENGNEERING DESIGN ITEMS ARE SHOWN HEREON FOR PLANNING PURPOSES ONLY AND WILL BE DESIGNED SEPARATELY BY LICENSED ENGINEER. 17 HIS SUBDINISION INCLUDES A REPLAT OF THAT PORTION OF NORTH SIDE INDUSTRIAL PARK INCLUDING NECESSARY VACATION OF ROADWAYS, EASEMENTS AND ALL COVENANTS / RESTRICTIONS ASSOCIATED THEREWITH. 18 NO DIRECT ALCESS TO TRACKER ROAD OR MAIN STREET FROM ADJOINING LOTS. ALL LOT ACCESS MUST BE FROM ADJOINING STREETS WITHIN SUBDINISION INTERIOR. 19 NO INCLUDES A REPLAT OF THAT PORTION OF NORTH SIDE INDUSTRIAL PARK INCLUDING NECESSARY VACATION OF ROADWAYS, EASEMENTS AND ALL COVENANTS / RESTRICTIONS ASSOCIATED THEREWITH. 10 NO DIRECT ALCESS TO TRACKER ROAD OR MAIN STREET FROM ADJOINING LOTS. ALL LOT ACCESS MUST BE FROM ADJOINING STREETS WITHIN SUBDINISION INTERIOR. 11 NISSUEDINISION INTERIOR. 12 NO INCLUDES A REPLAT OF THAT PORTION OF NORTH SIDE INDUSTRIAL PARK INCLUDING NECESSARY VACATION OF ROADWAYS, EASEMENTS AND ALL COVENANTS / RESTRICTIONS ASSOCIATED THEREWITH. 14 BODSOLING TATE PLANE MIDDATE DIRAWING REPRODUCTION ADJOINT ATTATE PLANE MIDDATE DIRAWING REPROD	5.	GC (GENERAL COMM 20 FOOT BUILDING SE 20 FOOT BUILDING SE 10 FOOT BUILDING SE 15 FOOT BUILDING SE	ERCIAL) TBACK LINE IN TH TBACK LINE IN TH TBACK LINE ON TH TBACK LINE ON TH	E FRONT OF ALI E REAR OF ALL HE SIDE OF ALL HE SIDE OF ALL	LOTS. LOTS. LOTS. LOTS. WITH LOCAI	L STREET FRONTAG	GE.			ES SUBI	NTY, MISSOU	RS & ASS	ARY PL
 10 FOOT UTILITY EASEMENT ON FRONT AND REAR OF ALL LOTS. ROADS ARE TO BE DEDICATED FOR THE USE OF THE PUBLIC. COMMON AREA (C1 & C2), ARE TO BE COMMON AREA. PRELIMINARY SINKHOLE FLOOD OUTLINE FOR THE 100-YEAR FLOOD. SEE FLOOD PLAIN NOTE THIS SHEET. APPROXIMATE LOCATION OF PROPOSED FIRE HYDRANT (TYPICAL). APPROXIMATE LOCATION OF PROPOSED FIRE HYDRANT (TYPICAL). APPROXIMATE LOCATION OF PROPOSED DETENTION AREAS (TYPICAL). ROADS UTILITES AND OTHER ENGINEERING DESIGN TEMS ARE SHOWN HEREON FOR PLANNING PURPOSES ONLY AND WILL BE DESIGNED SEPARATELY BY LICENSED ENGINEER. NO THERE TO THACKER ROAD OR MAIN STREET FROM ADJOINING LOTS. ALL LOT ACCESS MUST BE FROM ADJOINING STREETS WITHIN SUBDIVISION INTERIOR. THIS SUBDIVISION INCLUDES A REPLAT OF THAT PORTION OF NORTH SIDE INDUSTRIAL PARK INCLUDING NECESSARY VACATION OF ROADWAYS, EASEMENTS AND ALL COVENANTS / RESTRICTIONS ASSOCIATED THEREWITH. MISSOURI STATE PLANE MAD SIGENTRAL ZONE VERTICAL DATUM = NAVD1988 VERTICAL DATUM = NAVD1988 DESCLING MAY CHANGE THE INDICATE ORGENTIFIC. THIS SUBDIVISION INCLUDES A REPLAT OF THAT PORTION OF NORTH SIDE INDUSTRIAL PARK INCLUDING NECESSARY VACATION OF ROADWAYS, EASEMENTS AND ALL COVENANTS / RESTRICTIONS ASSOCIATED THEREWITH. MISSOURI STATE PLANE MAD SIGENTRAL ZONE VERTICAL DATUM = NAVD1988 DETE: DRAWING REPRODUCTION AND SOCIALING MAY CHANGE THE INDICATE ORGENTING COLLING FROM COULDES TO THE PLANE INDICATE ORGENTING COLLING FROM THE PLANE MAD SIGENTRAL ZONE MISSOURI STATE PLANE MAD SIGENT GRAPHIC SOCIALS FROM THE COLLING THE COLLING THE PLANE MAD SIGENT GRAPHICE SOCIAL SYSTEM MISSOURI STATE PLANE MAD S	6.	R-3 (HIGH-DENSITY M 20 FOOT BUILDING SE 12 FOOT BUILDING SE 8 FOOT BUILDING SET 12 FOOT BUILDING SE	ULTI-FAMILY) TBACK LINE IN TH TBACK LINE IN THI BACK LINE ON THI TBACK LINE ON TH	E FRONT OF ALI E REAR OF ALL E SIDE OF ALL L HE SIDE OF ALL	LOTS. LOTS. OTS. LOTS WITH LOCAI	L STREET FRONTAG	GE.			ESTATE	RISTIAN COUN	(BUILDE	
 ROADS ARE TO BE DEDICATED FOR THE USE OF THE PUBLIC. COMMON AREA (C1 & C2), ARE TO BE COMMON AREA. PRELIMINARY SINKHOLE FLOOD OUTLINE FOR THE 100-YEAR FLOOD. SEE FLOOD PLAIN NOTE THIS SHEET. APPROXIMATE LOCATION OF PROPOSED FIRE HYDRANT (TYPICAL). APPROXIMATE LOCATION OF PROPOSED DETENTION AREAS (TYPICAL). ND DIRECT ACCESS TO TRACKER RIAD DE NUMIN TEMES ARE SHOWN HEREON FOR PLANNING PURPOSES ONLY AND WILL BE DESIGNED SEPARATELY BY LICENSED ENGINEER: MAD SIGNER'S WITHIN SUBDIVISION INTERIOR: THIS SUBDIVISION INCLUES A REPLAT OF THAT PORTION OF NORTH SIDE INDUSTRIAL PARK INCLUDING NECESSARY VACATION OF ROADWAYS, EASEMENTS AND ALL COVENANTS / RESTRICTIONS ASSOCIATED THEREWITH. BASIS OF BEARING MISSOURI STATE PLANE NO BIS CENTRAL ZONE VERTICAL DATUM = NAVD1988 URTE: ORAWING REPRODUCTION AND SCALING MERCHANGE THE INDICATE DEGRAPHIC SCALES WE WILL SUBDIVISION INTERION OF ORAPHICASES 	7.	10 FOOT UTILITY EASE	EMENT ON FRONT	AND REAR OF A	LL LOTS.					Ŕ	CHF	Ś	R
 COMMON AREA (C1 & C2), ARE TO BE COMMON AREA. PRELIMINARY SINKHOLE FLOOD OUTLINE FOR THE 100-YEAR FLOOD. SEE FLOOD PLAIN NOTE THIS SHEET. PRELIMINARY SINKHOLE FLOOD OUTLINE FOR THE 500-YEAR FLOOD. SEE FLOOD PLAIN NOTE THIS SHEET. APPROXIMATE LOCATION OF PROPOSED FIRE HYDRANT (TYPICAL). APPROXIMATE LOCATION OF PROPOSED DETENTION AREAS (TYPICAL). APPROXIMATE LOCATION OF PROPOSED DETENTION AREAS (TYPICAL). ROADS, UTILITES AND OTHER ROINEERING DESIGN ITEMS ARE SHOWN HEREON FOR PLANNING PURPOSES ONLY AND WILL BE DESIGNED SEPARATELY BY LICENSED ENGINEER. ND DIRECT ACCESS TO TRACKER ROAD OR MAIN STREET FROM ADJOINING LOTS. ALL LOT ACCESS MUST BE FROM ADJOINING STREETS WITHIN SUBDIVISION INTERIOR. THIS SUBDIVISION INCLUDES A REPLAT OF THAT PORTION OF NORTH SIDE INDUSTRIAL PARK INCLUDING NECESSARY VACATION OF ROADWAYS, EASEMENTS AND ALL COVENANTS / RESTRUCTIONS ASSOCIATED THEREWITH. MISSOURI STATE PLANE NAD 83 CENTRAL ZONE VERTICAL DATUM = NAVD1988 UTIC: DRAWING REPRODUCTION AND 83 CENTRAL ZONE NOTE: DRAWING REPRODUCTION AND 83 CENTRAL ZONE 	8.	ROADS ARE TO BE DE	DICATED FOR THE	E USE OF THE PI	JBLIC.					Ü		Ш	<u>م</u>
 PRELIMINARY SINKHOLE FLOOD OUTLINE FOR THE 100-YEAR FLOOD. SEE FLOOD PLAIN NOTE THIS SHEET. PRELIMINARY SINKHOLE FLOOD OUTLINE FOR THE 500-YEAR FLOOD. SEE FLOOD PLAIN NOTE THIS SHEET. APPROXIMATE LOCATION OF PROPOSED FIRE HYDRANT (TYPICAL). APPROXIMATE LOCATION OF PROPOSED DETENTION AREAS (TYPICAL). APPROXIMATE LOCATION OF PROPOSED DETENTION AREAS (TYPICAL). NO DIRECT ACCESS TO TRACKER ROAD OR MAIN STREET FROM ADJOINING LOTS. ALL LOT ACCESS MUST BE FROM ADJOINING STREETS WITHIN SUBDIVISION INTERIOR. NO DIRECT ACCESS TO TRACKER ROAD OR MAIN STREET FROM ADJOINING LOTS. ALL LOT ACCESS MUST BE FROM ADJOINING STREETS WITHIN SUBDIVISION INTERIOR. THIS SUBDIVISION INCLUDES A REPLAT OF THAT PORTION OF NORTH SIDE INDUSTRIAL PARK INCLUDING NECESSARY VACATION OF ROADWAYS, EASEMENTS AND ALL COVENANTS / RESTRICTIONS ASSOCIATED THEREWITH. MISBOURI STATE PLANE NAD ALL COVENANTS / RESTRICTIONS ASSOCIATED THEREWITH. VERTICAL DATUM = NAVD1988 DETE DRAWING REPRODUCTION FUNCTION FOR THERE TOR DATION OF NORTH SIDE INDUSTRIAL PARK INCLUDING NECESSARY SOLUCE ALL SYSTEM DATION OF ROADWAYS, EASEMENTS AND ALL COVENANTS / RESTRICTIONS ASSOCIATED THEREWITH. 	9.	COMMON AREA (C1 &	C2), ARE TO BE C	COMMON AREA.						L L		DRI	
 PRELIMINARY SINKHOLE FLOOD OUTLINE FOR THE 500-YEAR FLOOD. SEE FLOOD PLAIN NOTE THIS SHEET. APPROXIMATE LOCATION OF PROPOSED FIRE HYDRANT (TYPICAL). APPROXIMATE LOCATION OF PROPOSED DETENTION AREAS (TYPICAL). ROADS, UTILITIES AND OTHER ENGINEERING DESIGN ITEMS ARE SHOWN HEREON FOR PLANNING PURPOSES ONLY AND WILL BE DESIGNED SEPARATELY BY LICENSED ENGINEER. NO DIGNING STREETS TO TRACKER ROAD OR MAIN STREET FROM ADJOINING LOTS. ALL LOT ACCESS MUST BE FROM ADJOINING STREETS WITHIN SUBDIVISION INTERIOR. THIS SUBDIVISION INCLUDES A REPLAT OF THAT PORTION OF NORTH SIDE INDUSTRIAL PARK INCLUDING NECESSARY VACATION OF ROADWAYS, EASEMENTS AND ALL COVENANTS / RESTRICTIONS ASSOCIATED THEREWITH. MISSOURI STATE PLANE MUSSOURI STATE PLANE MUSSOURI STATE PLANE ND SIGCINITE ALADINE DUSCALING MAY CHANGE THE DUSCALING MAY CHANGE THE UNTE: DRAWING REPRODUCTION MUSCICALING MAY CHANGE THE DUSCALING MAY CHANGE THE UNTE: DRAWING REPRODUCTION MUSCICALING MAY CHANGE THE UNTE: DRAWING REPRODUCTION MUSCICALING MAY CHANGE THE UNTER DISCOURD BY DUSCALING MAY CHANGE THE DUSCALING MAY CHANGE	10.	PRELIMINARY SINKHO	LE FLOOD OUTLIN	IE FOR THE 100-	YEAR FLOOD. SEI	E FLOOD PLAIN NOT	TE THIS S	HEET.		۸Þ		Ŭ	
 APPROXIMATE LOCATION OF PROPOSED FIRE HYDRANT (TYPICAL). APPROXIMATE LOCATION OF PROPOSED DETENTION AREAS (TYPICAL). ROADS, UTILITIES AND OTHER ENGINEERING DESIGN ITEMS ARE SHOWN HEREON FOR PLANNING PURPOSES ONLY AND WILL BE DESIGNED SEPARATELY BY LICENSED ENGINEER. NO DIRECT ACCESS TO TRACKER ROAD OR MAIN STREET FROM ADJOINING LOTS. ALL LOT ACCESS MUST BE FROM ADJOINING STREETS WITHIN SUBDIVISION INTERIOR. THIS SUBDIVISION INCLUDES A REPLAT OF THAT PORTION OF NORTH SIDE INDUSTRIAL PARK INCLUDING NECESSARY VACATION OF ROADWAYS, EASEMENTS AND ALL COVENANTS / RESTRICTIONS ASSOCIATED THEREWITH. MISSOURI STATE PLANE NAD 83 CENTRAL ZONE VERTICAL DATUM = NAVD1988 MOTE: DRAWING REPRODUCTION BID SCALING MAY CHANCE FILE UNDICATED GRAPHIC SCALES MOTE: DRAWING MAY CHANCE REPRODUCTION BID SCALING MAY CHANCE RALE UNDICATED GRAPHIC SCALES MIT NO: 	11.	PRELIMINARY SINKHO	LE FLOOD OUTLIN	IE FOR THE 500-	YEAR FLOOD. SEI	E FLOOD PLAIN NOT	TE THIS S	HEET.					
 APPROXIMATE LOCATION OF PROPOSED DETENTION AREAS (TYPICAL). ROADS, UTILITIES AND OTHER ENGINEERING DESIGN ITEMS ARE SHOWN HEREON FOR PLANNING PURPOSES ONLY AND WILL BE DESIGNED SEPARATELY BY LICENSED ENGINEER. NO DIRECT ACCESS TO TRACKER ROAD OR MAIN STREET FROM ADJOINING LOTS. ALL LOT ACCESS MUST BE FROM ADJOINING STREETS WITHIN SUBDIVISION INTERIOR. THIS SUBDIVISION INCLUDES A REPLAT OF THAT PORTION OF NORTH SIDE INDUSTRIAL PARK INCLUDING NECESSARY VACATION OF ROADWAYS, EASEMENTS AND ALL COVENANTS / RESTRICTIONS ASSOCIATED THEREWITH. MISSOURI STATE PLANE NAD 83 CENTRAL ZONE VERTICAL DATUM = NAVD1988 UTICE DRAWING REPRODUCTION ON DET. DRAWING REPRODUCTION NDE SCALING MAY CHANGE THE DISCATED GRAWING REPRODUCTION AND SCALING MAY CHANGE THE DRAWING REPRODUCTION AND AND AND AND AND AND AND AND AND AN	12.	APPROXIMATE LOCAT	TION OF PROPOSE	D FIRE HYDRAN	T (TYPICAL).								
 14. ROADS, UTILITIES AND OTHER ENGINEERING DESIGN ITEMS ARE SHOWN HEREON FOR PLANNING PURPOSES ONLY AND WILL BE DESIGNED SEPARATELY BY LICENSED ENGINEER. 15. NO DIRECT ACCESS TO TRACKER ROAD OR MAIN STREET FROM ADJOINING LOTS. ALL LOT ACCESS MUST BE FROM ADJOINING STREETS WITHIN SUBDIVISION INTERIOR. 16. THIS SUBDIVISION INCLUDES A REPLAT OF THAT PORTION OF NORTH SIDE INDUSTRIAL PARK INCLUDING NECESSARY VACATION OF ROADWAYS, EASEMENTS AND ALL COVENANTS / RESTRICTIONS ASSOCIATED THEREWITH. 17. BASIS OF BEARING MISSOURI STATE PLANE NAD 83 CENTRAL ZONE VERTICAL DATUM = NAVD1988 VERTICAL DATUM = NAVD1988 VIE: DRAWING REPRODUCTION AND SCALING MAY CHANGE THE DADAGAING MAY CHANGE THE INDICATE DERAWING REPRODUCTION AND SCALING MAY CHANGE THE OCALING MAY CHANGE THE OCALING MAY CHANGE THE ONDE CALING MAY CHANGE THE ONDE	13.	APPROXIMATE LOCAT	ION OF PROPOSE	D DETENTION A	REAS (TYPICAL).								
 15. NO DIRECT ACCESS TO TRACKER ROAD OR MAIN STREET FROM ADJOINING LOTS. ALL LOT ACCESS MUST BE FROM ADJOINING STREETS WITHIN SUBDIVISION INTERIOR. 16. THIS SUBDIVISION INCLUDES A REPLAT OF THAT PORTION OF NORTH SIDE INDUSTRIAL PARK INCLUDING NECESSARY VACATION OF ROADWAYS, EASEMENTS AND ALL COVENANTS / RESTRICTIONS ASSOCIATED THEREWITH. 17. BASIS OF BEARING MISSOURI STATE PLANE NAD 83 CENTRAL ZONE VERTICAL DATUM = NAVD1988 VERTICAL DATUM = NAVD1988	14.	ROADS, UTILITIES AND AND WILL BE DESIGN	D OTHER ENGINEE ED SEPARATELY B	RING DESIGN IT BY LICENSED EN	EMS ARE SHOWN GINEER.	I HEREON FOR PLA	NNING PL	JRPOSES ONLY					
16. THIS SUBDIVISION INCLUDES A REPLAT OF THAT PORTION OF NORTH SIDE INDUSTRIAL PARK INCLUDING NECESSARY VACATION OF ROADWAYS, EASEMENTS AND ALL COVENANTS / RESTRICTIONS ASSOCIATED THEREWITH. Image: Basis of Bearing Image: Basis of Bearing Missouri State PLANE Image: Basis of Bearing Not so central zone Image: Basis of Bearing Image: Determine the provide the	15.	NO DIRECT ACCESS T ADJOINING STREETS	O TRACKER ROAD WITHIN SUBDIVISIO) OR MAIN STRE ON INTERIOR.	ET FROM ADJOINI	ING LOTS. ALL LOT A	ACCESS I	MUST BE FROM					
BASIS OF BEARING MISSOURI STATE PLANE ND 83 CENTRAL ZONE VERTICAL DATUM = NAVD1988 NOTE: DRAWING REPRODUCTION ND 5CALING MAY CHANGE THE INDICATED GRAPHIC SCALES NOTE: AND SCALING MAY CHANGE THE INDICATED GRAPHIC SCALES	16.	THIS SUBDIVISION INC VACATION OF ROADW	CLUDES A REPLAT /AYS, EASEMENTS	OF THAT PORTI AND ALL COVE	ON OF NORTH SIE NANTS / RESTRIC	DE INDUSTRIAL PAR TIONS ASSOCIATED	RK INCLUE D THEREV	DING NECESSAR VITH.	RY				
BASIS OF BEARING MISSOURI STATE PLANE NAD 83 CENTRAL ZONE VERTICAL DATUM = NAVD1988 MISSOURI STATE PLANE NAD 50 CENTRAL ZONE MISSOURI D 50 100 D 50					Ν	J							
0 50 100 ONE CALL SYSTEM Image: Call or Click Before You Dig! NOTE: DRAWING REPRODUCTION AND SCALING MAY CHANGE THE INDICATED GRAPHIC SCALES 1-800-DIG-RITE Or Q14 Image: Call or Click Before You Dig! SHT NO: SHT NO:		B	BASIS OF BE/ MISSOURI STATE NAD 83 CENTRAL ERTICAL DATUM = I	ARING PLANE . ZONE NAVD1988				MISS	SOURI				
					0 50 NOTE: DRAWING AND SCALING MA INDICATED GRA	0 100 REPRODUCTION AY CHANGE THE APHIC SCALES		ONE CA Call o Before 1-800-D	LL SYSTEM r Click You Dig! DIG-RITE 814	L D D D C O L C D L C D L C D L C D L C D L C D L C D L C D L C D L C C L C L	LOCATION:	CLIENT:	ТПСЕ:

mo1call.com

INDICATED GRAPHIC SCALES H. SCALE: 1" = 100'

REVISION									
DATE									
J	DSEF	PROFILE PROFILE PH R. M	PLS PLS PLS PLS PULL D# P	OF DSE PUL NUN S-200 (AL	EPH I LIAM IBER 06016 LAND	SOUR R. 641 SUR SUR ND S 01664		And Star	R
DWN.BY: BJS	CKD BY:	DCG	APPD. BY: JRP		DATE: 06/18/2021	SCALE:	1" = 100'	Graphic scale may change due to drawing	reproduction
					www.tothassociates.com	CERTIFICATE OF AUTHORITY: MO# LS-2011008797	O 2021 Toth and Associates, Inc.	Drawings and specifications are not intended for use on other projects at this site or other sites	without written approval of the engineer
	WALKER ESTATES SUBDIVISION		CHRISTIAN COUNTY, MISSOURI		MORELOCK RUILDERS & ASSOCIATES			PRELIMINARY PLAT	

C-001



COUNCIL BILL EXHIBIT A -ATTACHMENT 2

TRANSPORTATION IMPACT STUDY

WALKER ESTATES AND WALKER WOODS SUBDIVISION CITY OF NIXA, MISSOURI | SUMMER 2021



1550 E. REPUBLIC ROAD | SPRINGFIELD, MO 65804 | 417.888.0645 107 SE WASHINGTON ST | SUITE 465 | PORTLAND, OR 97214 | 503.946.6440 369 W HERMISTON AVE | HERMISTON, OR 97838 | 541-289-7000 TOTHASSOCIATES.COM

TABLE OF CONTENTS

TRANSPORTATION IMPACT STUDY

1.	EXECUTIVE SUMMARY 1.1 Findings 1.2 Recommendations	1 1
2.	INTRODUCTION 2.1 Purpose of Report 2.2 Objectives 2.3 Intersections Studied 2.4 Location Map of Project	2 2 3 3
3.	DEVELOPMENT SITE 3.1 Existing Land Use 3.2 Proposed Land Use 3.3 Proposed Access Points 3.4 Relationship to Current Plans 3.5 Multimodal Evaluation 3.6 Study Scenarios	4 4 5 5
4.	EXISTING CONDITIONS 4.1 Description of Key Roads 4.2 Intersection Traffic Volumes and Turning Counts 4.3 Available Bike and Pedestrian Infrastructure 4.4 Available Transit Infrastructure	6 6 11 11
5.	PROJECTED TRAFFIC 5.1 Estimated Trip Generation and/or Relocated Traffic 5.2 Trip Distribution and Assignment 5.3 Map of Projected Directional Distribution 5.4 Total Future Traffic (AM/PM)	12 13 14 16
6.	CAPACITY ANALYSIS FOR THE STUDIED INTERSECTIONS 6.1 Existing and Proposed Scenarios for AM/PM 6.2 Existing/Future Level of Service	44 44
7.	PARKING EVALUATION 7.1 Parking to Be Provided on Site 7.2 Parking Required by Nixa City Code	46 46
8.	SIGHT DISTANCE REVIEW 8.1 Minimum Stopping Sight Distances Required 8.2 Stopping Sight Distances Provided 8.3 Additional Recommendations	47 47 47



9.	SIGHT REVIEW	
	9.1 MUTCD Standards	48
	9.2 Site Circulation and Turning Templates	48
	9.3 Site Conflicts	48
10		
10.		
	10.1 Left Turn Warrant	49

SUMMARY OF FINDINGS AND RECOMMENDATIONS
 Geometric and Lane Recommendations to Accommodate Proposed Traffic Volume 50

EXHIBITS

- Exhibit 1: Walker Woods Preliminary Plat
- Exhibit 2: Walker Estates Preliminary Plat
- Exhibit 3: Walker Woods Autoturn Analysis
- Exhibit 4: Walker Estates Autoturn Analysis
- Exhibit 5: Proposed Turn Lane Improvements
- Exhibit 6: OTO Major Thoroughfare Plan

APPENDICES

- Appendix A: Cost Estimate
- Appendix B: Collected Turning Movement Count Data Appendix C: Capacity Calculations





1. EXECUTIVE SUMMARY

1.1 Findings

- The property at the northeast and southeast corners of Tracker Road and Main Street is owned by the Walker family and was recently annexed and rezoned for two proposed subdivisions: Walker Woods Subdivision (located north of Tracker Road) and Walker Estates Subdivision (located south of Tracker Road)
- Due to the fact that the proposed intersections from this development connect to roads classified as Collector or higher, it is the City of Nixa's policy to require a Transportation Impact Study to be completed.
- Based on current City of Nixa policy, the developer will be donating sufficient right of way (hereinafter referred to as ROW) along the properties adjacent to both Main Street and Tracker Road where existing ROW width is less than OTO standards per the individual classification of the road. Tracker Road is classified as a Secondary Arterial and Main Street is classified as a Collector, according to the OTO.
- Additionally it is also the City's policy to require the developer to make necessary lane improvements to any street classified as a Collector or higher, according to the adopted OTO Major Thoroughfare Plan 2040, when the development generates a new intersecting City Street.
- Results of this Transportation Impact Study will determine the geometry of the required left turn lanes at 3 of the 4 newly proposed intersections.
- The new road connecting Walker Estates to Main Street will not require mitigation, as Main Street has recently been improved to 3 lanes in that location.

1.2 Recommendations

It is our recommendation that the City of Nixa approve the conceptual design of the proposed improvements described within this Transportation Impact Study. The recommendations are summarized as follows:

 Install required pavement and striping for turn lanes at the following 3 intersections: Main Street and Mandy Lane, Donald Street and Tracker Road, and Maxine Avenue and Tracker Road.



2. INTRODUCTION

2.1 Purpose

Morelock Builders & Associates (hereinafter referred to as MBA) has secured the services of Toth & Associates to complete a transportation impact study related to their Client's proposed subdivision for implementing traffic solutions that are in accordance with the City of Nixa, Missouri and the Ozarks Transportation Organization (hereinafter referred to as the OTO). This Transportation Impact Study (hereinafter referred to as TIS) summarizes the existing and future traffic parameters and provides recommendations to alleviate growth related traffic issues over a planning period, as recommended by the OTO. This TIS is classified as a Level II TIS, based on the peak hourly generated trips being between 100 and 499 trips.

2.2 Objectives

The following summarized scope of work was completed in preparation of this TIS.

- Determine the impact that the proposed subdivisions will have on the area, specifically regarding traffic flows at the 5 studied intersections. The intersections studied include the existing intersections of Tracker Road and Main Street and the 4 newly created intersections due to both subdivision developments.
- Utilize traffic count data that was collected as part of the TIS and growth rate data provided in previously approved studies to project anticipated traffic growth at the studied intersections.
- Describe the project in detail and what changes to existing intersections need to be made, based on findings herein.
- Estimate projected traffic due to the multiple types of proposed developments within both subdivisions.
- Analyze both the capacity of select intersections, utilizing the Highway Capacity Manual (2016).
- Perform Parking Evaluations, Multimodal Evaluations, a Site Distance Review and a Site Review of the newly proposed R3 and GC zoned developments.
- Provide a recommendation on the nature and type of improvements deemed necessary by the results of this TIS.



2.3 Intersections Studied

The following intersections have been studied extensively in the preparation of this traffic impact study:

- Tracker Road and Main Street (existing)
- Main Street and Mandy Lane (proposed)
- Donald Street and Tracker Road (proposed)
- Maxine Avenue and Tracker Road (proposed)
- Main Street and Greenbriar Drive (proposed but currently a 3 leg intersection)

2.4 Location Map of Project

The following map shows the location of the project, and the studied intersections:





3. DEVELOPMENT SITE

3.1 Existing Land Use

Prior to the generation of this TIS, the land in question was recently rezoned and annexed into the city limits. The land comprising Walker Woods subdivision currently has one residential dwelling on it and the land comprising Walker Estates subdivision currently has no structures on it and is primarily pasture. Traffic count data was acquired at the intersection of Tracker and Main for both the peak AM and PM hours, and traffic data at Greenbriar Drive in terms of project traffic entering/exiting that drive was estimated based on its existing land use. Due to the nature of the multifamily improvements, the residential area in and around Greenbriar Drive, Viola Street and Flora Street have been classified as "Residential Condo/Townhouses" according to the latest edition of the Institute of Transportation Engineers (ITE) Trip Generation Manual. The ITE Land Use Code is 230. Anticipated traffic and turning movements was estimated using this approach due to its current 'one way in, one way out' access onto Main. As appropriate, traffic count data was quantified from the intersection of Tracker and Main accordingly. Traffic directionality was estimated in line with corresponding AM/PM peak hour ratios observed during the traffic counts at Tracker Road and Main Street.

3.2 Proposed Land Use

As mentioned previously in this study, multiple types of proposed land uses will result from these two developments. Within the Walker Estates Subdivision, the following land use codes in the ITE Trip Generation Manual have been assumed: Business Park, Apartments, and Single-Family Homes. The respective ITE Land Use Codes are 770, 220 and 210. Independent variables for the Apartments and the Single-Family Homes are both "Dwelling Units (DU's), while the Business Park independent variable is total floor area in KSF. Between both Walker Estates and Walker Woods subdivisions, the combined "Business Parks" have a total floor area of approximately 37.5 KSF, total of 95 dwelling units from "Apartments" and a total of 79 dwelling units of "Single Family Homes". Using OTO guidance, floor area was chosen as the independent variable in the "Business Parks" land use, as it is more general in nature. Refer to Section 5 of this study for detailed trip generation tables.

Future growth in terms of adjacent traffic along Tracker Road and Main Street will occur, and a rate of 2% is assumed. Full buildout of both subdivisions is expected to occur within 2 years.

3.3 Proposed Access Points

As can be seen previously in this study, as well as in the attached Preliminary Plats for both subdivisions (Exhibits 1 and 2), there are 4 proposed access points; two at Walker Woods



Subdivision and two at Walker Estates Subdivision.

Walker Woods proposed access points consist of new intersections at Mandy Lane and Main Street and Tracker Road and Donald Street. Walker Estates proposed access points consist of a new intersections at Maxine Avenue and Tracker Road and a modified intersection at Greenbriar Drive and Main Street. The modified intersection will transition from a 3-leg intersection to a 4-leg intersection.

3.4 Relationship to Current Plans

Based on discussions with City staff, as well as long range OTO plans, the proposed subdivision and road improvements are in line with the future vision of the City of Nixa. All planned drives, both commercial and residential will comply design standards.

3.5 Multimodal Evaluation

The subdivision will be designed in accordance with City standards, as well as ADA regulations. Accessibility will be provided for transit services. Bicycle lanes are currently in place in select locations running parallel with Main Street. Bicycle lanes will be incorporated into the design of the intersection of Mandy Lane and Main Street, to continue the recently constructed bicycle lane to the north. Sidewalks will be provided in both subdivisions and will meet ADA guidelines for safe pedestrian movements.

3.6 Study Scenarios

The forecasts for this Level II TIS will include three "No-Build" scenarios and two "Build" scenarios. The "No Build" scenarios will consist of traffic forecast for Existing Conditions, the year of full build out, and 20 years after full build out. The "Build" scenarios will consist of traffic forecast for the year of full build out, and 20 years after the full build out. 2021 is the existing year, 2023 is the proposed year of full build out, and 2043 is 20 years after full build out.

Forecasts for future year scenarios will be based on an accepted growth rate of surrounding traffic of 2%. Adding traffic from the proposed developments to the related "No-Build" scenarios provides the expected traffic for the full build out scenario forecasts.



4. EXISTING CONDITIONS

4.1 Description of Key Roads

The following streets surround the area of expansion:

- Main Street
 - o Functional Classification: Collector
 - 35 MPH posted speed limit south of Tracker Road and 40 MPH posted speed limit north of Tracker Road
- Tracker Road
 - Functional Classification: Secondary Arterial
 - 30 MPH posted speed limit
- Greenbriar Drive
 - o Functional Classification: Local Road
 - o No speed limit posted; City-wide base speed limit of 30 MPH applies

Refer to Exhibit 6, which depicts the OTO's road classifications throughout the area, in their Major Thoroughfare Plan.

4.2 Intersection Traffic Volumes and Turning Counts

As mentioned in the Introduction of this study, raw traffic count data was collected at the intersection of Tracker Road and Main Street in June of 2021. Additionally, ITE trip generation estimates were performed to estimate traffic at Greenbriar Drive, as it is a one way in one way out intersection into the existing multifamily development. Supporting documentation can be found in Appendix B of this study. The following 4 exhibits depict AM and PM peak hour turning movement diagrams (TMD) at both studied intersections as they existed in June of 2021.





Exhibit 4.2.1 Tracker Rd. & Main St. TMD - AM Peak Hour for Existing Scenario (2021)





Exhibit 4.2.2 Tracker Rd. & Main St. TMD - PM Peak Hour for Existing Scenario (2021)





Exhibit 4.2.3 Greenbriar Dr. & Main St. TMD - AM Peak Hour for Existing Scenario (2021)





Exhibit 4.2.4 Greenbriar Dr. & Main St. TMD - PM Peak Hour for Existing Scenario (2021)

Based on the field collected traffic count data, the Tracker Road and Main Street AM Peak Hour occurs from 7 AM to 8 AM, while the PM Peak Hour is from 4:30 PM to 5:30 PM. This also holds true and can be applied to the intersection at Greenbriar Drive and Main Street.



4.3 Available Bike and Pedestrian Infrastructure

As mentioned previously in this study, bicycle lanes were recently added to the intersection of Tracker Road and Main Street when it was improved. All legs of the intersection, except for east on Tracker, contain dedicated bicycle lanes. The new local roads within the subdivision will be designed in accordance with the City of Nixa standards and will accommodate anticipated bicycle and pedestrian traffic safely.

4.4 Available Transit Infrastructure

As mentioned previously in this study, the proposed infrastructure will be designed in accordance with the City of Nixa standards and will accommodate transit, such as OAT's.



5. PROJECTED TRAFFIC

5.1 Estimated Trip Generation and/or Relocated Traffic

Utilizing the latest edition of the ITE Trip Generation Manual, see the following tables:

ITE LAND USE CODE	DESCRIPTION OF ITE CODE	UNITS	EXPECTED UNITS	тоти	TOTAL GENERATED TRIPS			DISTRIBUTION OF GENERATED TRIPS			
			Ind. Variable	Daily	AM HOUR	PM HOUR	AM In	AM Out	PM In	PM Out	
230	Resd. Condo/Townhouse	DU 1	87	505	38	45	7	32	30	15	
	DU ¹ = Dwelling Units			-							

Table 5.1.1: Tri	Generation	for existing	Greenbriar	Drive Development
10010 011111 111	Generation	TOT CAUSEINS	Greenwinar	Brive Bevelopment

Table 5.1.2: Trip Generation for Walker Estates Proposed Subdivision

ITE LAND USE CODE	DESCRIPTION OF ITE CODE	UNITS	EXPECTED UNITS	TOT	TOTAL GENERATED TRIPS			DISTRIBUTION OF GENERATED TRIPS			
			Ind. Variable	Daily	AM HOUR	PM HOUR	AM In	AM Out	PM In	PM Out	
770	Business Park	KSF ¹	17.5	218	25	22	21	4	6	16	
220	Apartments	DU ²	95	632	48	59	10	39	38	21	
210	Single Family Homes	DU ²	25	238	19	25	5	14	16	9	
			Totals	1088	92	106	36	57	60	46	

Table 5.1.3: Trip Generation for Walker Woods Proposed Subdivision

ITE LAND USE CODE	DESCRIPTION OF ITE CODE	UNITS	EXPECTED UNITS	TOTA	TRIPS	DISTRIBUTION OF GENERATED TRIPS				
			Ind. Variable	Daily	AM HOUR	PM HOUR	AM In	AM Out	PM In	PM Out
770	Business Park	KSF ¹	20	249	28	25	24	4	7	19
210	Single Family Homes	DU ²	54	514	41	54	10	30	34	20
			Totals	763	69	79	34	34	41	39



5.2 Trip Distribution and Assignment

Based on the tables in Section 5.1 above, for the Greenbriar Drive development, the total combined AM Peak Hour of 39 trips (rounded) was comprised of 7 entering trips and 32 exiting trips. Similarly, the PM Peak Hour of 45 was comprised of 30 entering trips and 15 exiting trips.

Based on the tables in Section 5.1 above, for the Walker Estates Subdivision, the total combined AM Peak Hour of 93 trips (rounded) was comprised of 36 entering trips and 57 exiting trips. Similarly, the PM Peak Hour of 106 was comprised of 60 entering trips and 46 exiting trips.

Based on the tables in Section 5.1 above, for the Walker Woods Subdivision, the total combined AM Peak Hour of 68 trips (rounded) was comprised of 34 entering trips and 34 exiting trips. Similarly, the PM Peak Hour of 80 (rounded) was comprised of 41 entering trips and 39 exiting trips.



5.3 Map of Projected Directional Distribution

The following map shows the directional distribution of anticipated traffic flow at the proposed Walker Woods Subdivision located at the northeast corner of Tracker Road and Main Street:





The following map shows the directional distribution of anticipated traffic flow at the proposed Walker Estates Subdivision located at the southeast corner of Tracker Road and Main Street:





5.4 Total Future Traffic (AM/PM)

Utilizing a growth rate of 2% annually, surrounding traffic growth was calculated and applied to the Year of Full Buildout (2023) condition, and the 20 Years after Full Build Out (2043) condition. The following four exhibits depict the "No-Build Scenarios for the 2023 Year of full buildout condition.

Exhibit 5.4.1 Tracker Rd. & Main St. TMD - AM Peak Hour for No-Build Scenario (2023)







Exhibit 5.4.2 Tracker Rd. & Main St. TMD - PM Peak Hour for No-Build Scenario (2023)





Exhibit 5.4.3 Greenbriar Drive. & Main St. TMD - AM Peak Hour for No-Build Scenario (2023)





Exhibit 5.4.4 Greenbriar Drive. & Main St. TMD - PM Peak Hour for No-Build Scenario (2023)

The following four exhibits depict the "No-Build Scenarios for the 2043 20 years after Full Buildout Conditions.




Exhibit 5.4.5 Tracker Rd. & Main St. TMD - AM Peak Hour for No-Build Scenario (2043)





Exhibit 5.4.6 Tracker Rd. & Main St. TMD - PM Peak Hour for No-Build Scenario (2043)





Exhibit 5.4.7 Greenbriar Drive. & Main St. TMD - AM Peak Hour for No-Build Scenario (2043)





Exhibit 5.4.8 Greenbriar Drive. & Main St. TMD - PM Peak Hour for No-Build Scenario (2043)

The following ten exhibits depict the "Build Scenarios for the 2023 Year of Full Buildout Conditions.





Exhibit 5.4.9 Tracker Rd. & Main St. TMD - AM Peak Hour for Build Scenario (2023)





Exhibit 5.4.10 Tracker Rd. & Main St. TMD - PM Peak Hour for Build Scenario (2023)





Exhibit 5.4.11 Greenbriar Drive. & Main St. TMD - AM Peak Hour for Build Scenario (2023)





Exhibit 5.4.12 Greenbriar Drive. & Main St. TMD - PM Peak Hour for Build Scenario (2023)





Exhibit 5.4.13 Mandy Lane & Main St. TMD - AM Peak Hour for Build Scenario (2023)





Exhibit 5.4.14 Mandy Lane & Main St. TMD - PM Peak Hour for Build Scenario (2023)





Exhibit 5.4.15 Tracker Rd. & Donald St. TMD - AM Peak Hour for Build Scenario (2023)





Exhibit 5.4.16 Tracker Rd. & Donald St. TMD - PM Peak Hour for Build Scenario (2023)













The following ten exhibits depict the "Build Scenarios for the 2043 Year of Full Buildout Conditions.





Exhibit 5.4.19 Tracker Rd. & Main St. TMD - AM Peak Hour for Build Scenario (2043)





Exhibit 5.4.20 Tracker Rd. & Main St. TMD - PM Peak Hour for Build Scenario (2043)





Exhibit 5.4.21 Greenbriar Drive. & Main St. TMD - AM Peak Hour for Build Scenario (2043)





Exhibit 5.4.22 Greenbriar Drive. & Main St. TMD - PM Peak Hour for Build Scenario (2043)





Exhibit 5.4.23 Mandy Lane & Main St. TMD - AM Peak Hour for Build Scenario (2043)





Exhibit 5.4.24 Mandy Lane & Main St. TMD - PM Peak Hour for Build Scenario (2043)





Exhibit 5.4.25 Tracker Rd. & Donald St. TMD - AM Peak Hour for Build Scenario (2043)





Exhibit 5.4.26 Tracker Rd. & Donald St. TMD - PM Peak Hour for Build Scenario (2043)









Exhibit 5.4.28 Tracker Rd. & Maxine Ave. TMD - PM Peak Hour for Build Scenario (2043)





6. CAPACITY ANALYSIS FOR THE STUDIED INTERSECTIONS

6.1 Existing and Proposed Scenarios for AM/PM

As mentioned previously in this report, conditions were analyzed for the following scenarios: Build and No Build scenarios for the years 2021, 2023, and 2043.

Using information provided in this report and from the field study, the capacities of select intersections were studied in detail and analyzed for future build conditions. Due to City Policy, all of the new intersections except for Greenbriar Drive and Main Street will be adding necessary turn lanes along the Collector (Main Street) and the Secondary Arterial (Tracker Road). It is anticipated that the city will make improvements in the future north of Tracker Road along Main Street, likely to make accommodations for a continuous turn lane from its intersection with Tracker Road north to an undetermined location. It is for that reason that a detailed capacity analysis was not performed for the Mandy Lane and Main Street intersection. Additionally, as the existing Greenbriar Drive and Main Street intersection has already been improved with the widening of Main Street to 3 lanes in that area, a detailed capacity analysis was not performed at that intersection.

The intersection of Tracker Road is currently a signalized intersection and was recently expanded. As this intersection already has a signal, the focus of the capacity calculations in this study have been on the remaining intersections proposed along Tracker Road. Should further analysis of this signalized intersection be required, additional site-specific information and further field analysis will be needed.

6.2 Existing and Future Level of Service

Traffic operations for the studied intersections were analyzed using procedures documented in the *Highway Capacity Manual (HCM)* 6th Edition, Transportation Research Board, 2016. From this analysis, a key predictor or "level of service" rating of the traffic operational conditions was obtained. In general, level of service (LOS) is a qualitative assessment of traffic operational conditions within a traffic stream in terms of average stopped delay per vehicle at a controlled intersection.

Levels of service are described by a letter designation of either A, B, C, D, E, or F, with LOS A representing essentially uninterrupted flow, and LOS F representing a breakdown of traffic flow with noticeable congestion and delay. Unsignalized, or stop sign controlled, intersection capacity analyses produce LOS results for each movement which must yield to conflicting traffic at the intersection. The table below summarizes LOS criteria for unsignalized (stop sign controlled) intersections.



Table 6.2.1: Level of Service (LOS) Criteria for Stop Sign Controlled Interse	ctions
---	--------

	Average Control Delay per Vehicle (sec/veh)
Level of Service	Stop Sign Controlled Intersections
A	≤ 10
В	> 10 to 15
С	> 15 to 25
D	> 25 to 35
E	> 35 to 50
F	> 50
HCM 6th Edition, Exhibit 20-2	

Calculations and guidance from the HCM were utilized to evaluate traffic operations at the aforementioned studied stop sign controlled intersections for this study. All intersection movements for both Tracker Road and Donald Street as well as for Tracker Road and Maxine Avenue are anticipated to perform at LOS B or better. Capacity calculations are shown in Appendix C of this study.



7. PARKING EVALUATION

7.1 Parking to be Provided on Site

A total of 323 parking stalls will be provided on site, over the General Commercial (GC) and Apartments (R3) proposed between the two subdivisions. To further break this down, 145 stalls are provided for the proposed apartments and 178 stalls are provided for the general commercial parcels.

7.2 Parking Required by Nixa City Code

According to the City of Nixa's Zoning Code, multifamily residential developments are required to provide 1.5 spaces per dwelling. The units provide a total of 145 stalls and are required to provide 143 stalls, thereby complying with Zoning regulations.

According to the aforementioned Zoning Code, commercial shopping plazas are required to provide 1 space per 250 square feet of gross floor area. The units provide a total of 178 stalls and are required to provide 150 stalls, thereby complying with Zoning regulations.



8. SIGHT DISTANCE REVIEW

This study has taken a preliminary step in considering the importance of stopping sight distances. Two areas of particular concern by the public are the proposed intersections of Mandy Lane and Main Street and that of Tracker Road and Donald Street.

8.1 Minimum Stopping Sight Distances Required

Based on design guidance from the AASHTO "Green Book" required stopping sight distances for both of the aforementioned intersections were analyzed. The required stopping sight distance for the intersection of Mandy Lane and Main Street is approximately 315 feet. This assumes a grade of 3% along Main Street to the north of the proposed intersection, and a posted speed limit of 40 MPH.

The required stopping sight distance for the intersection of Tracker Road and Donald Street is approximately 227 feet. This assumes a grade of 9% along Tracker Road to the east of the proposed intersection, and a posted speed limit of 30 MPH.

8.2 Stopping Sight Distances Provided

Based on the site survey and reconnaissance, the stopping sight distance provided by the placement of the intersection of Mandy Lane and Main Street is approximately 340'. In the same fashion, the stopping sight distance provided by the placement of the intersection of Tracker Road and Donald Street is approximately 335'.

According to the methodology provided herein, both of the proposed intersections of concern meet the required stopping sight distance.

8.3 Additional Recommendations

In both cases, measured sight distance satisfies the minimum requirements and is acceptable. For either access, tree trimming may be necessary within the right-of-way to ensure these acceptable sight lines.



9. SIGHT REVIEW

9.1 MUTCD Standards

Utilizing the Manual on Uniform Traffic Control Devices (MUTCD), 2009 Edition, taper distances for the three required left turn lanes were computed. Additionally, sidewalks and ramps will be provided throughout both of the subdivisions that will be designed to meet or exceed ADA standards. Based on the proposed amount of generated traffic at each of the two subdivisions, circulation throughout will be at acceptable levels for cars, trucks, buses, bicycles and pedestrians.

9.2 Site Circulation and Turning Templates

The subdivisions contain multiple cul-de-sacs that were laid out and will be designed to meet or exceed City of Nixa standards. Utilizing Autodesk's Civil 3D software, an Autoturn Analysis was performed throughout the proposed streets in both subdivisions. The design vehicle was a school bus with a width of 8 feet and a length of approximately 36 feet. Refer to the attached Exhibits 3 and 4 which depict wheel tracking for the design vehicle, as it traverses the subdivisions.

9.3 Site Conflicts

Site conflicts are expected to be minimal, as the R3 and GC zoned portions will each have more than sufficient parking spaces based on preliminary layouts. Street parking is expected to be minimal and sufficient signage shall be put in place in restricted areas with limited maneuverability.

One defining aspect of both of the subdivisions is that of the known karst features on the properties. Nearly all aspects of the road layout, as well as the zoning and lot layouts relied on compatibility and safety in terms of adapting to the said karst features. The majority of the known karst features will be platted into common areas to be maintained by the future Property Owners Association or Home Owners Association.



10. MAIN FINDINGS OF THE STUDY

This study has shown the projected impacts that the two proposed subdivisions will have on the two existing studied intersections and the remaining proposed intersections throughout the course of the planned phasing. As can be seen in the attached Preliminary Plats (Exhibits 1 and 2 of this study), sufficient right of way (ROW) will be dedicated to bring both Tracker Road and Main Street up to current City of Nixa standard ROW widths. Additionally, based on City of Nixa policy, three dedicated left turn lanes with appropriate taper and storage lengths are being added. Two of the three turn lanes are added along Tracker Road, at Donald Street and Maxine Avenue, and the third will be added at along Main Street at Mandy Lane.

10.1 Right Turn and Left Turn Warrants

Based on the exhibit below, according to MoDOT's guidelines (940.9.1 in the MoDOT Engineering Policy Guide), left turn lanes are not warranted at the three aforementioned intersection locations.





11. SUMMARY OF FINDINGS AND RECOMMENDATIONS

As shown in Section 10 of this study, dedicated left turn lanes are not warranted for this development. However, the City of Nixa has stated that per City Policy (Resolution No. 2009-91), all roads classified as a collector or higher are required to meet the three lane road typical section outlined in the Ozarks Transportation Organization (OTO). Therefore, dedicated left turn lanes are proposed for this development. A preliminary layout for the proposed dedicated left turn lanes on Tracker Road and Main Street is shown on the attached Exhibit 5. A preliminary opinion of probable construction costs for the dedicated left turn lanes has been provided in Appendix A. The preliminary opinion of probable construction costs shows an estimated cost of \$297,778 for these improvements. The City has mentioned that they have future plans to widen Main Street in this area. The City has asked the developer to consider widening Tracker Road from the intersection of Tracker and Main to the east end of the development in lieu of constructing the turn lane on Main Street. The cost to widen Tracker Road is estimated to exceed the cost to install the three individual left turn lanes. The developer is willing to support public road improvements in this area up to the amount of \$300,000.

11.1 Geometric and Lane Recommendations to Accommodate Proposed Traffic Volume

Utilizing the AASHTO "Green Book", and the MUTCD, a preliminary layout has been proposed for the three new turn lanes in question. Taper and deceleration lengths vary per the posted speed limit and are in line with AASHTO minimums. For detailed dimensions refer to Exhibit 5.



EXHIBITS

- 1. WALKER WOODS PRELIMINARY PLAT
- 2. WALKER ESTATES PRELIMINARY PLAT
- 3. WALKER WOODS AUTOTURN ANALYSIS
- 4. WALKER ESTATES AUTOTURN ANALYSIS
- 5. PROPOSED TURN LANE IMPROVEMENTS
- 6. OTO MAJOR THOROUGHFARE PLAN





SINGLE F	AMILY RESIDENTIA	AL DISTRICT
LOT #	SQ. FT.	AC.
1	10,047	0.23
2	10,010	0.23
3	11,440	0.26
4	11,440	0.26
5	11,356	0.26
6	14,074	0.32
7	13,396	0.31
8	12,758	0.29
9	13,842	0.32
10	10,010	0.23
11	10,010	0.23
12	10,000	0.23
13	15,384	0.35
14	11,416	0.26
15	8,925	0.20
16	9,608	0.22
17	10,673	0.25
18	10.220	0.23

SINGLE FA	MILY RESIDEN	TIAL DISTRICT
LOT #	SQ FT	AC

19	16,548	0.38
20	20,611	0.47
21	10,010	0.23
22	10,010	0.23
23	15,259	0.35
24	10,886	0.25
25	10,010	0.23
26	10,970	0.25
27	12,373	0.28
28	16,187	0.37
29	16,812	0.39
30	11,354	0.26
31	11,507	0.26
32	11,520	0.26
33	11,520	0.26
34	11,520	0.26
35	11,520	0.26
36	12,022	0.28

SINGLE F	AMILY RESIDENTIA	AL DISTRI
LOT #	SQ. FT.	AC.
37	13,898	0.32
38	12,284	0.28
39	12,493	0.29
40	14,007	0.32
41	14,984	0.34
42	10,010	0.23
43	10,010	0.23
44	10,578	0.24
45	11,175	0.26
46	11,018	0.25
47	9,724	0.22
48	9,724	0.22
49	9,724	0.22
50	9,724	0.22
51	9,724	0.22
52	9,724	0.22
53	9,724	0.22
54	9,857	0.23

GENERAL	COMMERCIAL	
LOT #	SQ. FT.	AC.
GC1	55,264	1.27
GC2	44,979	1.03
	I AREA SQ. FT.	AC.
C1	25,676	0.59
C2	83,615	1.92
C3	85,198	1.96
00	-	



BASED ON THE PRELIMINARY FIRM PANEL 29043C0058D, WITH A PRELIMINARY DATE OF 2019/09/20

DECLARATION BY SURVEYOR

I, JOSEPH R. PULLIAM, DO HEREBY CERTIFY THAT THIS PRELIMINARY PLAT WAS PREPARED UNDER MY PERSONAL SUPERVISION FROM AN ACTUAL SURVEY OF THE LAND HEREIN, IN ACCORDANCE WITH THE CURRENT MISSOURI STANDARDS FOR PROPERTY BOUNDARY SURVEYS.

PHYSICAL EVIDENCE OF IMPROVEMENTS IS SHOWN FROM INFORMATION TAKEN BY VISUAL INSPECTION OF THE PREMISES. EASEMENTS SHOWN ARE THOSE WRITTEN, PROVIDED, OR DISCOVERED AND MAY NOT BE ALL INCLUSIVE. APPARENT OWNERSHIPS AS SHOWN ARE BASED UPON INFORMATION PROVIDED BY OTHERS AND DO NOT REPRESENT AN OPINION AS TO TITLE. THIS PRELIMINARY PLAT IS INTENDED FOR REVIEW AND PLANNING PURPOSES ONLY AND IS NOT TO BE USED BY ANYONE FOR CONVEYANCE OF LANDS OR TITLE OF REAL ESTATE.

COMMON AREA

COMMON AREAS DEPICTED ON THIS SUBDIVISION PLAT AS LOTS C1 THROUGH C4 SHALL BE CONVEYED IN FEE-TITLE TO THE HOME OWNERS ASSOCIATION FOR SAID SUBDIVISION FOLLOWING COMPLETION OF CONSTRUCTION AND THE RECORDING OF FINAL PLAT THEREOF. THESE COMMON AREAS ARE HEREAFTER RESTRICTED FROM ADDITIONAL SUBDIVIDING OR FROM THE CONSTRUCTION AND/OR ERECTION OF ANY STRUCTURE WHETHER PERMANENT OR TEMPORARY. THESE AREAS ARE TO BE RESERVED AND SET ASIDE IN PERPETUITY AS "GREEN SPACE", THE ONLY PERMITTED USE OF SAID AREAS BEING THE INSTALLATION OF LANDSCAPING, INCLUDING THE PLANTING OF TREES, AND GENERAL MAINTENANCE ACTIVITIES SUCH AS MOWING AND DEBRIS REMOVAL. ALL TAXES, EXPENSES AND OTHER COST RELATED TO THESE COMMON AREAS ARE THE SOLE RESPONSIBILITY OF THE HOMEOWNERS ASSOCIATION.

DATE OF PREL TOTAL ACREA TOTAL NUMBE CURRENT ZON

PROPOSED ZO R-1 SMALLEST R-1 LARGEST

NOTES

- 4.

LEGEND

 ADJOINING PROPERTY LINE
 UTILITY EASEMENT LINE
 SETBACK LINE
 SINKHOLE BOUNDARY
SINKHOLE

SINKHOLE (NO CONSTRUCTION LIMITS)

PRELIMINARY PLAT WALKER WOODS SUBDIVISION A SUBDIVISION IN THE SOUTHEAST QUARTER OF THE SOUTHEAST QUARTER OF SECTION 1, TOWNSHIP 27 NORTH

RANGE 22 WEST OF THE FIFTH PRINCIPAL MERIDIAN, CITY OF NIXA, CHRISTIAN COUNTY, STATE OF MISSOURI.

OWNER: DON E. WALKER AND LOIS M. WALKER

DEVELOPER: MORELOCK BUILDERS & ASSOCIATES

722 W. OLIVE STREET SPRINGFIELD, MISSOURI 65806



PROPERTY DESCRIPTION

ALL THAT PART OF THE SOUTHEAST QUARTER OF THE SOUTHWEST QUARTER OF SECTION 1 - TOWNSHIP 27 NORTH - RANGE 22 WEST OF THE FIFTH PRINCIPAL MERIDIAN, CHRISTIAN COUNT, STATE OF MISSOURI, DESCRIBED AS FOLLOWS: COMMENCING AT THE SOUTHEAST CORNER OF SAID SOUTHEAST QUARTER OF THE SOUTHWEST QUARTER AND MEASURE N01°44'43"E ALONG THE EAST LINE THEREOF 1328.70 FEET TO THE NORTHEAST CORNER THEREOF; THENCE N87°47'06"W ALONG THE NORTH LINE THEREOF 15.0 FEET TO THE POINT OF BEGINNING; THENCE S01°44'43"W 1308.54 FEET TO A POINT ON THE NORTH RIGHT OF WAY LINE OF TRACKER ROAD: (THE FOLLOWING FOLLOWS THE NORTH R/W OF TRACKER ROAD) THENCE N87°10'30"W 754.49 FEET; THENCE N02°59'28"E 23.57 FEET; THENCE N87°04'01"W 490.18 FEET: THENCE N42°51'10"W 35.82 FEET TO A POINT ON THE EAST RIGHT OF WAY LINE OF MAIN STREET; (THE FOLLOWING FOLLOWS THE EAST R/W OF MAIN STREET) THENCE N01°27'03"E 339.90 FEET; THENCE N88°07'29"W 13.97 FEET; THENCE N02°01'18"E 242.62 FEET TO A POINT ON THE SOUTH LINE OF THE NORTHWEST QUARTER OF THE SOUTHEAST QUARTER OF THE SOUTHWEST QUARTER; THENCE S87°30'09"E ALONG THE SOUTH LINE THEREOF 631.22 FEET TO THE SOUTHEAST CORNER THEREOF: THENCE N01°45'07"E ALONG THE EAST LINE THEREOF 661.06 FEET TO THE NORTHEAST CORNER THEREOF; THENCE S87°47'06"E ALONG THE NORTH LINE OF THE NORTHEAST QUARTER OF THE SOUTHEAST QUARTER OF THE SOUTHWEST QUARTER 652.40 FEET TO THE POINT OF BEGINNING, CONTAINING 28.39 ACRES.

LIMINARY PLA	T SUBMITTAL: JU	JNE 18, 2021
AGE OF THE DE	EVELOPMENT: 28	3.39
ER OF LOTS:	56	
NING:	R-1 (SINGLE FAMIL` GC (GENERAL COM	Y RESIDENTIAL DISTRICT) IMERCIAL)
ONING:	R-1 (SINGLE FAMIL` GC (GENERAL COM	Y RESIDENTIAL DISTRICT) IMERCIAL)
T LOT:	LOT 12, 10,000 SQU/	ARE FEET
LOT:	LOT 20, 20,611 SQU	ARE FEET

1. MINIMUM LOT WIDTH IS 60 FEET FOR R-1 (SINGLE FAMILY RESIDENTIAL DISTRICT). 2. MINIMUM LOT WIDTH IS NONE FOR GC (GENERAL COMMERCIAL).

3. MINIMUM LOT SIZE IS 6,600 SQUARE FEET.

R-1 (SINGLE FAMILY RESIDENTIAL DISTRICT) 25 FOOT BUILDING SETBACK LINE IN THE FRONT OF ALL LOTS. 20 FOOT BUILDING SETBACK LINE IN THE REAR OF ALL LOTS. 5 FOOT BUILDING SETBACK LINE ON THE SIDE OF ALL LOTS. 12 FOOT BUILDING SETBACK LINE ON THE SIDE OF ALL LOTS WITH LOCAL STREET FRONTAGE.

5. GC (GENERAL COMMERCIAL) 20 FOOT BUILDING SETBACK LINE IN THE FRONT OF ALL LOTS. 20 FOOT BUILDING SETBACK LINE IN THE REAR OF ALL LOTS. 10 FOOT BUILDING SETBACK LINE ON THE SIDE OF ALL LOTS

15 FOOT BUILDING SETBACK LINE ON THE SIDE OF ALL LOTS WITH LOCAL STREET FRONTAGE. 6. ROADS ARE TO BE DEDICATED FOR THE USE OF THE PUBLIC.

7. 10 FOOT UTILITY EASEMENT ON FRONT AND REAR OF ALL LOTS.

8. COMMON AREA (C1, C2, C3 & C4), ARE TO BE COMMON AREA.

9. APPROXIMATE LOCATION OF PROPOSED FIRE HYDRANT (TYPICAL).

10. PRELIMINARY SINKHOLE FLOOD OUTLINE FOR THE 100-YEAR FLOOD. SEE FLOOD PLAIN NOTE THIS SHEET. 11. PRELIMINARY SINKHOLE FLOOD OUTLINE FOR THE 500-YEAR FLOOD. SEE FLOOD PLAIN NOTE THIS SHEET. 12. APPROXIMATE LOCATION OF PROPOSED DETENTION AREAS (TYPICAL).

13. ROADS, UTILITIES AND OTHER ENGINEERING DESIGN ITEMS ARE SHOWN HEREON FOR PLANNING PURPOSES

ONLY AND WILL BE DESIGNED SEPARATELY BY LICENSED ENGINEER. 14. PRE-EXISTING STRUCTURE LOCATED ON LOTS 21 AND 22 EXEMPT FROM SETBACK REQUIREMENTS UNTIL SUCH TIME AS STRUCTURE IS REMOVED, ALL NEW STRUCTURES MUST CONFORM TO LOT SETBACKS.

15. NO DIRECT ACCESS TO TRACKER ROAD OR MAIN STREET FROM ADJOINING LOTS. ALL LOT ACCESS MUST BE FROM ADJOINING STREETS WITHIN SUBDIVISION INTERIOR.

> BASIS OF BEARING MISSOURI STATE PLANE NAD 83 CENTRAL ZONE VERTICAL DATUM = NAVD1988



NOTE: DRAWING REPRODUCTION AND SCALING MAY CHANGE THE INDICATED GRAPHIC SCALES H. SCALE: 1" = 100'



mo1call.com

JOSEPH R. PULLIAM - LAND SURVEYOR MO# PLS-2006016641 Ш C-001

Δ

Σ

PR

PULLIAM NUMBER 5-200601



SINGLE F	AMILY RESIDENTI	AL DISTRICT
LOT #	SQ. FT.	AC.
1	10,602	0.24
2	11,613	0.27
3	11,613	0.27
4	10,170	0.23
5	10,009	0.23
6	10,069	0.23
7	11,540	0.26
8	11,192	0.26
9	10,789	0.25
10	10,758	0.25
11	8,057	0.18
12	8,129	0.19
13	7,497	0.17

LOT #	SQ. FT.	AC.
14	11,148	0.26
15	10,670	0.24
16	15,077	0.35
17	11,328	0.26
18	10,002	0.23
19	10,050	0.23
20	10,492	0.24
21	11,409	0.26
22	11,114	0.26
23	10,435	0.24
24	10,010	0.23
25	9,794	0.22

SINGLE FAMILY RESIDENTIAL DISTRICT

CO

MMON	IAREA	
OT #	SQ. FT.	AC.
C1	28,919	0.66
C2	448,246	10.29
NERAL	COMMERCIAL	
OT #	SQ. FT.	AC.
GC1	72,410	1.66
GH-DENSITY MULTI-FAMILY		
OT #	SQ. FT.	AC.
H1	75,979	1.74
H2	237,464	5.45

— — — — — UTILITY EASEMENT LINE ----- SETBACK LINE _____

(NO CONSTRUCTION LIMITS)

ADJOINING PROPERTY LINE

15' UTILITY EASEMENT

BOOK G PAGE 484

COPPER LEAF

BOOK 370

PAGE 1419

N87°10'30"W 754.49' MEAS.-

ELECTRIC EASEMENT

350.0' GC - (GENERAL COMMERCIAL) R-1 (SINGLE FAMILY RESIDENTIAL

> SINKHOLE BOUNDARY

BOOK 2007 PAGE 2656

SINKHOLE

SINKHOLE BOUNDARY

LEGEND

____ __ ___

PRELIMINARY PLAT WALKER ESTATES SUBDIVISION A SUBDIVISION IN THE NORTHEAST QUARTER OF THE NORTHWEST QUARTER OF SECTION 12, TOWNSHIP 27 NORTH.

RANGE 22 WEST OF THE FIFTH PRINCIPAL MERIDIAN, CITY OF NIXA, CHRISTIAN COUNTY, STATE OF MISSOURI.

OWNER: DON E. WALKER AND LOIS M. WALKER

DEVELOPER: MORELOCK BUILDERS & ASSOCIATES

722 W. OLIVE STREET SPRINGFIELD, MISSOURI 65806



PROPERTY DESCRIPTION

ROBERT HUNSAKER

BOOK 341 PAGE 806

QUARTER CORNER SECTION 1 & 12

EXISTING FIRE HYDRANT

ROGER ECKLEY

BOOK 2007 PAGE 5222

SEE NOTE 11

FLOOD NOTE

AND ARE USED AS A REFERENCE ONLY.

DECLARATION BY SURVEYOR

EASEMENT VACATION

DEPICTED HEREON.

COMMON AREA

BY GRAPHIC PLOTTING ONLY, THIS PROPERTY IS IN ZONE X OF THE FLOOD INSURANCE RATE MAP,

THE SINKHOLE FLOOD OUTLINES SHOWN FOR THE 100-YEAR AND 500-YEAR FLOODPLAINS ARE

BASED ON THE PRELIMINARY FIRM PANEL 29043C0058D, WITH A PRELIMINARY DATE OF 2019/09/20

I, JOSEPH R. PULLIAM, DO HEREBY CERTIFY THAT THIS PRELIMINARY PLAT WAS PREPARED UNDER MY PERSONAL SUPERVISION FROM AN ACTUAL SURVEY OF THE LAND HEREIN, IN

ACCORDANCE WITH THE CURRENT MISSOURI STANDARDS FOR PROPERTY BOUNDARY SURVEYS.

PHYSICAL EVIDENCE OF IMPROVEMENTS IS SHOWN FROM INFORMATION TAKEN BY VISUAL INSPECTION OF THE PREMISES. EASEMENTS SHOWN ARE THOSE WRITTEN, PROVIDED, OR

DISCOVERED AND MAY NOT BE ALL INCLUSIVE. APPARENT OWNERSHIPS AS SHOWN ARE BASED UPON INFORMATION PROVIDED BY OTHERS AND DO NOT REPRESENT AN OPINION AS TO TITLE.

THIS PRELIMINARY PLAT IS INTENDED FOR REVIEW AND PLANNING PURPOSES ONLY AND IS NOT

BY APPROVAL OF THE FINAL PLAT OF WALKER ESTATES SUBDIVISION BY THE CITY OF NIXA ALL

EXISTING PUBLIC UTILITY EASEMENTS AND PUBLIC ROAD RIGHT-OF-WAY (OF RECORD OR NOT OF

RECORD) LOCATED WITHIN THE BOUNDARY OF SAID SUBDIVISION BUT NOT SPECIFICALLY CALLED OUT AND/OR GRAPHICALLY DEPICTED HEREON SHALL HENCEFORTH BECOME ABANDONED,

DISSOLVED AND VACATED. ANY EXISTING UTILITY STRUCTURE, LINE OR APPURTENANCE

REGARDLESS OF TYPE LOCATED WITHIN ANY HEREINAFTER VACATED EASEMENT OR RIGHT-OF-WAY MAY REMAIN IN PLACE UNTIL SUCH TIME AS REPAIR, UPGRADE OR RELOCATION

BECOME NECESSARY. ONCE REPAIR, UPGRADE OR RELOCATION BECOME NECESSARY SAID

UTILITY STRUCTURE MUST BE RELOCATED INTO ONE OF THE NEWLY ESTABLISHED EASEMENTS

COMMON AREAS DEPICTED ON THIS SUBDIVISION PLAT AS LOTS C1 THROUGH C2 SHALL BE CONVEYED IN FEE-TITLE TO THE HOME OWNERS ASSOCIATION FOR SAID SUBDIVISION

FOLLOWING COMPLETION OF CONSTRUCTION AND THE RECORDING OF FINAL PLAT THEREOF.

COMMON AREAS ARE THE SOLE RESPONSIBILITY OF THE HOMEOWNERS ASSOCIATION.

THESE COMMON AREAS ARE HEREAFTER RESTRICTED FROM ADDITIONAL SUBDIVIDING OR FROM THE CONSTRUCTION AND/OR ERECTION OF ANY STRUCTURE WHETHER PERMANENT OR TEMPORARY. THESE AREAS ARE TO BE RESERVED AND SET ASIDE IN PERPETUITY AS "GREEN SPACE", THE ONLY PERMITTED USE OF SAID AREAS BEING THE INSTALLATION OF LANDSCAPING, INCLUDING THE PLANTING OF TREES, AND GENERAL MAINTENANCE ACTIVITIES SUCH AS MOWING AND DEBRIS REMOVAL. ALL TAXES, EXPENSES AND OTHER COST RELATED TO THESE

TO BE USED BY ANYONE FOR CONVEYANCE OF LANDS OR TITLE OF REAL ESTATE.

COMMUNITY PANEL NO. 29043C0060C, WHICH BEARS AN EFFECTIVE DATE OF DECEMBER 17, 2010.

SEE NOTE 10-

- SEE NOTE 13

ALL THAT PART OF THE NORTHEAST QUARTER OF THE NORTHWEST QUARTER OF SECTION 12 - TOWNSHIP 27 NORTH - RANGE 22 WEST OF THE FIFTH PRINCIPAL MERIDIAN, CHRISTIAN COUNT, STATE OF MISSOURI, DESCRIBED AS FOLLOWS: COMMENCING AT THE SOUTHWEST CORNER OF SAID NORTHEAST QUARTER OF THE NORTHWEST QUARTER AND MEASURE \$87°09'29"E ALONG THE SOUTH LINE THEREOF 46.72 FEET TO A POINT ON THE EAST RIGHT OF WAY LINE OF MAIN STREET FOR THE POINT OF BEGINNING; THENCE N01°44'33"E ALONG SAID EAST RIGHT OF WAY LINE 10.00 FEET TO A POINT ON THE SOUTH LINE OF THAT TRACT OF LAND DESCRIBED IN BOOK 2017 ON PAGE 9466; THENCE S87°14'38"E ALONG SAID SOUTH LINE 200.29 FEET TO THE SOUTHEAST CORNER THEREOF: THENCE N01°44'45"W ALONG THE EAST LINE THEREOF 172.00 FEET TO THE NORTHEAST CORNER THEREOF: THENCE N87°13'12"W ALONG THE NORTH LINE THEREOF 200.30 FEET TO A POINT ON THE EAST RIGHT OF WAY LINE OF MAIN STREET; (THE FOLLOWING FOLLOWS THE EAST R/W OF MAIN STREET) THENCE N01°44'41"E 487.33 FEET; THENCE N01°45'40"E 271.99 FEET; THENCE N07°27'19"E 140.43 FEET; THENCE N02°24'42"E 189.27 FEET; THENCE N47°20'09"E 35.05 FEET TO A POINT ON THE SOUTH RIGHT OF WAY LINE OF TRACKER ROAD; (THE FOLLOWING FOLLOWS THE SOUTH R/W OF TRACKER ROAD) THENCE S87°03'09"E 476.06 FEET; THENCE N02°49'33"E 16.69 FEET; THENCE S87°11'50"E 452.72 FEET TO A POINT MARKING THE NORTHEAST CORNER OF THE WEST 350 FEET OF THE EAST HALF OF THE NORTHEAST QUARTER OF THE NORTHWEST QUARTER: THENCE S01°36'27"W ALONG THE EAST LINE THEREOF 1311.90 FEET TO THE SOUTHEAST CORNER THEREOF, SAID POINT ON THE SOUTH LINE OF SAID NORTHEAST QUARTER OF THE NORTHWEST QUARTER; THENCE N87°09'29"W 973.52 FEET TO THE POINT OF BEGINNING, CONTAINING 28.17 ACRES.

DAT	E OF PRELIMINARY PLA	T SUBMITTAL:	JUNE 18, 2021									l	
TOTAL ACREAGE OF THE DEVELOPMENT: 28.17													
тот	AL NUMBER OF LOTS:	28											
CUR	RRENT ZONING:	R-1 (SINGLE FAN GC (GENERAL CO R-3 (HIGH-DENSI	IILY RESIDENTI OMMERCIAL) ITY MULTI-FAMII	AL DISTRICT) _Y)									
PRO	POSED ZONING:	R-1 (SINGLE FAN GC (GENERAL CO R-3 (HIGH-DENSI	IILY RESIDENTI OMMERCIAL) ITY MULTI-FAMII	AL DISTRICT) _Y)									
R-1	SMALLEST LOT:	LOT 13, 7,497 SQI	UARE FEET									l	
R-1 I	LARGEST LOT:	LOT 16, 15,077 SC	QUARE FEET									l	
												l	
NO	TES												
1.	MINIMUM LOT WIDTH	IS 60 FEET FOR R-1	1 (SINGLE FAMIL	Y RESIDENTIAL D	ISTRICT).							l	
2.	MINIMUM LOT WIDTH	IS NONE FOR GC (GENERAL COM	MERCIAL).									
3.	MINIMUM LOT SIZE IS	6,600 SQUARE FEE	ET.							Z		(0	
4.	R-1 (SINGLE FAMILY RESIDENTIAL DISTRICT) 25 FOOT BUILDING SETBACK LINE IN THE FRONT OF ALL LOTS. 20 FOOT BUILDING SETBACK LINE IN THE REAR OF ALL LOTS. 5 FOOT BUILDING SETBACK LINE ON THE SIDE OF ALL LOTS. 12 FOOT BUILDING SETBACK LINE ON THE SIDE OF ALL LOTS WITH LOCAL STREET FRONTAGE.												
5.	GC (GENERAL COMMERCIAL) 20 FOOT BUILDING SETBACK LINE IN THE FRONT OF ALL LOTS. 20 FOOT BUILDING SETBACK LINE IN THE REAR OF ALL LOTS. 10 FOOT BUILDING SETBACK LINE ON THE SIDE OF ALL LOTS. 15 FOOT BUILDING SETBACK LINE ON THE SIDE OF ALL LOTS WITH LOCAL STREET FRONTAGE.							RY PL/					
6.	R-3 (HIGH-DENSITY MULTI-FAMILY) 20 FOOT BUILDING SETBACK LINE IN THE FRONT OF ALL LOTS. 12 FOOT BUILDING SETBACK LINE ON THE SIDE OF ALL LOTS. 8 FOOT BUILDING SETBACK LINE ON THE SIDE OF ALL LOTS. 12 FOOT BUILDING SETBACK LINE ON THE SIDE OF ALL LOTS. 12 FOOT BUILDING SETBACK LINE ON THE SIDE OF ALL LOTS WITH LOCAL STREET FRONTAGE.												
7.	10 FOOT UTILITY EAS	DT UTILITY EASEMENT ON FRONT AND REAR OF ALL LOTS. $\begin{array}{c c} & & & \\ & & $											
8.	ROADS ARE TO BE DE												
9.	COMMON AREA (C1 8												
10.	PRELIMINARY SINKHO	DLE FLOOD OUTLIN	E FOR THE 100-	YEAR FLOOD. SEE	E FLOOD PLAIN NO ⁻	TE THIS SHEE	ET.			Ă		WO	
11.	PRELIMINARY SINKHO	DLE FLOOD OUTLIN	E FOR THE 500-	YEAR FLOOD. SEE	E FLOOD PLAIN NO ⁻	TE THIS SHEE	ET.			>			
12.	APPROXIMATE LOCAT	TION OF PROPOSEI	D FIRE HYDRAN	T (TYPICAL).									
13.	APPROXIMATE LOCAT	TION OF PROPOSEI	D DETENTION A	REAS (TYPICAL).								l	
14.	ROADS, UTILITIES ANI AND WILL BE DESIGN	S, UTILITIES AND OTHER ENGINEERING DESIGN ITEMS ARE SHOWN HEREON FOR PLANNING PURPOSES ONLY VILL BE DESIGNED SEPARATELY BY LICENSED ENGINEER.											
15.	NO DIRECT ACCESS T ADJOINING STREETS	ESS TO TRACKER ROAD OR MAIN STREET FROM ADJOINING LOTS. ALL LOT ACCESS MUST BE FROM EETS WITHIN SUBDIVISION INTERIOR.											
16.	THIS SUBDIVISION INCLUDES A REPLAT OF THAT PORTION OF NORTH SIDE INDUSTRIAL PARK INCLUDING NECESSARY VACATION OF ROADWAYS, EASEMENTS AND ALL COVENANTS / RESTRICTIONS ASSOCIATED THEREWITH.												
				N				Ĺ					
	E	BASIS OF BEA MISSOURI STATE NAD 83 CENTRAL	ARING PLANE ZONE				~	K					
	VE	ERTICAL DATUM = N	NAVD1988		0 100		MISS	OURI					
							UNE CALL Call or (Before Yo	CISIEM Click Du Dig! C DITE	PROJECT:		LOCATION:	CLIENT:	TITLE:



INDICATED GRAPHIC SCALES H. SCALE: 1" = 100'

^{or} 811 mo1call.com

C-001



IVISIO	N		E ASSOCIATES				
	JOB NUMBER:	72-007CE	Toth & Associates, Inc.				
	ISSUED DATE:	06/18/2021	Missouri State Certificate of Authority #2004004242				



:	8.00
:	8.00
:	6.0

BDIVISIC	ON		ASSOCIATES				
	JOB NUMBER:	72-010CE	Toth & Associates, Inc.				
	ISSUED DATE:	06/18/2021	Missouri State Certificate of Authority #2004004242				


KEY NOTES:

- (1) INSTALL TURN LANE IMPROVEMENTS.
- $\langle 2 \rangle$ PROPOSED INTERSECTION.





Major Thoroughfare Plan

Map 8-1

MO 174





As each of the projects in the Major Thoroughfare Plan (MTP) is implemented, coordination, agreement, and independent approval of the participating local jurisdiction is required. No part of this MTP is to be interpreted as to diminish the authority of local jurisdictions in the area of land use and transportation.

APPENDIX A COST ESTIMATE





TRACKER AND MAIN ROADWAY IMPROVEMENTS

Item	Description	Quantity	Units	Unit Price	Total Cost
1.00	EARTHWORK				
1.01	Clearing and Grubbing	1	LS	\$5,000	\$5,000
1.02	Sawcut and Removal of Existing Pavement	1	LS	\$5,000	\$5,000
1.03	Coldmilling Existing Pavement	350	SY	\$3	\$1,050
1.04	Site Grading - Cut (Unclassified)	750	CY	\$10	\$7,500
1.05	Site Grading - Fill	2,250	CY	\$10	\$22,500
1.06	Sediment and Erosion Control	1.0	LS	\$7,500	\$7,500
1.07	Seed, Fertilizer, and Mulch	1.0	AC	\$5,000	\$5,000
				SUBTOTAL	\$53,550

Item	Description	Quantity	Units	Unit Price	Total Cost
2.00	PAVING AND MISC.				
2.01	6 in. Heavy Duty Asphalt Pavement	13,000	SF	\$3.50	\$45,500
2.02	8 in. Aggregate Base for Heavy Duty Asphalt	13,000	SF	\$1.00	\$13,000
2.03	Asphalt Pavement for Overlay (1.75" Thick)	32,000	SF	\$1.25	\$40,000
2.03	Pavement Markings	1	LS	\$10,000	\$10,000
2.04	Signage	1	LS	\$5,000	\$5,000
2.05	Traffic Control	1	LS	\$10,000	\$10,000
				SUBTOTAL	\$123,500

Item	Description	Quantity	Units	Unit Price	Total Cost
3.00	UTILITIES				
3.01	Relocation of Existing Utilites	1	LS	\$15,000	\$15,000
					\$15,000

CONSTRUCTION TOTALS

Construction Total	\$192,050
Construction Contingency (20%)	\$38,500
Mobilization, Demobilization, and Bonding (5%)	\$11,528
Professional Services (23%)	\$55,700
TOTAL	\$297,778

NOTICE:

Opinion of Probable Construction Cost: The services, if any, of Engineer with respect to Opinion of Probable Construction Cost are to be made on the basis of Engineer's experience and qualifications and represent Engineer's best judgement as an experienced and qualified professional generally familiar with the construction industry. However, since Engineer has no control over the cost of labor, materials, equipment, or services furnished by others, or over contractor's methods of determining prices, or over competitive bidding or market conditions, Engineer cannot and does not guarantee that proposals, bids, or actual Construction Cost will not vary from Opinions of Probable Construction Cost prepared by Engineer.

APPENDIX B COLLECTED TURNING MOVEMENT COUNT DATA



OBSERVER: LINCOLN DUNNING/DAN SHANNON WEATHER: CLEAR 80°

DATE: <u>6.3.2021</u> COUNTY: <u>CHRISTIAN</u> DAY: THURSDAY CITY: NIXA STATE: MO

15 Minute Time	fror	<u>MAIN ST</u> m NORTH (S	SB)	fror	<u>MAIN ST</u> m SOUTH (1	NB)	<u>T</u> fro	RACKER R	<u>D</u> (B)	<u>T</u> fro	RACKER R m WEST (E	<u>D</u> B)
Period	Left	Thru	Right	Left	Thru	Right	Left	Thru	_, Right	Left	Thru	_, Right
4:00 PM - 4:15 PM	5	64	39	14	58	11	13	19	6	23 5 HEAVY VEHICLES	23	21
4:15 PM - 4:30 PM	4	66 1 HEAVY VEHICLE	42	7	65 1 HEAVY VEHICLE	9	13	21 1 HEAVY VEHICLE	9	14 1 HEAVY VEHICLE	28	24
<mark>4:30 PM -</mark> 4:45 PM	7	74 3 HEAVY VEHICLES	42	19	82 6 HEAVY VEHICLES	11 2 BICYCLES	13	27	6	28 2 HEAVY VEHICLES	25	30
<mark>(4:45 PM -</mark> 5:00 PM	8	91	36	12	54 1 HEAVY VEHICLE	17	18	30 1 BICYCLE	9	23	42	20

OBSERVER: LINCOLN DUNNING/DAN SHANNON WEATHER: CLEAR 80°

DATE: 6.3.2021 COUNTY: CHRISTIAN DAY: THURSDAY CITY: NIXA STATE: MO

15 Minute	from	MAIN ST	20)	fror	MAIN ST		<u>T</u>	RACKER R	<u>D</u>	Ţ	RACKER R	<u>D</u>
Period	l oft	Thru	SD) Right	l oft	Thru	ND) Right	l eft	Thru	D) Right	iro Left	III VV⊑ƏT (E Thru	D) Right
5:00 PM - 5:15 PM	6	83	35	22 3 HEAVY VEHICLES	64 1 HEAVY VEHICLE	19	14	40	9	29	30 1 HEAVY VEHICLE	23 1 BICYCLE
(<mark>5:15 PM -</mark> (5:30 PM)	6	91	52	14	66 1 HEAVY VEHICLE	11	8	26	8	21 2 HEAVY VEHICLES	24	26
5:30 PM - 5:45 PM	5	36	25	10	24	5	6	22	7	14 1 HEAVY VEHICLE	15	12
5:45 PM - 6:00 PM	5	23	27	3	11	2	4	11	6	7	8	10

OBSERVER: LINCOLN DUNNING/DAN SHANNON WEATHER: CLEAR 65°

DATE: 6.4.2021 COUNTY: CHRISTIAN CITY: NIXA DAY: FRIDAY STATE: MO

15 Minute		MAIN ST			MAIN ST		T	RACKER R	<u>D</u>	<u>T</u>	RACKER R	<u>D</u>
Time	fror	m NORTH (SB)	fror	n SOUTH (I	NB)	fro	m EAST (W	В)	fro	m WEST (E	B)
Period	Left	Thru	Right	Left	Thru	Right	Left	Thru	Right	Left	Thru	Right
<mark>(7:00 AM -</mark> (7:15 AM)	1	25	36 1 HEAVY VEHICLE	27 5 HEAVY VEHICLES	56 1 HEAVY VEHICLE	4	7	36	10	22 1 HEAVY VEHICLE	18	22 7 HEAVY VEHICLES
<mark>7:15 AM -</mark> 7:30 AM	1	32 1 HEAVY VEHICLE	26	29	89	10	5	27	5	28 3 HEAVY VEHICLES	20	14 1 HEAVY VEHICLE
<mark>(7:30 AM -</mark> 7:45 AM	0	33 3 HEAVY VEHICLES	14	18 1 HEAVY VEHICLE	90 3 HEAVY VEHICLES	4	7	33	12	41 2 HEAVY VEHICLES	12 1 HEAVY VEHICLE	3
<mark>(7:45 AM -</mark> 8:00 AM)	5	67	27 5 HEAVY VEHICLES	11	47 1 HEAVY VEHICLE	6	11	26	13	21	12	3

OBSERVER: LINCOLN DUNNING/DAN SHANNON WEATHER: CLEAR 65°

DATE: 6.4.2021 COUNTY: CHRISTIAN CITY: NIXA DAY: FRIDAY STATE: MO

15 Minute	r	MAIN ST		6	MAIN ST		Ţ	RACKER R	<u>D</u>	Ţ	RACKER R	<u>D</u>
I ime Poriod	tron Loft		SB) Diaht	fror	n SOUTH (ľ	NB) Diaht	fro Loft	m EAST (W	B) Diaht	tro Loft	m WEST (E	:B) Diabt
8:00 AM - 8:15 AM	2	34 1 HEAVY VEHICLE	27	12	54 2 HEAVY VEHICLES	11	5	17	22	28	16	11 1 HEAVY VEHICLE
8:15 AM - 8:30 AM	3	33 1 HEAVY VEHICLE	24 2 HEAVY VEHICLES	8 1 HEAVY VEHICLE	35 1 HEAVY VEHICLE	3	9	27 1 HEAVY VEHICLE	16	31 2 HEAVY VEHICLES	9	7 1 HEAVY VEHICLE
8:30 AM - 8:45 AM	2	34 1 HEAVY VEHICLE	18	13 1 HEAVY VEHICLE	54 1 HEAVY VEHICLE	8	7	16	11	18	8	7 2 HEAVY VEHICLES
8:45 AM - 9:00 AM	2	45	25	13	39 1 HEAVY VEHICLE	2	14	13	13	27 3 HEAVY VEHICLES	9	12

APPENDIX C CAPACITY CALCULATIONS



Intersection Info:	Tracker Road and Dona	ld St 2023	3 Build Scena	rio - AM Pe	ak Hour												
CONVERT MOVEMENT DE	MAND VOLUMES TO FLOW	/ RATES															
MOVEMENT		SBR	SBT	SBL		WBR	WBT	WBL	WBU		NBR	NBT	NBL	EBR	EBT	EBL	EBU
TRAFFIC VOLUME	veh/hr	10	0	5		3	200	0	0		0	0	0	0	97	2	0
GRADES	G integer %	1	1	1		-3	-3	-3	-3		1	1	1	3	3	3	3
GIUDES	G integer //	-	-	-		5	5	5	5		-	-	-	3	5	5	5
PHF		92%	92%	92%		92%	92%	92%	92%		92%	92%	92%	92%	92%	92%	92%
										_							
% HEAVY	integer %	0	0	0		0	8	0	0		0	0	0	0	0	0	0
MVMT FLOW	v _i veh/hr	11	0	5		3	217	0	0		0	0	0	0	105	2	0

CONFLICTING FLOW RATES,	V _{c,x}														
MOVEMENTS		12	11	10	-	-	4	4U	9	8	7	-	-	1	10
CONFLICTING FLOW ALL		110	328	275	-	-	105	105	53	329	218	-	-	220	220
CRITICAL HEADWAY, t _{c,x}															
Base Crit HW	t _{cbase}	6.90	-	-	-	-	4.10	6.40	6.90	-	-	-	-	4.10	6.40
Adj for HV	t _{c,HV}	2.00	2.00	2.00	-	-	2.00	2.00	2.00	2.00	2.00	-	-	2.00	2.00
Prop. Of HV	P _{HV}	0.00	0.00	0.00	-	-	0.00	0.00	0.00	0.00	0.00	-	-	0.00	0.00
Adj for Grade	t _{c,G}	0.10	0.20	0.20	-	-	-	-	0.10	0.20	0.20	-	-	-	-
Grades	G	1.00	1.00	1.00	-3.00	-3.00	-3.00	-3.00	1.00	1.00	1.00	3.00	3.00	3.00	3.00
Adj. for Int. Geom	t _{3,LT}	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Critical Headway		7.00	-	-	-	-	4.10	6.40	7.00	-	-	-	-	4.10	6.40

FOLLOW UP HEADWAY, t _{f,x}																
Base Follow up HW	t _{fbase}		3.30	4.00	3.50	-	-	2.20	2.50	3.30	4.00	3.50	-	-	2.20	2.50
Adj for HV	t _{f,HV}		1.00	1.00	1.00	-	-	1.00	1.00	1.00	1.00	1.00	-	-	1.00	1.00
Prop. Of HV	P_{HV}		0.00	0.00	0.00	-	-	0.00	0.00	0.00	0.00	0.00	-	-	0.00	0.00
Follow up Headway	t _{f,x}		3.30	4.00	3.50	-	-	2.20	2.50	3.30	4.00	3.50	-	-	2.20	2.50
POTENTIAL CAPACITY, c _{p,x}																
Potential Cap - 1 Maneuver			926	639	703	-	-	1,499	1,239	1,009	638	761	-	-	1,361	1,050
COMPUTE MOVEMENT CAPA	CITIES, C _{m,j}															
MOVEMENTS			12	11	10	-	-	4	4U	9	8	7	-	-	1	10
Compute Rank 1 Mov Cap's																
Compute Rank 2 Mov Cap's		Step 7a Step 7b Step 7c	926					1,499	1,239	1,009					1,361	1,038
Compute f_{1U}	0.98812															
Comput f _{4U}	1.00000	Sten 7d														
Use Eqn 20-42 as the LT and T not shared.	lanes are	Step / a														
Compute p _{0,j}	j = 1 or 4															
p _{0,1}	0.99853		р _{0,10}	1.00000												
P _{0,4}	1.00000		P _{0,4U}	1.00000												
Compute Rank 3 Mov Cap's		Step 8a														
f _k	0.99853		(capaci	ty adjustmen	t factor)											
Compute c																
Movement Cap - 2 Maneuver				638							637					
	STAGE 1			716							803					
	STAGE 2			803							715					
Rank 3 Two Stage Movement																
Compute adj factors a and y		Step 8b														
nm	2.00															
a	0.94910															
C _{II}	Red															
v _L (1 and 411)	2															
Select max v	2															
y	-			0.47868							2.18713					
Compute Total Cap, C _T (Cap 2 I	Maneuver)			670							668					

Compute Rank 4 Mov Cap's		Step 9a	
p _{0,8} p _{0,11}	1.00000 1.00000		
For Rank 4, Mvmt 7, p'' = From eqn 20-52, p' =		0.99853 0.99888	
For Rank 4, Mvmt 10, p'' = From eqn 20-52, p' =		0.99853 0.99888	
p _{0,9}	1.00000		
p _{0,12}	0.98812		
f _{p,l}		0.98701	0.99888
Compute c _{m,I}			
Movement Cap - 2 Maneuver		694	760
nm	2.00		
а	0.94910		
C _{II}	Red		
v _L (1 and 1U)	2		
v_L (4 and 4U)	0		
Select max v _L	2		
У		0.23326	1.01136
Compute Total Cap, C _T (Cap 2 I	Maneuver)	710	799

COMPUTE MOVEMENT CONT	ROL DELAY															
		Step 11a														
Compute CD for Rank 2 - Rank	4 Movement	ts														
MOVEMENTS			12	11	10	-	-	4	4U	9	8	7	-	-	1	1U
C _{m,x}	(veh/hr)	Т	926	670	710			1,499	1,239	1,009	668	799			1,361	1,038
d = Control delay (sec/veh)	h	0.25	8.9	10.4	10.1			7.4	7.9	8.6	10.4	9.5			7.6	8.5
v/c Ratio			0.01	0.00	0.01			0.00	0.00	0.00	0.00	0.00			0.00	0.00
HCM LOS			А	В	В			А	Α	А	В	А			А	Α

COMPUTE APPROACH CONTROL DELAY										
d _A (southbound)	9.26	s/veh			d _A (northbound)	#DIV/0!	s/veh			
HCM LOS	А				HCM LOS	#DIV/0!				
COMPUTE 95TH PERCENTILE QUEUE LENGTHS										
Т										
0.25										
Q ₉₅	0.03605	0.00000	0.02128	0.00000	0.00000	0.00000	0.00000	0.00000	0.00441	0.00000

Intersection Info:	Tracker Road and Dona	ld St 202	3 Build Scena	rio - PM Pe	ak Hour													
CONVERT MOVEMENT DEM	MAND VOLUMES TO FLOW	RATES																
MOVEMENT		SBR	SBT	SBL		WBR	WBT	WBL	WBU		NBR	NBT	NBL		EBR	EBT	EBL	EBU
TRAFFIC VOLUME	veh/hr	5	0	5		14	216	0	0	l i	0	0	0		0	214	13	0
GRADES	G integer %	1	1	1		-3	-3	-3	-3	I .	1	1	1	I .	3	3	3	3
PHF		92%	92%	92%		92%	92%	92%	92%	1	92%	92%	92%		92%	92%	92%	92%
% HEAVY	integer %	0	0	0		0	0	0	0	1	0	0	0	1	0	1	0	0
MVMT FLOW	v _i veh/hr	5	0	5		15	235	0	0		0	0	0		0	233	14	0

CONFLICTING FLOW RATES,	V _{c,x}														
MOVEMENTS		12	11	10	-	-	4	4U	9	8	7	-	-	1	10
CONFLICTING FLOW ALL		125	504	387	-	-	233	233	117	511	379	-	-	250	250
CRITICAL HEADWAY, t _{c,x}															
Base Crit HW	t _{cbase}	6.90	-	-	-	-	4.10	6.40	6.90	-	-	-	-	4.10	6.40
Adj for HV	t _{c,HV}	2.00	2.00	2.00	-	-	2.00	2.00	2.00	2.00	2.00	-	-	2.00	2.00
Prop. Of HV	P _{HV}	0.00	0.00	0.00	-	-	0.00	0.00	0.00	0.00	0.00	-	-	0.00	0.00
Adj for Grade	t _{c,G}	0.10	0.20	0.20	-	-	-	-	0.10	0.20	0.20	-	-	-	-
Grades	G	1.00	1.00	1.00	-3.00	-3.00	-3.00	-3.00	1.00	1.00	1.00	3.00	3.00	3.00	3.00
Adj. for Int. Geom	t _{3,LT}	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Critical Headway		7.00	-	-	-	-	4.10	6.40	7.00	-	-	-	-	4.10	6.40

FOLLOW UP HEADWAY, t _{f,x}																	
Base Follow up HW	t _{fbase}		3.30	4.00	3.50	-	-	2.20	2.50		3.30	4.00	3.50	-	-	2.20	2.50
Adj for HV	t _{f,HV}		1.00	1.00	1.00	-	-	1.00	1.00		1.00	1.00	1.00	-	-	1.00	1.00
Prop. Of HV	P _{HV}		0.00	0.00	0.00	-	-	0.00	0.00		0.00	0.00	0.00	-	-	0.00	0.00
Follow up Headway	t _{f,x}		3.30	4.00	3.50	-	-	2.20	2.50		3.30	4.00	3.50	-	-	2.20	2.50
POTENTIAL CAPACITY, c _{p,x}																	
Potential Cap - 1 Maneuver			905	529	601	-	-	1,346	1,031		917	525	608	-	-	1,327	1,006
COMPUTE MOVEMENT CAPAC	CITIES, C _{m,j}																
MOVEMENTS			12	11	10	-	-	4	4U		9	8	7	-	-	1	10
Compute Rank 1 Mov Cap's																	
Compute Rank 2 Mov Cap's		Step 7a Step 7b Step 7c	905					1,346	1,031		917					1,327	1,000
Compute f _{1U}	0.99448																
Comput I ₄₀	1.00000	Step 7d															
Use Eqn 20-42 as the LT and T not shared.	lanes are	·															
Compute p _{0,j}	j = 1 or 4																
P _{0,1}	0.98945		p _{0,1U}	1.00000													
P _{0,4}	1.00000		р _{0,4U}	1.00000													
Compute Rank 3 Mov Cap's Rank 3 One Stage Movement		Step 8a															
f _k	0.98945		(capaci	ity adjustmen	t factor)												
Compute c _{m k}																	
Movement Cap - 2 Maneuver				524								520					
	STAGE 1 STAGE 2			692 679								679 687					
Rank 3 Two Stage Movement Compute adj factors a and y		Step 8b															
nm	2.00																
a	0.94910																
C_{\parallel}	Red																
	14																
v _L (4 and 40) Select may v	0																
v	14			1 10//2								1 03083					
, Compute Total Cap, C _τ (Cap 2 M	Maneuver)			594								592					
,																	

Compute Rank 4 Mov Cap's		Step 9a	
p _{0,8} p _{0,11}	1.00000 1.00000		
For Rank 4, Mvmt 7, p'' = From eqn 20-52, p' =		0.98945 0.99195	
For Rank 4, Mvmt 10, p'' = From eqn 20-52, p' =		0.98945 0.99195	
p _{0,9}	1.00000		
p _{0,12}	0.99448		
f _{p,l}		0.98648	0.99195
Compute c _{m,i}			
Movement Cap - 2 Maneuver		592	603
nm	2.00		
C _{II}	Red		
v _L (1 and 1U)	14		
v _L (4 and 4U)	0		
Select max v _L	14		
У		0.59114	0.43006
Compute Total Cap, C _T (Cap 2 M	laneuver)	666	663

COMPUTE MOVEMENT CONT	ROL DELAY															
	5	itep 11a														
Compute CD for Rank 2 - Rank	4 Movements															
MOVEMENTS			12	11	10	-	-	4	4U	9	8	7	-	-	1	10
C _{m,x}	(veh/hr)	Т	905	594	666			1,346	1,031	917	592	663			1,327	1,000
d = Control delay (sec/veh)	h	0.25	9.0	11.1	10.4			7.7	8.5	8.9	11.1	10.4			7.7	8.6
v/c Ratio			0.01	0.00	0.01			0.00	0.00	0.00	0.00	0.00			0.01	0.00
HCM LOS			А	В	В			А	А	А	В	В			Α	Α

COMPUTE APPROACH CONTROL DELAY										
d _A (southbound)	9.69	s/veh			d _A (northbound)	#DIV/0!	s/veh			
HCM LOS	А				HCM LOS	#DIV/0!				
COMPUTE 95TH PERCENTILE QUEUE LENGTHS										
Т										
0.25										
Q ₉₅	0.01666	0.00000	0.02270	0.00000	0.00000	0.00000	0.00000	0.00000	0.03197	0.00000

Intersection Info:	Tracker Road and Dona	ld St 2043	3 Build Scena	rio - AM Pe	ak Hour											
CONVERT MOVEMENT DE	EMAND VOLUMES TO FLOW	V RATES														
MOVEMENT		SBR	SBT	SBL		WBR	WBT	WBL	WBU	NBR	NBT	NBL	EBR	EBT	EBL	EBU
TRAFFIC VOLUME	veh/hr	10	0	5		3	297	0	0	0	0	0	0	144	2	0
GRADES	G integer %	1	1	1		-3	-3	-3	-3	1	1	1	3	4	3	3
PHF		92%	92%	92%		92%	92%	92%	92%	92%	92%	92%	92%	92%	92%	92%
% HEAVY	integer %	0	0	0		0	8	0	0	0	0	0	0	0	0	0
MVMT FLOW	v _i veh/hr	11	0	5		3	323	0	0	0	0	0	0	157	2	0

CONFLICTING FLOW RATES,	V _{c,x}														
MOVEMENTS		12	11	10	-	-	4	4U	9	8	7	-	-	1	10
CONFLICTING FLOW ALL		163	486	407	-	-	157	157	79	487	323	-	-	326	326
CRITICAL HEADWAY, t _{c,x}															
Base Crit HW	t _{cbase}	6.90	-	-	-	-	4.10	6.40	6.90	-	-	-	-	4.10	6.40
Adj for HV	t _{c,HV}	2.00	2.00	2.00	-	-	2.00	2.00	2.00	2.00	2.00	-	-	2.00	2.00
Prop. Of HV	P _{HV}	0.00	0.00	0.00	-	-	0.00	0.00	0.00	0.00	0.00	-	-	0.00	0.00
Adj for Grade	t _{c,G}	0.10	0.20	0.20	-	-	-	-	0.10	0.20	0.20	-	-	-	-
Grades	G	1.00	1.00	1.00	-3.00	-3.00	-3.00	-3.00	1.00	1.00	1.00	3.00	4.00	3.00	3.00
Adj. for Int. Geom	t _{3,LT}	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Critical Headway		7.00	-	-	-	-	4.10	6.40	7.00	-	-	-	-	4.10	6.40

FOLLOW UP HEADWAY, t _{f,x}																	
Base Follow up HW	t _{fbase}		3.30	4.00	3.50	-	-	2.20	2.50	3.30	4.00	3.50	1	-	-	2.20	2.50
Adj for HV	t _{f,HV}		1.00	1.00	1.00	-	-	1.00	1.00	1.00	1.00	1.00	I	-	-	1.00	1.00
Prop. Of HV	P _{HV}		0.00	0.00	0.00	-	-	0.00	0.00	0.00	0.00	0.00		-	-	0.00	0.00
Follow up Headway	t _{f,x}		3.30	4.00	3.50	-	-	2.20	2.50	3.30	4.00	3.50		-	-	2.20	2.50
POTENTIAL CAPACITY, c _{p,x}																	
Potential Cap - 1 Maneuver			855	540	584	-	-	1,435	1,150	971	539	657		-	-	1,245	901
COMPUTE MOVEMENT CAPA	CITIES, C _{m,j}																
MOVEMENTS			12	11	10	-	-	4	4U	9	8	7		-	-	1	10
Compute Rank 1 Mov Cap's																	
Compute Rank 2 Mov Cap's		Step 7a Step 7b Step 7c	855					1,435	1,150	971						1,245	890
Compute f _{1U}	0.98714																
Comput f _{4U}	1.00000	Sten 7d															
Use Eqn 20-42 as the LT and T not shared.	lanes are																
Compute p _{0,j}	j = 1 or 4																
P _{0,1}	0.99839		p _{0,1U}	1.00000													
p _{0,4}	1.00000		р _{0,40}	1.00000													
Compute Rank 3 Mov Cap's Rank 3 One Stage Movement		Step 8a															
f _k	0.99839		(capaci	ty adjustmen	t factor)												
Compute c _{m,k} Movement Cap - 2 Maneuver	STAGE 1			539 640							538 761						
	STAGE 2			761							639						
Rank 3 Two Stage Movement Compute adj factors a and y		Step 8b															
nm a	2.00 0.94910																
C _{II}	Red																
v _L (1 and 1U)	2																
v_L (4 and 4U)	0																
Select max v _L	2																
y Compute Total Cap. C. (Cap.2	Manouver			0.46129							2.24377						
compute rotal Cap, CT (Cap 2	maneuver)			292							333						

Compute Rank 4 Mov Cap's		Step 9a	
p _{0,8} p _{0,11}	1.00000 1.00000		
For Rank 4, Mvmt 7, p'' = From eqn 20-52, p' =		0.99839 0.99878	
For Rank 4, Mvmt 10, p'' = From eqn 20-52, p' =		0.99839 0.99878	
p _{0,9}	1.00000		
p _{0,12}	0.98714		
f _{p,l}		0.98593	0.99878
Compute c _{m,I}			
Movement Cap - 2 Maneuver		576	657
nm	2.00		
a	0.94910		
C_{\parallel}	Red		
v _L (1 and 10)	2		
VL (4 driu 40)	0		
v	2	0.21591	1 01575
Compute Total Cap, C _T (Cap 2 I	Maneuver)	611	727

COMPUTE MOVEMENT CONT	ROL DELAY															
		Step 11a														
Compute CD for Rank 2 - Rank	4 Moveme	nts														
MOVEMENTS			12	11	10	-	-	4	40	9	8	7	-	-	1	10
C _{m,x}	(veh/hr)	т	855	595	611			1,435	1,150	971	593	727			1,245	890
d = Control delay (sec/veh)	h	0.25	9.2	11.0	10.9			7.5	8.1	8.7	11.1	9.9			7.9	9.0
v/c Ratio			0.01	0.00	0.01			0.00	0.00	0.00	0.00	0.00			0.00	0.00
HCM LOS			А	В	В			А	А	А	В	А			А	Α

COMPUTE APPROACH CONTROL DELAY										
d _A (southbound)	9.74	s/veh			d _A (northbound)	#DIV/0!	s/veh			
HCM LOS	А				HCM LOS	#DIV/0!				
COMPUTE 95TH PERCENTILE QUEUE LENGTHS										
Т										
0.25										
Q ₉₅	0.03907	0.00000	0.02474	0.00000	0.00000	0.00000	0.00000	0.00000	0.00483	0.00000

Intersection Info:	Tracker Road and Dona	ld St 204	3 Build Scena	irio - PM Pe	ak Hour												
CONVERT MOVEMENT DE	MAND VOLUMES TO FLOW	RATES															
MOVEMENT		SBR	SBT	SBL		WBR	WBT	WBL	WBU		NBR	NBT	NBL	EBR	EBT	EBL	EBU
TRAFFIC VOLUME	veh/hr	5	0	5		14	321	0	0		0	0	0	0	319	13	0
GRADES	G integer %	1	1	1		-3	-3	-3	-3	I	1	1	1	3	3	3	3
PHF		92%	92%	92%		92%	92%	92%	92%		92%	92%	92%	92%	92%	92%	92%
% HEAVY	integer %	0	0	0		0	0	0	0	1	0	0	0	0	1	0	0
MVMT FLOW	v _i veh/hr	5	0	5		15	349	0	0		0	0	0	0	347	14	0

CONFLICTING FLOW RATES,	V _{c,x}														
MOVEMENTS		12	11	10	-	-	4	4U	9	8	7	-	-	1	10
CONFLICTING FLOW ALL		182	732	558	-	-	347	347	174	739	550	-	-	364	364
CRITICAL HEADWAY, t _{c,x}															
Base Crit HW	t _{cbase}	6.90	-	-	-	-	4.10	6.40	6.90	-	-	-	-	4.10	6.40
Adj for HV	t _{c,HV}	2.00	2.00	2.00	-	-	2.00	2.00	2.00	2.00	2.00	-	-	2.00	2.00
Prop. Of HV	P _{HV}	0.00	0.00	0.00	-	-	0.00	0.00	0.00	0.00	0.00	-	-	0.00	0.00
Adj for Grade	t _{c,G}	0.10	0.20	0.20	-	-	-	-	0.10	0.20	0.20	-	-	-	-
Grades	G	1.00	1.00	1.00	-3.00	-3.00	-3.00	-3.00	1.00	1.00	1.00	3.00	3.00	3.00	3.00
Adj. for Int. Geom	t _{3,LT}	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Critical Headway		7.00	-	-	-	-	4.10	6.40	7.00	-	-	-	-	4.10	6.40

FOLLOW UP HEADWAY, t _{f,x}																	
Base Follow up HW	t _{fbase}		3.30	4.00	3.50	-	-	2.20	2.50	l	3.30	4.00	3.50	-	-	2.20	2.50
Adj for HV	t _{f,HV}		1.00	1.00	1.00	-	-	1.00	1.00		1.00	1.00	1.00	-	-	1.00	1.00
Prop. Of HV	P_{HV}		0.00	0.00	0.00	-	-	0.00	0.00		0.00	0.00	0.00	-	-	0.00	0.00
Follow up Headway	t _{f,x}		3.30	4.00	3.50	-	-	2.20	2.50		3.30	4.00	3.50	-	-	2.20	2.50
POTENTIAL CAPACITY, c _{p,x}																	
Potential Cap - 1 Maneuver			831	413	472	-	-	1,223	874		842	409	477	-	-	1,206	853
COMPUTE MOVEMENT CAPAC	CITIES, C _{m,j}																
MOVEMENTS			12	11	10	-	-	4	4U		9	8	7	-	-	1	10
Compute Rank 1 Mov Cap's																	
Compute Rank 2 Mov Cap's		Step 7a Step 7b Step 7c	831					1,223	874		842					1,206	848
Compute f _{1U}	0.99399																
	1.00000	Step 7d															
Use Eqn 20-42 as the LT and T I not shared.	lanes are																
Compute p _{0,j}	j = 1 or 4		n	1 00000													
P _{0,1}	1 00000		P _{0,1U}	1.00000													
P0,4	1.00000		P0,40	1.00000													
Compute Rank 3 Mov Cap's		Step 8a															
f _v	0.98839		(capaci	tv adiustmen	t factor)												
ĸ			(-,,	,												
Compute c _{m,k}																	
Movement Cap - 2 Maneuver	STACE 1			408								405					
	STAGE 1 STAGE 2			601								608					
Deal 2 Tax Chara Manager																	
Compute adj factors a and y		Step 8b															
nm	2.00																
a	0.94910																
C_{\parallel}	Red																
v _L (1 and 10)	14																
Select max v.	1/																
V	14			1.14534								1.03659					
, Compute Total Cap, C _T (Cap 2 N	/laneuver)			508								506					

Compute Rank 4 Mov Cap's		Step 9a	
p _{0,8} p _{0,11}	1.00000 1.00000		
For Rank 4, Mvmt 7, p'' = From eqn 20-52, p' =		0.98839 0.99114	
For Rank 4, Mvmt 10, p'' = From eqn 20-52, p' =		0.98839 0.99114	
p _{0,9}	1.00000		
p _{0,12}	0.99399		
f _{p,l}		0.98518	0.99114
Compute c _{m,I}			
Movement Cap - 2 Maneuver		465	473
nm	2.00		
a	0.94910		
C _{II}	Red		
v _L (1 and 1U)	14		
v_{L} (4 and 4U)	0		
Select max v _L	14		
У		0.53040	0.42115
Compute Total Cap, C _T (Cap 2 M	aneuver)	564	561

COMPUTE MOVEMENT CONT	ROL DELAY														
	S	itep 11a													
Compute CD for Rank 2 - Rank	4 Movements														
MOVEMENTS			12	11	10	-	-	4	4U	9	8	7	-	- 1	10
C _{m,x}	(veh/hr)	Т	831	508	564			1,223	874	842	506	561		1,206	848
d = Control delay (sec/veh)	h	0.25	9.3	12.1	11.4			7.9	9.1	9.3	12.1	11.4		8.0	9.2
v/c Ratio			0.01	0.00	0.01			0.00	0.00	0.00	0.00	0.00		0.01	0.00
HCM LOS			А	В	В			А	Α	А	В	В		А	А

COMPUTE APPROACH CONTROL DELAY										
d _A (southbound)	10.36	s/veh			d _A (northbound)	#DIV/0!	s/veh			
HCM LOS	В				HCM LOS	#DIV/0!				
COMPUTE 95TH PERCENTILE QUEUE LENGTHS										
Т										
0.25										
Q ₉₅	0.01815	0.00000	0.02684	0.00000	0.00000	0.00000	0.00000	0.00000	0.03523	0.00000

Intersection Info:	Tracker Road and Maxi	ine Ave 20	023 Build Sce	nario - AM P	eak Hour											
CONVERT MOVEMENT	DEMAND VOLUMES TO FLOW	W RATES														
MOVEMENT		SBR	SBT	SBL		WBR	WBT	WBL	WBU	NBR	NBT	NBL	EBR	EBT	EBL	EBU
TRAFFIC VOLUME	veh/hr	0	0	0		0	200	16	0	3	0	8	8	97	0	0
GRADES	G integer %	1	1	1		-4	-4	-4	-4	1	1	1	4	4	4	4
PHF		92%	92%	92%		92%	92%	92%	92%	92%	92%	92%	92%	92%	92%	92%
% HEAVY	integer %	0	0	0		0	8	0	0	0	0	0	0	0	0	0
MVMT FLOW	v _i veh/hr	0	0	0		0	217	17	0	3	0	9	9	105	0	0

CONFLICTING FLOW RATES,	V _{c,x}														
MOVEMENTS		12	11	10	-	-	4	4U	9	8	7	-	-	1	1U
CONFLICTING FLOW ALL		109	365	304	-	-	114	114	57	361	252	-	-	217	217
CRITICAL HEADWAY, t _{c,x}															
Base Crit HW	t _{cbase}	6.90	-	-	-	-	4.10	6.40	6.90	-	-	-	-	4.10	6.40
Adj for HV	t _{c,HV}	2.00	2.00	2.00	-	-	2.00	2.00	2.00	2.00	2.00	-	-	2.00	2.00
Prop. Of HV	P _{HV}	0.00	0.00	0.00	-	-	0.00	0.00	0.00	0.00	0.00	-	-	0.00	0.00
Adj for Grade	t _{c,G}	0.10	0.20	0.20	-	-	-	-	0.10	0.20	0.20	-	-	-	-
Grades	G	1.00	1.00	1.00	-4.00	-4.00	-4.00	-4.00	1.00	1.00	1.00	4.00	4.00	4.00	4.00
Adj. for Int. Geom	t _{3,LT}	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Critical Headway		7.00	-	-	-	-	4.10	6.40	7.00	-	-	-	-	4.10	6.40

FOLLOW UP HEADWAY, t _{f,x}																
Base Follow up HW	t _{fbase}		3.30	4.00	3.50	-	-	2.20	2.50	3.30	4.00	3.50	-	-	2.20	2.50
Adj for HV	t _{f,HV}		1.00	1.00	1.00	-	-	1.00	1.00	1.00	1.00	1.00	-	-	1.00	1.00
Prop. Of HV	P_{HV}		0.00	0.00	0.00	-	-	0.00	0.00	0.00	0.00	0.00	-	-	0.00	0.00
Follow up Headway	t _{f,x}		3.30	4.00	3.50	-	-	2.20	2.50	3.30	4.00	3.50	-	-	2.20	2.50
POTENTIAL CAPACITY, c _{p,x}																
Potential Cap - 1 Maneuver			928	614	675	-	-	1,488	1,223	1,002	617	726	-	-	1,365	1,055
COMPUTE MOVEMENT CAPA	CITIES, C _{m,j}															
MOVEMENTS			12	11	10	-	-	4	4U	9	8	7	-	-	1	10
Compute Rank 1 Mov Cap's																
Compute Rank 2 Mov Cap's		Step 7a Step 7b Step 7c	928					1,488	1,219	1,002					1,365	1,055
Compute f _{1U}	1.00000															
Comput f _{4U}	0.99701	Step 7d														
Use Eqn 20-42 as the LT and T not shared.	lanes are	·														
Compute p _{0,j}	j = 1 or 4			4 00000												
P _{0,1}	1.00000		Р _{0,10}	1.00000												
P0,4	0.56657		P0,40	1.00000												
Compute Rank 3 Mov Cap's		Step 8a														
f _k	0.98857		(capaci	ty adjustmen	t factor)											
Compute c _{m,k}				607							610					
	STAGE 1			685							795					
	STAGE 2			791							685					
Rank 3 Two Stage Movement																
Compute adj factors a and y		Step 8b														
nm	2.00															
а	0.94910															
C _{II}	Red															
v _L (1 and 1U)	0															
v _L (4 and 4U)	17															
select max v _L	17			0 46794							3 17702					
, Compute Total Cap, C _τ (Cap 2 I	Maneuver)			641							630					
	,															

Compute Rank 4 Mov Cap's		Step 9a	
p _{0,8} p _{0,11}	1.00000 1.00000		
For Rank 4, Mvmt 7, p'' = From eqn 20-52, p' =		0.98857 0.99128	
For Rank 4, Mvmt 10, p'' = From eqn 20-52, p' =		0.98857 0.99128	
p _{0,9}	0.99701		
p _{0,12}	1.00000		
f _{p,l}		0.99128	0.98832
Compute c _{m,I}			
Movement Cap - 2 Maneuver		669	717
nm	2.00		
a	0.94910		
CII	Red		
v _L (1 and 1U)	0		
v_L (4 and 4U)	17		
Select max v _L	17		
У		0.19423	1.55529
Compute Total Cap, C _T (Cap 2 I	Maneuver)	682	757

COMPUTE MOVEMENT CONT	ROL DELAY															
	9	Step 11a														
Compute CD for Rank 2 - Rank	4 Movement	ts														
MOVEMENTS			12	11	10	-	-	4	4U	9	8	7	-	-	1	1U
C _{m,x}	(veh/hr)	Т	928	641	682			1,488	1,219	1,002	630	757			1,365	1,055
d = Control delay (sec/veh)	h	0.25	8.9	10.6	10.3			7.4	8.0	8.6	10.7	9.8			7.6	8.4
v/c Ratio			0.00	0.00	0.00			0.01	0.00	0.00	0.00	0.01			0.00	0.00
HCM LOS			А	В	В			А	Α	А	В	А			А	Α

COMPUTE APPROACH CONTROL DELAY										
d _A (southbound)	#DIV/0!	s/veh			d _A (northbound)	9.47	s/veh			
HCM LOS	#DIV/0!				HCM LOS	А				
COMPUTE 95TH PERCENTILE QUEUE LENGTHS										
Т										
0.25										
Q ₉₅	0.00000	0.00000	0.00000	0.03467	0.00000	0.00901	0.00000	0.03608	0.00000	0.00000

Intersection Info:	Tracker Road and Maxi	ne Ave 20	023 Build Sce	nario - PM I	Peak Hour													
CONVERT MOVEMENT DE	EMAND VOLUMES TO FLOW	RATES																
MOVEMENT		SBR	SBT	SBL		WBR	WBT	WBL	WBU		NBR	NBT	NBL		EBR	EBT	EBL	EBU
TRAFFIC VOLUME	veh/hr	0	0	0		0	216	7	0	I	10	0	11		7	214	0	0
GRADES	G integer %	1	1	1		-4	-4	-4	-4	1	1	1	1	1	4	4	4	4
PHF	1	92%	92%	92%		92%	92%	92%	92%		92%	92%	92%		92%	92%	92%	92%
% HEAVY	integer %	0	0	0		0	0	0	0		0	0	0		0	1	0	0
MVMT FLOW	v _i veh/hr	0	0	0		0	235	8	0		11	0	12		8	233	0	0

CONFLICTING FLOW RATES,	V _{c,x}														
MOVEMENTS		12	11	10	-	-	4	4U	9	8	7	-	-	1	10
CONFLICTING FLOW ALL		118	492	368	-	-	241	241	121	488	371	-	-	235	235
CRITICAL HEADWAY, t _{c,x}															
Base Crit HW	t _{cbase}	6.90	-	-	-	-	4.10	6.40	6.90	-	-	-	-	4.10	6.40
Adj for HV	t _{c,HV}	2.00	2.00	2.00	-	-	2.00	2.00	2.00	2.00	2.00	-	-	2.00	2.00
Prop. Of HV	P _{HV}	0.00	0.00	0.00	-	-	0.00	0.00	0.00	0.00	0.00	-	-	0.00	0.00
Adj for Grade	t _{c,G}	0.10	0.20	0.20	-	-	-	-	0.10	0.20	0.20	-	-	-	-
Grades	G	1.00	1.00	1.00	-4.00	-4.00	-4.00	-4.00	1.00	1.00	1.00	4.00	4.00	4.00	4.00
Adj. for Int. Geom	t _{3,LT}	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Critical Headway		7.00	-	-	-	-	4.10	6.40	7.00	-	-	-	-	4.10	6.40

FOLLOW UP HEADWAY, t _{f,x}																
Base Follow up HW	t _{fbase}		3.30	4.00	3.50	-	-	2.20	2.50	3.30	4.00	3.50	-	-	2.20	2.50
Adj for HV	t _{f,HV}		1.00	1.00	1.00	-	-	1.00	1.00	1.00	1.00	1.00	-	-	1.00	1.00
Prop. Of HV	P _{HV}		0.00	0.00	0.00	-	-	0.00	0.00	0.00	0.00	0.00	-	-	0.00	0.00
Follow up Headway	t _{f,x}		3.30	4.00	3.50	-	-	2.20	2.50	3.30	4.00	3.50	-	-	2.20	2.50
POTENTIAL CAPACITY, c _{p,x}																
Potential Cap - 1 Maneuver			916	536	617	-	-	1,337	1,019	912	538	615	-	-	1,344	1,028
COMPUTE MOVEMENT CAPAC	CITIES, C _{m,j}															
MOVEMENTS			12	11	10	-	-	4	4U	9	8	7	-	-	1	10
Compute Rank 1 Mov Cap's																
Compute Rank 2 Mov Cap's		Step 7a Step 7b Step 7c	916					1,337	1,007	912					1,344	1,028
Compute f _{1U}	1.00000															
Comput r ₄₀	0.98793	Step 7d														
Use Eqn 20-42 as the LT and T l not shared.	lanes are															
Compute p _{0,j}	j = 1 or 4															
P _{0,1}	1.00000		p _{0,1U}	1.00000												
P _{0,4}	0.99402		р _{0,4U}	1.00000												
Compute Rank 3 Mov Cap's Rank 3 One Stage Movement		Step 8a														
f _k	0.99402		(capaci	ty adjustmen	t factor)											
Compute c _{m,k} Movement Cap - 2 Maneuver				533							535					
	STAGE 1 STAGE 2			689 696							699 689					
Rank 3 Two Stage Movement Compute adj factors a and y		Step 8b														
nm a	2.00 0.94910															
CII	Red															
v _L (1 and 1U)	0															
v _L (4 and 4U)	8															
Select max v _L	8															
У				1.00455							1.12506					
Compute Total Cap, C _T (Cap 2 N	/laneuver)			604							605					

Compute Rank 4 Mov Cap's		Step 9a		
p _{0,8}	1.00000			
P _{0,11}	1.00000			
For Rank 4, Mvmt 7, p'' = From eqn 20-52, p' =		0.99402 0.99544		
For Rank 4, Mvmt 10, p'' = From eqn 20-52, p' =		0.99402 0.99544		
p _{0,9}	0.98793			
p _{0,12}	1.00000			
f _{p,l}		0.99544	0.98343	
Compute c _{m,i}				
Movement Cap - 2 Maneuver		614	604	
nm	2.00			
a	0.94910			
C _{II}	Red			
v _L (1 and 1U)	0			
v_L (4 and 4U)	8			
Select max v _L	8			
у		0.43621	0.54243	
Compute Total Cap, C _T (Cap 2 M	aneuver)	674	673	

COMPUTE MOVEMENT CONT	ROL DELAY															
	S	tep 11a														
Compute CD for Rank 2 - Rank	4 Movements															
MOVEMENTS			12	11	10	-	-	4	40	9	8	7	-	-	1	10
C _{m,x}	(veh/hr)	Т	916	604	674			1,337	1,007	912	605	673			1,344	1,028
d = Control delay (sec/veh)	h	0.25	8.9	11.0	10.3			7.7	8.6	9.0	10.9	10.4			7.7	8.5
v/c Ratio			0.00	0.00	0.00			0.01	0.00	0.01	0.00	0.02			0.00	0.00
HCM LOS			А	В	В			А	А	А	В	В			А	А

COMPUTE APPROACH CONTROL DELAY										
d _A (southbound)	#DIV/0!	s/veh			d _A (northbound)	9.69	s/veh			
HCM LOS	#DIV/0!				HCM LOS	А				
COMPUTE 95TH PERCENTILE QUEUE LENGTHS										
Т										
0.25										
Q ₉₅	0.00000	0.00000	0.00000	0.01805	0.00000	0.03663	0.00000	0.05446	0.00000	0.00000

Intersection Info:	Tracker Road and Maxi	ine Ave 20	043 Build Sce	nario - AM P	eak Hour											
CONVERT MOVEMENT	DEMAND VOLUMES TO FLOW	N RATES														
MOVEMENT		SBR	SBT	SBL		WBR	WBT	WBL	WBU	NBR	NBT	NBL	EBR	EBT	EBL	EBU
TRAFFIC VOLUME	veh/hr	0	0	0		0	297	16	0	3	0	8	8	144	0	0
GRADES	G integer %	1	1	1		-4	-4	-4	-4	1	1	1	4	4	4	4
PHF		92%	92%	92%		92%	92%	92%	92%	92%	92%	92%	92%	92%	92%	92%
% HEAVY	integer %	0	0	0		0	8	0	0	0	0	0	0	0	0	0
MVMT FLOW	v _i veh/hr	0	0	0		0	323	17	0	3	0	9	9	157	0	0

CONFLICTING FLOW RATES,	V _{c,x}														
MOVEMENTS		12	11	10	-	-	4	4U	9	8	7	-	-	1	1U
CONFLICTING FLOW ALL		162	523	436	-	-	166	166	83	519	357	-	-	323	323
CRITICAL HEADWAY, t _{c,x}															
Base Crit HW	t _{cbase}	6.90	-	-	-	-	4.10	6.40	6.90	-	-	-	-	4.10	6.40
Adj for HV	t _{c,HV}	2.00	2.00	2.00	-	-	2.00	2.00	2.00	2.00	2.00	-	-	2.00	2.00
Prop. Of HV	P _{HV}	0.00	0.00	0.00	-	-	0.00	0.00	0.00	0.00	0.00	-	-	0.00	0.00
Adj for Grade	t _{c,G}	0.10	0.20	0.20	-	-	-	-	0.10	0.20	0.20	-	-	-	-
Grades	G	1.00	1.00	1.00	-4.00	-4.00	-4.00	-4.00	1.00	1.00	1.00	4.00	4.00	4.00	4.00
Adj. for Int. Geom	t _{3,LT}	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Critical Headway		7.00	-	-	-	-	4.10	6.40	7.00	-	-	-	-	4.10	6.40

FOLLOW UP HEADWAY, t _{f,x}																
Base Follow up HW	t _{fbase}		3.30	4.00	3.50	-	-	2.20	2.50	3.30	4.00	3.50	-	-	2.20	2.50
Adj for HV	t _{f,HV}		1.00	1.00	1.00	-	-	1.00	1.00	1.00	1.00	1.00	-	-	1.00	1.00
Prop. Of HV	P_{HV}		0.00	0.00	0.00	-	-	0.00	0.00	0.00	0.00	0.00	-	-	0.00	0.00
Follow up Headway	t _{f,x}		3.30	4.00	3.50	-	-	2.20	2.50	3.30	4.00	3.50	-	-	2.20	2.50
POTENTIAL CAPACITY, c _{p,x}																
Potential Cap - 1 Maneuver			857	518	561	-	-	1,424	1,135	964	521	626	-	-	1,248	905
COMPUTE MOVEMENT CAPAC	CITIES, C _{m,j}															
MOVEMENTS			12	11	10	-	-	4	4U	9	8	7	-	-	1	10
Compute Rank 1 Mov Cap's																
Compute Rank 2 Mov Cap's		Step 7a Step 7b Step 7c	857					1,424	1,131	964					1,248	905
Compute f _{1U}	1.00000															
Comput f _{4U}	0.99689	Step 7d														
Use Eqn 20-42 as the LT and T not shared.	lanes are	·														
Compute p _{0,j}	j = 1 or 4			4 00000												
ρ _{0,1}	0.98806		P _{0,1U}	1.00000												
P0,4	0.98800		P0,4U	1.00000												
Compute Rank 3 Mov Cap's		Step 8a														
f _k	0.98806		(capaci	tv adiustmen	t factor)											
ĸ			(.,,	,											
Compute c _{m,k}																
Movement Cap - 2 Maneuver	STAGE 1			512 612							515 752					
	STAGE 2			749							612					
Rank 3 Two Stage Movement																
Compute adj factors a and y		Step 8b														
nm	2.00															
a	0.94910															
C _{II} v. (1 and 111)	Red															
v _L (1 and 10)	17															
Select max v	17															
y	1/			0.45503							2.95526					
Compute Total Cap, C _T (Cap 2 I	Maneuver)			569							559					

Compute Rank 4 Mov Cap's		Step 9a	
p _{0,8} p _{0,11}	1.00000 1.00000		
For Rank 4, Mvmt 7, p'' = From eqn 20-52, p' =		0.98806 0.99090	
For Rank 4, Mvmt 10, p'' = From eqn 20-52, p' =		0.98806 0.99090	
p _{0,9}	0.99689		
p _{0,12}	1.00000		
f _{p,l}		0.99090	0.98781
Compute c _{m,I}			
Movement Cap - 2 Maneuver		556	619
nm	2.00		
a	0.94910		
C _{II}	Red		
v _L (1 and 1U)	0		
v_L (4 and 4U)	17		
Select max v _L	17		
У		0.18976	1.39044
Compute Total Cap, C _T (Cap 2 I	Maneuver)	587	689

COMPUTE MOVEMENT CONT	ROL DELAY															
		Step 11a														
Compute CD for Rank 2 - Rank	4 Movemer	nts														
MOVEMENTS C _{m,x}	(veh/hr)	т	12 857	11 569	10 587	-	-	4 1,424	4U 1,131	9 964	8 559	7 689	-	-	1 1,248	1U 905
d = Control delay (sec/veh)	h	0.25	9.2	11.3	11.1			7.5	8.2	8.7	11.4	10.2			7.9	9.0
v/c Ratio			0.00	0.00	0.00			0.01	0.00	0.00	0.00	0.01			0.00	0.00
HCM LOS			А	В	В			Α	Α	А	В	В			Α	Α

COMPUTE APPROACH CONTROL DELAY										
d _A (southbound)	#DIV/0!	s/veh			d _A (northbound)	9.85	s/veh			
HCM LOS	#DIV/0!				HCM LOS	А				
COMPUTE 95TH PERCENTILE QUEUE LENGTHS										
Т										
0.25										
Q ₉₅	0.00000	0.00000	0.00000	0.03623	0.00000	0.00936	0.00000	0.03968	0.00000	0.00000

Intersection Info:	Tracker Road and Maxi																
CONVERT MOVEMENT DE	EMAND VOLUMES TO FLOW	RATES															
MOVEMENT		SBR	SBT	SBL	WBR	WBT	WBL	WBU		NBR	NBT	NBL		EBR	EBT	EBL	EBU
TRAFFIC VOLUME	veh/hr	0	0	0	0	321	7	0	I	10	0	11		7	319	0	0
GRADES	G integer %	1	1	1	-4	-4	-4	-4		1	1	1	1	4	4	4	4
PHF	1	92%	92%	92%	92%	92%	92%	92%	1	92%	92%	92%		92%	92%	92%	92%
% HEAVY	integer %	0	0	0	0	0	0	0	1	0	0	0		0	1	0	0
MVMT FLOW	v _i veh/hr	0	0	0	0	349	8	0		11	0	12		8	347	0	0

CONFLICTING FLOW RATES,	V _{c,x}														
MOVEMENTS		12	11	10	-	-	4	4U	9	8	7	-	-	1	10
CONFLICTING FLOW ALL		175	720	539	-	-	355	355	178	716	542	-	-	349	349
CRITICAL HEADWAY, t _{c,x}															
Base Crit HW	t _{cbase}	6.90	-	-	-	-	4.10	6.40	6.90	-	-	-	-	4.10	6.40
Adj for HV	t _{c,HV}	2.00	2.00	2.00	-	-	2.00	2.00	2.00	2.00	2.00	-	-	2.00	2.00
Prop. Of HV	P _{HV}	0.00	0.00	0.00	-	-	0.00	0.00	0.00	0.00	0.00	-	-	0.00	0.00
Adj for Grade	t _{c,G}	0.10	0.20	0.20	-	-	-	-	0.10	0.20	0.20	-	-	-	-
Grades	G	1.00	1.00	1.00	-4.00	-4.00	-4.00	-4.00	1.00	1.00	1.00	4.00	4.00	4.00	4.00
Adj. for Int. Geom	t _{3,LT}	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Critical Headway		7.00	-	-	-	-	4.10	6.40	7.00	-	-	-	-	4.10	6.40

FOLLOW UP HEADWAY, t _{f,x}																
Base Follow up HW	t _{fbase}		3.30	4.00	3.50	-	-	2.20	2.50	3.30	4.00	3.50	-	-	2.20	2.50
Adj for HV	t _{f,HV}		1.00	1.00	1.00	-	-	1.00	1.00	1.00	1.00	1.00	-	-	1.00	1.00
Prop. Of HV	P _{HV}		0.00	0.00	0.00	-	-	0.00	0.00	0.00	0.00	0.00	-	-	0.00	0.00
Follow up Headway	t _{f,x}		3.30	4.00	3.50	-	-	2.20	2.50	3.30	4.00	3.50	-	-	2.20	2.50
POTENTIAL CAPACITY, c _{p,x}																
Potential Cap - 1 Maneuver			841	418	485	-	-	1,215	864	837	420	483	-	-	1,221	872
COMPUTE MOVEMENT CAPAC	CITIES, C _{m,j}															
MOVEMENTS			12	11	10	-	-	4	4U	9	8	7	-	-	1	10
Compute Rank 1 Mov Cap's																
Compute Rank 2 Mov Cap's		Step 7a Step 7b Step 7c	841					1,215	853	837					1,221	872
Compute f _{1U}	1.00000															
Comput 140	0.98686	Step 7d														
Use Eqn 20-42 as the LT and T I not shared.	lanes are															
Compute p _{0,j}	j = 1 or 4															
р _{0,1}	1.00000		р _{0,1U}	1.00000												
μ _{0,4}	0.99342		P0,4U	1.00000												
Compute Rank 3 Mov Cap's Rank 3 One Stage Movement		Step 8a														
f _k	0.99342		(capaci	ity adjustmen	t factor)											
Compute c _{m,k}																
Movement Cap - 2 Maneuver	STAGE 1 STAGE 2			415 610 617							417 619 610					
Rank 3 Two Stage Movement Compute adj factors a and y		Step 8b														
nm	2.00															
C _{II}	Red															
v _L (1 and 1U)	0															
v _L (4 and 4U)	8															
Select max v _L	8															
у				1.00759							1.09278					
Compute Total Cap, C _T (Cap 2 N	/laneuver)			517							518					

Compute Rank 4 Mov Cap's		Step 9a	
P _{0,8} P _{0,11}	1.00000 1.00000		
For Rank 4, Mvmt 7, p'' = From eqn 20-52, p' =		0.99342 0.99498	
For Rank 4, Mvmt 10, p'' = From eqn 20-52, p' =		0.99342 0.99498	
p _{0,9}	0.98686		
p _{0,12}	1.00000		
f _{p,l}		0.99498	0.98190
Compute c _{m,l}			
Movement Cap - 2 Maneuver		483	474
nm	2.00		
a	0.94910		
C_{\parallel}	Red		
v _L (1 and 10)	0		
VL (4 dilu 40)	8		
v	0	0.42512	0.49710
, Compute Total Cap, C _T (Cap 2 Ma	aneuver)	571	569

COMPUTE MOVEMENT CONT	ROL DELAY														
	9	Step 11a													
Compute CD for Rank 2 - Rank	4 Movements														
MOVEMENTS			12	11	10	-	-	4	4U	9	8	7	-	- 1	1U
C _{m,x}	(veh/hr)	Т	841	517	571			1,215	853	837	518	569		1,221	872
d = Control delay (sec/veh)	h	0.25	9.3	12.0	11.3			8.0	9.2	9.3	11.9	11.3		7.9	9.1
v/c Ratio			0.00	0.00	0.00			0.01	0.00	0.01	0.00	0.02		0.00	0.00
HCM LOS			Α	В	В			А	Α	А	В	В		А	А

COMPUTE APPROACH CONTROL DELAY										
d _A (southbound)	#DIV/0!	s/veh			d _A (northbound)	10.36	s/veh			
HCM LOS	#DIV/0!				HCM LOS	В				
COMPUTE 95TH PERCENTILE QUEUE LENGTHS										
Т										
0.25										
Q ₉₅	0.00000	0.00000	0.00000	0.01988	0.00000	0.03993	0.00000	0.06456	0.00000	0.00000





1550 East Republic Road Springfield, MO 65804 tothassociates.com 417.888.0645

COUNCIL BILL EXHIBIT A -ATTACHMENT 3

July 16, 2021

Mr. Garrett Tyson Director of Planning & Development City of Nixa, MO

RE: Walker Property – Traffic Impact Study – Peer Review

Dear Mr. Tyson,

Please accept this letter as our response to select review comments provided in a memo from Mr. Jason Sommerer dated July 13, 2021. Select review comments have been shown in italics for your convenience.

1. The TIS presents findings related to Stopping Sight Distance (SSD). For proposed public road intersections, such as Mandy Lane and Donald Street, Intersection Sight Distance (ISD) – Green Book Section 9.5 – should also be evaluated in addition to SSD. (Section 8 – Sight Distance Review - General Comment)

Refer to the attached ISD/SSD Summary (Exhibit 8), as well as an exhibit created to show Donald Street's provided ISD/SSD (Exhibit 7). The remaining 4 intersection analyses used the same approach as Donald Street. Utilizing the topo survey data, in addition to the recommendations provided in the memo, a more thorough and consistent approach was taken. This results in slightly different values than shown in the original TIS, but overall depicts a complete summary.

 Two of the proposed intersections were discussed in the report (Main Street at Mandy Lane; Tracker Road at Donald Street). The other two proposed intersections should also be discussed. (Main Street at Greenbriar Drive; Tracker Road at Maxine Avenue). (Section 8 – Sight Distance Review - General Comment)

Refer to the attached Exhibit 8, which depicts a summary of all SSD and ISD values.

3. Roadway grade assumptions are noted for each intersection. Were these assumed from visual inspection or measured in some manner. (Section 8.1 – Minimum Sight Distance Review - General Comment)

Initially they were assumed from visual inspection, but upon responding to the comments in the memo, they were measured in a consistent manner based on the survey. Refer to Answer in Comment #1 above.

4. For each driveway, "downgrade" or "upgrade" was not listed. (Section 8.1 – Minimum Sight Distance Review - General Comment)
Refer to the attached Exhibit 8, which depicts upgrade (UG) or downgrade (DG), as applicable.

5. What "height-of-object" and "height-of-eye" was utilized for the sight distance measurements? (Section 8.2 – Stopping Sight Distance Provided - General Comment)

Per the Green Book Section 3.2.6, for both the SSD and ISD, the "height-of-eye" distance utilized for measurements was 3.5 feet. For the SSD, the "height-of-object" distance utilized for measurements was 2.0 feet. For the ISD, the "height-of-object" distance utilized for measurements was 3.5 feet. Refer to the attached Exhibit 7 for an example of how the measurements were made based on survey data.

6. Who will determine if it (tree trimming) is necessary? Who will be responsible for the trimming? (Section 8.3 – Additional Recommendations - General Comment)

These comments will be taken into consideration during the design of the subdivision road plans, but currently the intent would be for the HOA to take responsibility of ensuring safe sight lines at all intersections. The HOA will comply with all applicable City codes and statues in terms of sight line safety and recommendations.

7. Is the assumption that culverts will be installed as part of the property development construction and that the roadway widening will tie into existing ditches? (OPCC - General Comments)

Yes. Culvert costs are not depicted in the attached cost estimate as they will be reflected in the subdivision design documentation.

As a general response to the multiple price recommendations: Noted. Values in the cost estimate were modified per the recommendations in the memo. The revised Opinion of Probable Construction Costs has been attached for reference.

8. Does the City want to tie directly into the intersection, to avoid the short taper in and back out? (OPCC - General Comments)

Based on discussions with the City, the desired approach is to not show any improvements being made to Main Street, as there is a plan in place for the City to make improvements to Main Street in the near future. Part of those improvements include lowering the hill just north of the Walker Woods Subdivision. As opposed to making improvements on Main, the City would prefer that Tracker Road be further improved by widening and milling/overlaying back to the west to where the existing curb and gutter terminates. Refer to the attached revised Exhibit 5 and revised Opinion of Probable Construction Costs that depict these changes.

If you have any additional comments or questions, please don't hesitate to call me at 417-888-0645.

Respectfully,

David Garrett, PE, CFM

Project Manager



KEY NOTES:

- (1) INSTALL TURN LANE IMPROVEMENTS. $\langle 2 \rangle$ PROPOSED INTERSECTION.







EXHIBIT 8 - ISD/SSD SUMMARY

STREET NAME	DIRECTION	APPROX. GRADE	ADJ. NEEDED?	UG/DG/NA	SSD REQ. (FT)	SSD PROV. (FT)	SSD MET?	ISD REQ. (FT)	ISD PROV. (FT)	ISD MET?
DONALD	EAST	6.00%	YES	UG	184	>440	YES	384	>440	YES
DONALD	WEST	3.00%	NO	UG	200	395	YES	335	456	YES
MANDY	NORTH	1.96%	NO	NA	305	345	YES	445	345	NO ²
MANDY	SOUTH	2.43%	NO	NA	305	>500	YES	445	>500	YES
GREENBRIAR	NORTH	1.54%	NO	NA	250	>400	YES	390	>400	YES
GREENBRIAR	SOUTH	0.60%	NO	NA	250	>400	YES	390	>400	YES
MAXINE	EAST	3.00%	NO	UG	205	440	YES	335	440	YES
MAXINE	WEST	3.00%	NO	DG	200	>500	YES	335	>500	YES

NOTES:

 SPEED LIMITS: TRACKER EAST OF MAIN 30 MPH. MAIN NORTH OF TRACKER 40 MPH. MAIN SOUTH OF TRACKER 35 MPH
MANDY NORTH ISD NOT MET BASED ON EXISTING CONDITIONS BUT LIKELY WILL BE MET UPON MAIN STREET IMPROVEMENTS BY CITY DUE TO THE PROPOSED LOWERING OF THE EXISTING TERRAIN FOR THE CONSTRUCTION OF NEW ROADWAY.



TRACKER AND MAIN ROADWAY IMPROVEMENTS

Item	Description	Quantity	Units	Unit Price	Total Cost
1.00	EARTHWORK				
1.01	Clearing and Grubbing	1	LS	\$5,000	\$5,000
1.02	Sawcut and Removal of Existing Pavement	1	LS	\$5,000	\$5,000
1.03	Coldmilling Existing Pavement	200	SY	\$10	\$2,000
1.04	Site Grading - Cut (Unclassified)	700	CY	\$10	\$7,000
1.05	Site Grading - Fill	2,000	CY	\$20	\$40,000
1.06	Sediment and Erosion Control	1.0	LS	\$7,000	\$7,000
1.07	Seed, Fertilizer, and Mulch	1.0	AC	\$4,500	\$4,500
				SUBTOTAL	\$70,500

Item	Description	Quantity	Units	Unit Price	Total Cost
2.00	PAVING AND MISC.				
2.01	6 in. Heavy Duty Asphalt Pavement	11,450	SF	\$3.50	\$40,075
2.02	8 in. Aggregate Base for Heavy Duty Asphalt	11,450	SF	\$1.10	\$12,595
2.03	Asphalt Pavement for Overlay (1.75" Thick)	29,100	SF	\$1.25	\$36,375
2.04	Pavement Markings	1	LS	\$5,000	\$5,000
2.05	Signage	1	LS	\$3,500	\$3,500
2.06	Traffic Control	1	LS	\$10,000	\$10,000
				SUBTOTAL	\$107,545

CONSTRUCTION TOTALS

Construction Total	\$193,045
Construction Contingency (20%)	\$38,700
Mobilization, Demobilization, and Bonding (5%)	\$11,587
Professional Services (23%)	\$56,000
TOTAL	\$299,332

NOTICE:

Opinion of Probable Construction Cost: The services, if any, of Engineer with respect to Opinion of Probable Construction Cost are to be made on the basis of Engineer's experience and qualifications and represent Engineer's best judgement as an experienced and qualified professional generally familiar with the construction industry. However, since Engineer has no control over the cost of labor, materials, equipment, or services furnished by others, or over contractor's methods of determining prices, or over competitive bidding or market conditions, Engineer cannot and does not guarantee that proposals, bids, or actual Construction Cost will not vary from Opinions of Probable Construction Cost prepared by Engineer.